

## OVERVIEW

Unit Level Monitored rPDUs provide reliable power distribution to critical IT equipment while delivering a comprehensive view of input level power usage via remote network access.

### Benefits

- Reliable power distribution with local and remote power monitoring options offer quick access to critical power usage information to evaluate energy usage trends and maximize uptime.
- Fault-Tolerant Daisy Chaining with RSTP simplifies intelligent rPDU connectivity and ensures data is reported even when a break in the network chain occurs.
- Standard 1 year warranty.



## Part #: EP4G90A0

**Model Number:** VC1HBB2A20B4DXX

**Category:** Monitored

**Subcategory:** Unit Level

**Power Configuration:** 32A, 230V, 7.2kW

**Physical Configuration:** 66in / 1683mm, Vertical

**Product Summary:** rPDU, Monitored Unit Level, 32A, 230V, 7.2kW, Vertical, (20) Manual Lock IEC C13, (4) Manual Lock IEC C19, 10ft power cord with 2P+E (IP44), Black Powder Coat.

**Monitoring:** Input power monitoring with breaker level current monitoring. Daisy chain Ethernet connectivity. Local high visibility LED display.

### Plug Form:



1P+N+PE

### Receptacle:



Manual Lock IEC C13  
(Quantity:20)



Manual Lock IEC C19  
(Quantity:4)

### Chassis Color



## Vertiv.com

© 2024 Vertiv Group Corp. All rights reserved. Vertiv™, and the Vertiv logo are trademarks or registered trademarks of Vertiv Group Corp. All other names and logos referred to are trade names, trademarks or registered trademarks of their respective owners. While every precaution has been taken to ensure accuracy and completeness here, Vertiv Group Corp. assumes no responsibility, and disclaims all liability, for damages resulting from use of this information or for any errors or omissions. Specifications, rebates and other promotional offers are subject to change at Vertiv's sole discretion upon notice.

## Product Specification and Options

### System Features

<b>Monitoring</b>	Input power monitoring with breaker level current monitoring. Daisy chain Ethernet connectivity. Local high visibility LED display.
<b>Monitoring Level 1</b>	Phase (A) Monitoring (kWh, W, VA, PF, V, A)  Power Measurements Compliant with ANSI C12.1 and IEC 62053-21 at 1% Accuracy Class Requirements
<b>Monitoring Level 2</b>	Circuit / Breaker Monitoring (A)  Circuit/Breaker Current Measurements Independently Tested and Verified at 2% Accuracy
<b>Quantity Of Inputs</b>	1
<b>Voltage</b>	230V
<b>Current</b>	32A
<b>VA per Input (Load Capacity)</b>	7.2kW
<b>Frequency</b>	50/60Hz
<b>Over Current Protection</b>	(2) 16A Single Pole Magnetic Breakers
<b>Scrolling / Rotatable Digital Display</b>	Yes
<b>Power Cable Wire Gauge</b>	4mm <sup>2</sup> H07RN-F
<b>Power Cable Length</b>	10ft / 3m
<b>Plug Type</b>	IEC60309 2P+E, 32A, 250V, Splash proof IP44
<b>Combined Total Receptacle/Socket Quantity</b>	24
<b>Receptacle/Socket Type #1</b>	Manual Lock IEC C13
- Quantity	20
- Quantity per Breaker	10
- Maximum Output per Receptacle/Socket	10A
- Voltage per Receptacle/Socket	230V
<b>Receptacle/Socket Type #2</b>	Manual Lock IEC C19
- Quantity	4
- Quantity per Breaker	2
- Maximum Output per Receptacle/Socket	16A
- Voltage per Receptacle/Socket	230V

<b>Network Connection</b>	Dual 10/100Mbps Ethernet
<b>Protocols Supported</b>	ARP, IPv4, IPv6, ICMP, ICMPv6, NDP, TCP, UDP, RSTP, STP, DNS, HTTP, HTTPS (TLSv1.3), SMTP, SMTPS, Modbus TCP/IP, DHCP, SNMP (V1/V2c/V3), LDAP, TACACS+, RADIUS, NTP, SSH, and Syslog
<b>Data Access Formats</b>	CSV datalog, JSON API, JSON datalog
<b>IP Reset Button</b>	Yes
<b>Hard Reboot Button</b>	Yes
<b>Maximum Operating Temperature</b>	45°C / 113F
<b>Heavy Steel - Powder Coat Finish</b>	Black
<b>Configuration</b>	0U, Vertical
<b>Toolless mounting HW – Center to Center</b>	1560mm and 1645mm (Vertical mounting bracket included)
<b>Product Warranty</b>	Standard 1 year warranty
<b>Certification/Agency Approvals</b>	CE Marked
<b>Certification/Agency Approvals</b>	FCC Marked
<b>Certification/Agency Approvals</b>	Complies with IEC 62368-1
<b>Certification/Agency Approvals</b>	Complies with EN 55032 and EN 55035
<b>Certification/Agency Approvals</b>	RoHS
<b>Chassis Dimensions (LxWxD)</b>	1683mm x 51mm x 51mm
<b>Shipped Weight</b>	7.5kg