

Delock USB 40 Gbps Cable USB Type-C[™] male to male PD 3.1 240 W E-Marker 1 m grey metal

Description

This USB cable by Delock enables the connection of various devices, such as smart phones, monitors, external enclosures and docking stations, via a USB Type-C[™] or Thunderbolt[™] 3 port of a PC or laptop. The cable supports the transfer of USB as well as DisplayPort and PCI Express data.

USB 40 Gbps

The cable enables data transfer rates up to 40 Gbps when connecting compatible devices. Of course, USB 3.2 or USB 2.0 devices can also be connected.

Connect DisplayPort monitors

The Delock cable supports DisplayPort 1.4a as well as DisplayPort 2.0 Alternate Mode, enabling the connection of DisplayPort monitors with a screen resolution up to 8K 60 Hz.

USB Power Delivery (USB PD 3.1) support up to 240 watt

Support for the Extended Power Range resp. USB Power Delivery 3.1 standard means that connected devices can be supplied with power, up to 240 W (48 V / 5 A) is possible.

Technical details

- Connectors: 2 x USB 40 Gbps USB Type-C[™] male
- Downwards compatible to USB 3.2, USB 2.0 and Thunderbolt™ 3
- Chipset: E-Marker
- Connector with metal housing
- Cable gauge: 24 AWG data line
 - 22 AWG power line
- Contacts gold-plated
- Cable jacket material: TPE



1 m

Item no. 81191

EAN: 4043619811915 Country of origin: China Package: Zip poly bag





- Cable diameter: ca. 5 mm
- Data transfer rate up to 40 Gbps
- Display resolution up to 7680 x 4320 @ 60 Hz
- (depending on the system and the connected hardware)
- Supports HDR10
- Supports HDCP 1.4 and 2.3
- Supports PCI Express 3.0 protocol
- Supports DisplayPort 1.4a protocol
- Supports DisplayPort Alt Mode 2.0
- Dual channel, bi-directional data transfer
- Supports Extended Power Range (EPR)
- USB Power Delivery (USB PD 3.1) support up to 240 watt (48 V / 5 A)
- · Colour: black / grey
- Length incl. connectors: ca. 1 m

System requirements

• USB 40 Gbps cable

Images





General

Specification:	HDCP 1.4
	DisplayPort 1.4
	HDR10
	PCI Express 3.0
	HDCP 2.3
	USB Power Delivery 3.1
	USB 40 Gbps

Interface

Connector 1:	1 x USB Type-C™ male
Connector 2:	1 x USB Type-C™ male

Technical characteristics

Chipset:	E-Marker
Data transfer rate:	40 Gbps
Maximum screen resolution:	7680 x 4320 @ 60 Hz
Maximum power:	240 W
Maximum current:	5 A
Voltage:	20.0 V

Physical characteristics

Pin finishing:	gold-plated
Cable gauge:	22 AWG power line 24 AWG data line
Length:	1 m
Colour:	grey black
Cable diameter:	5 mm
Cable jacket material:	TPE

Herstellerinformation

DATASHEET



Strasse	В
PLZ	1
Ort	В
Land	D
E-Mail	ir
Webseite	W

Beeskowdamm 13/15 14167 Berlin Deutschland nfo@delock.de www.delock.de