

Delock Push Switch for Installation 22 mm 6 x solder connection LED white power symbol + ring

Description

This push switch by Delock is ideal for **installation in control panels**, for example in **industry, control or regulation technology**. Push buttons can also be found in the **automotive industry** or the consumer sector.

Push switch

Unlike a button, a switch remains in its position after being actuated. Examples of switches are toggle switches, rotary switches or slide switches. The light switch is probably the best-known example.

Opener and closer

The NO (closer) contact establishes a connection between two contacts, while the NC (opener) contact releases them.

Note

- The installation should only be carried out by qualified electricians in compliance with the usual national power supply guidelines.
- Earthing is necessary for low-voltage systems to ensure the safety and functionality of the system.



Item no. 22051

EAN: 4043619220519

Country of origin: China

Package: Retail Box

Technical details

- Connectors: 6 x solder connection
- Switch type: 2 NO + 2 NC
- Switching voltage: AC 230 V~ / 3 A
- Number of contacts: 6
- Function: latching
- Actuator: flat
- Operating temperature: -25 °C ~ 55 °C
- Mounting hole diameter: ca. 22 mm
- Hexagon nut spanner width: 25 mm
- Mounting depth: ca. 39 mm
- Thread size: M22

- LED lighting: white
- LED voltage: 12 V
- LED type: power symbol + ring
- Material: stainless steel nickel plated
- Mechanical life: 1,000,000 cycles
- Electrical service life: 100,000 cycles
- Protection class: IP65
- Dimensions (LxD): ca. 40 x 30 mm

Package content

- Push switch

Images



Herstellerinformation

Strasse	Beeskowdamm 13/15
PLZ	14167
Ort	Berlin
Land	Deutschland
E-Mail	info@delock.de
Webseite	www.delock.de