

140W USB-C Wall Charger, 3x USB-C/1x USB-A, PD 3.1 GaN Power Adapter for MacBook, Dell XPS/Inspiron/Precision

Product ID: 3114GCU-WALL-CHARGER



This USB-IF Certified 140W USB-C GaN Charger delivers a versatile, high-power charging solution for USB-C devices, supporting up to 140W with PD 3.1. The package includes .

The USB-IF Certified Power Adapter and included USB-IF Certified USB Type-C cable provide safe and reliable charging solutions. Supporting high-performance USB Power Delivery (PD) 3.1 with Extended Power Range (EPR), this adapter can charge demanding 140W devices, including the MacBook M3 Pro/Max. Its robust design accommodates current laptops like the MacBook Air, Dell XPS, iPad Pro, iPhone, Samsung smartphones, and Google Pixel, while also ensuring future-proof compatibility with next-generation devices.

This USB Wall Charger is engineered for optimal cooling, providing a safer, more reliable charging experience. Balancing compact size with powerful functionality, it features a foldable North American power plug (NEMA 1-15P) for easy storage and delivers fast, efficient charging while maintaining long-lasting performance. At just 10.5 oz (299 g), this travel-friendly adapter combines robust capabilities with easy portability, making it an ideal companion on the go.

Safety and efficiency are paramount with the 140W USB GaN Charger. It is TUV Safety Listed (IEC 62368-1) and FCC/ICES EMC certified, providing protection against over-voltage, current, and temperature. The Active Power Factor Correction (PF > 0.99) enhances efficiency and ensures cool operation. Additionally, it meets DOE Level VI standards, guaranteeing energy efficiency and reliable performance.

Certifications, Reports and Compatibility



Applications

- Ideal for travel with a light weight design and port variation eliminating the need to carry multiple chargers for different devices
- Power laptops and other USB devices in at the office or home office

Features

- **140W USB GaN CHARGER:** USB wall charger with 3x USB-C (140W max, PD 3.1) and 1x USB-A (12W max); Compact travel adapter (10.5 oz/299 g); Charges with multiple PD voltage profiles (5V/9V/12V/15V/20V/28V at up to 5A)
- **INTERNATIONAL TRAVEL READY:** Includes interchangeable power plugs for North America (NEMA 1-15P), United Kingdom (BS 1363P), and Europe (CEE 7/16P), making it perfect for hassle-free global use
- **16" MACBOOK PRO COMPATIBLE:** PD 3.1 Power Adapter fully supports MacBook M3 Pro/Max ensuring high-speed 140W charging; Charges all USB-C devices with earlier PD revisions like MacBook, Dell XPS/Precision/Inspiron, iPad Pro, iPhone & Samsung smartphones
- **COMPACT & COOL RUNNING:** Engineered for cool performance under extended full-load use, with a foldable North American power plug (NEMA 1-15P) that enhances portability and easy storage; Small footprint (2.6 in/6.8cm x 1.2in/3.1cm x 3in/7.8cm)
- **SAFE, RELIABLE & EFFICIENT:** Designed to keep users & devices safe; TUV Safety Listed (IEC 62368-1) & FCC/ICES EMC certified; Over-voltage, current, and temp. protection; Active Power Factor Correction (PF > 0.99); Meets DOE Level VI standards

Hardware

Warranty	2 Years
Number of Power Outlets	4
Industry Standards	USB Power Delivery 3.1

Performance

General Specifications	Total Aggregate Power (C1 + C2 + C3 + A1): 142.0W Max
	USB-C Port #1 Output:
	5.0V3.0A, 9.0V3.0A, 15.0V3.0A, 20.0V5.0A, 28.0V5A (140.0W Max)
	USB-C Ports #2 & 3 (Shared) Output:
	5.0V3.0A, 9.0V3.0A, 15.0V3.0A, 20.0V3.25A (65.0W Max)
	PPS: 3.3-21.0V3.25A (65.0W Max)

USB-A Port Output:
5.0V/2.4A (12.0W Max)

Connector(s)

Input Connector(s)	1 - NEMA 1-15 Power (North America) 1 - BS 1363 Power (UK) Plug 1 - CEE 7/16 Power (Europlug) Plug 1 - AS/NZS 3112 Power (Australia)
Output Connectors	1 - USB Type-C (24 pin) USB Power Delivery Only 1 - USB Type-A (4 pin) Power Only

Power

Input Voltage Frequency	50-60Hz
Input Voltage	100 - 240 AC
Input Current	2.0A
Output Voltage	15V DC 5V DC 9V DC 12V DC 20V DC 28V DC
Output Current	3A (5V, 9V, 12V, 15) / 5A (20V, 28V)
Power Consumption (In Watts)	140 W

Environmental

Operating Temperature	0 to 25C (32 to 77F)
Storage Temperature	-20 to 80C (-4 to 176F)
Humidity	Operation: 10% ~ 90% RH

Storage: 30% ~ 90% RH

Physical Characteristics

Color	Black
Material	Plastic
Product Length	3.8 in [9.6 cm]
Product Width	3.0 in [7.6 cm]
Product Height	1.2 in [3.1 cm]
Weight of Product	12.6 oz [358.0 g]

Packaging Information

Package Length	5.6 in [14.2 cm]
Package Width	6.7 in [17.0 cm]
Package Height	1.4 in [3.5 cm]
Shipping (Package) Weight	1.1 lb [0.5 kg]

What's in the Box

Included in Package	1 - 140W Multiport International Wall Charger
	1 - NA Plug (Installed)
	1 - EU Plug
	1 - UK Plug
	1 - 1 x Plug Storage Bag
	1 - Plug Storage Bag
	1 - QSG

**Product appearance and specifications are subject to change without notice.*