MPN: GLB232006

Triple 4K USB-C Docking Station

This triple-display USB-C dock lets you easily connect two HDMI monitors and one Displayport monitor using one USB-C cable, with no setup or display drivers required, right out of the box.

The stylish alunimium housing combines high performance and flexibility with a wide range of features including up to 100W PD charging, gigabit ethernet with PXE boot and MAC address passthrough, five USB ports to connect devices and card readers.

Featuring MST technology, it's ideal for professionals seeking reliable plug-and-play functionality with ease of use in an office setting.

Max resolution Windows
1 monitor: 8K@30Hz or 4K@144Hz
2 monitors: 4K@60Hz
3 monitors: 2x4K@60Hz + 1 x 4K@30Hz

Please note: Windows based computers support MST mirrored and extended desktop for up to 3 monitors.

Max resolution MacOS
1-2 monitors: 4K@60Hz
3 monitors: 4K@30Hz

Please note: MacOS based computers only support SST mirrored desktop for up to 3 monitors.

- Supports PXE Boot
- Supports MAC Pass-through
- MST dock

Specifications

Battery	Battery Type	NONE - Only use for non-battery items
Network	Ethernet LAN (RJ-45) ports	1
	Ethernet LAN data rates	1000 Mbit/s
Other features	Cable length	1 m
	Cable type	USB-C
Package dimensions	Depth (package,cm)	20.7 cm
	Gross Weight (Package, kg)	0.85 kg
	Height (package,cm)	7.8 cm
	Width (package,cm)	12.1 cm
Packaging content	AC adapter included	Yes
Performance	Built-in SSD	No
	Cable lock slot	Yes
	Cable lock slot type	Kensington
	Card reader integrated	Yes

Performance		
	Compatible memory cards	MicroSDXC, SDXC
	Data transfer rate	10 Gbit/s
	Display modes	Duplicate, Extended
	HD type	8K Ultra HD
	Housing material	Aluminium
	LED indicators	Link, Activity
	Maximum refresh rate	60 Hz
	Number of displays supported	3
	On/off switch	Yes
	Plug and Play	Yes
	Product colour	Aluminium, Black
	Suitable for	Office
Ports & interfaces		
	Combo headphone/mic port	Yes
	Connectivity technology	Wired
	DC-in jack	Yes
	DisplayPort version	1.4
	DisplayPorts quantity	1
	HDCP	Yes
	HDCP version	2.2
	HDMI ports quantity	2
	HDMI version	2.0
	Host interface	USB-C
	USB 2.0 ports quantity	1
	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2
	USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	2
	USB connector type	USB Type-C
	USB Power Delivery (USB PD)	Yes
	USB Power Delivery revision	3.0
	USB Power Delivery up to	100 W
	USB Type-C DisplayPort Alternate Mode	Yes
Power		
	AC input voltage	20 V
	Compatible power plug types	EU
	Input current	7.5 A
	Power connector	DC-in-jack
	Power consumption (max)	150 W
	Power consumption (standby)	0.2 W
	Power plug type	Type C
	Power source type	AC
	Power supply	150 W

Product dimensions		
	Net Weight (Product, kg)	0.752 kg
	Product Depth	16.8 cm
	Product Height	3.3 cm
	Product Width	6.85 cm

Software		
	Mac operating systems supported	Yes
	Other operating systems supported	ChromeOS, Linux
	Windows operating systems supported	Yes

Vendor information		
	Brand Name	eSTUFF
	Warranty	2 Year(s)

Other images