

Statement of Volatility

Dell Pro 27 Plus 4K USB-C Hub Monitor - P2725QE

⚠ CAUTION: A CAUTION indicates either potential damage to hardware or erasure of data and tells you how to avoid the problem.

The P2725QE Monitor contains both volatile and non-volatile components. Volatile components erase their data immediately after power is removed from the component. Non-volatile components continue to retain their data even after power is removed from the component. The following non-volatile components are present on the P2725QE Monitor system board.

Table 1. List of non-volatile components on system board

Description	Reference designator	Volatility description	User accessible for external data	Remedial action (action necessary to erase data)
System EEPROM	U25	Non-Volatile memory, 64 Kbit. For storage system setting.	No	Part place on Interface Board, it has hardware/software write protected.
System Flash ROM	U24	Non-Volatile memory, 32 Mbit. For storage system firmware.	No	Part place on Interface Board, it has hardware/software write protected.
HUB Flash ROM	U1203	Non-Volatile memory, 2 Mbit. For storage HUB firmware.	No	Part place on Interface Board, it has hardware/software write protected.
HUB Flash ROM	U1302	Non-Volatile memory, 2 Mbit. For storage HUB firmware.	No	Part place on Interface Board, it has hardware/software write protected.

⚠ CAUTION: All other components on the system board erase data if power is removed from the system. Primary power loss (unplugging the power cord and removing the battery) destroys all user data on the memory (DDR4, 2667 MHz). Secondary power loss (removing the on-board coin-cell battery) destroys system data on the system configuration and time-of-day information.