

HP EliteBook X G1i 14 inch Notebook Next Gen AI PC



Also available in  
Atmospheric Blue



Front

- |   |                         |   |                |
|---|-------------------------|---|----------------|
| 1 | Internal Microphone (2) | 4 | Camera Shutter |
| 2 | IR Camera               | 5 | Touchpad       |
| 3 | Webcam                  |   |                |





Sides

|   |                                                                                                  |    |                                                                              |
|---|--------------------------------------------------------------------------------------------------|----|------------------------------------------------------------------------------|
| 1 | 1 x HDMI 2.1                                                                                     | 6  | 1 x Nano SIM card slot (optional)                                            |
| 2 | 1 x Thunderbolt™ 4 with USB Type-C® 40Gbps signaling rate (USB Power Delivery, DisplayPort™ 2.1) | 7  | Power Indicator LED                                                          |
| 3 | 1 x Thunderbolt™ 4 with USB Type-C® 40Gbps signaling rate (USB Power Delivery, DisplayPort™ 2.1) | 8  | 1 x USB Type-C® 10Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4) |
| 4 | Power Indicator LED                                                                              | 9  | 1 x USB Type-A 5Gbps signaling rate (Powered)                                |
| 5 | 1 x Headphone/mic combo jack                                                                     | 10 | 1 x Nano Security Slot                                                       |

PRODUCT NAME

HP EliteBook X G1i 14 inch Notebook Next Gen AI PC

OPERATING SYSTEM

- FreeDOS
- Windows 11 Home - HP recommends Windows 11 Pro for business<sup>1</sup>
- Windows 11 Home Single Language - HP recommends Windows 11 Pro for business <sup>1</sup>
- Windows 11 Pro <sup>1</sup>
- Windows 11 Pro Windows 11 Enterprise (Available with a Volume Licensing Agreement)<sup>1</sup>

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows is automatically updated and enabled. High speed internet and Microsoft account required. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com>.

PROCESSORS

| Processor <sup>2,3,4</sup>         | Cores   | Number of P-cores |  | Number of E-cores | Number of LP E-cores | Threads |
|------------------------------------|---------|-------------------|--|-------------------|----------------------|---------|
| Intel® Core™ Ultra7 processor 268V | 8 cores | 4                 |  | N/A               | 4                    | 8       |
| Intel® Core™ Ultra7 processor 266V | 8 cores | 4                 |  | N/A               | 4                    | 8       |
| Intel® Core™ Ultra7 processor 258V | 8 cores | 4                 |  | N/A               | 4                    | 8       |
| Intel® Core™ Ultra7 processor 256V | 8 cores | 4                 |  | N/A               | 4                    | 8       |
| Intel® Core™ Ultra5 processor 238V | 8 cores | 4                 |  | N/A               | 4                    | 8       |
| Intel® Core™ Ultra5 processor 236V | 8 cores | 4                 |  | N/A               | 4                    | 8       |
| Intel® Core™ Ultra5 processor 228V | 8 cores | 4                 |  | N/A               | 4                    | 8       |
| Intel® Core™ Ultra5 processor 226V | 8 cores | 4                 |  | N/A               | 4                    | 8       |

| Processor <sup>2,3,4</sup>         | Smart Cache | Max Turbo Frequency |           | Intel SIPP/vPro® Enterprise | Integrated Graphics | NPU     |
|------------------------------------|-------------|---------------------|-----------|-----------------------------|---------------------|---------|
|                                    |             | P-cores             | LPE-cores |                             |                     |         |
| Intel® Core™ Ultra7 processor 268V | 12 MB       | 5.00 GHz            | 3.70 GHz  | X                           | Intel® Arc™ 140V    | 48 TOPS |

|                                    |       |          |          |   |                  |         |
|------------------------------------|-------|----------|----------|---|------------------|---------|
| Intel® Core™ Ultra7 processor 266V | 12 MB | 5.00 GHz | 3.70 GHz | X | Intel® Arc™ 140V | 48 TOPS |
| Intel® Core™ Ultra7 processor 258V | 12 MB | 4.80 GHz | 3.70 GHz |   | Intel® Arc™ 140V | 47 TOPS |
| Intel® Core™ Ultra7 processor 256V | 12 MB | 4.80 GHz | 3.70 GHz |   | Intel® Arc™ 140V | 47 TOPS |
| Intel® Core™ Ultra5 processor 238V | 8 MB  | 4.70 GHz | 3.50 GHz | X | Intel® Arc™ 130V | 40 TOPS |
| Intel® Core™ Ultra5 processor 236V | 8 MB  | 4.70 GHz | 3.50 GHz | X | Intel® Arc™ 130V | 40 TOPS |
| Intel® Core™ Ultra5 processor 228V | 8 MB  | 4.50 GHz | 3.50 GHz |   | Intel® Arc™ 130V | 40 TOPS |
| Intel® Core™ Ultra5 processor 226V | 8 MB  | 4.50 GHz | 3.50 GHz |   | Intel® Arc™ 130V | 40 TOPS |

Processor Family

- Intel® Core™ Ultra7 processor
- Intel® Core™ Ultra5 processor

- 2. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel’s numbering, branding and/or naming is not a measurement of higher performance.
- 3. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.
- 4. Max Boost clock frequency performance varies depending on hardware, software and overall system configuration.
- 5. In accordance with Microsoft’s support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on <http://www.support.hp.com>.
- 6. Features and software that require a NPU may require software purchase, subscription or enablement by a software or platform provider, and third party software may have specific configuration or compatibility requirements. Performance varies by use, configuration, and other factors.

### GRAPHICS

#### Integrated

Intel® ARC™ Graphics <sup>7</sup>

#### Supported Protocols

Support DX12, HDMI 2.1 (4K/60Hz only), HDCP 2.3

#### Displays supported (including Internal display; dock may be required)

Up to 3

#### Codec

Hardware Acceleration HEVC (H.265) CODEC is supported.

7. Intel® Arc™ graphics only available on select Intel® Core™ Ultra V-series processor-powered systems with at least 16GB of system memory in dual channel configuration.



DISPLAY

Availability may vary by country  
Actual brightness will be lower with touchscreen or HP Sure View.

Non-Touch

35.6 cm (14") diagonal, WUXGA (1920 x 1200), LCD, UWVA, Anti-Glare, Low Blue Light, 800 nits, sRGB 100%, HP Sure View 5<sup>8</sup>  
35.6 cm (14") diagonal, 2.5K (2560 x 1600), LCD, UWVA, 120Hz (VRR), Anti-Glare, WLED + Low Blue Light, 400 nits, DCI-P3 100% + Adobe 100%  
35.6 cm (14") diagonal, WUXGA (1920 x 1200), LCD, UWVA, Anti-Glare, WLED + Low Blue Light, 400 nits, Low power, sRGB 100%

Touch

35.6 cm (14") diagonal, WUXGA (1920 x 1200), LCD, UWVA, Touch, Anti-Glare, Low Blue Light, 800 nits, sRGB 100%, HP Sure View 5<sup>8</sup>  
35.6 cm (14") diagonal, WUXGA (1920 x 1200), LCD, UWVA, Touch, Anti-Glare, WLED, 500 nits, sRGB 100%

Display Size (Diagonal)

35.6 cm (14.0")

Screen to Body Ratio

89.8%

Aspect Ratio

16:10

Max Hinge Open Angle

177±3°

8. HP Sure View integrated privacy screen is an optional feature that must be configured at purchase and is designed to function in landscape orientation.

DOCKING (SOLD SEPARATELY)

|                                                                 |                                                                                                                                                                                                                                                                                                                                  |
|-----------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Docking station model #1                                        | HP Thunderbolt 4 100W G6 Dock                                                                                                                                                                                                                                                                                                    |
| Total number of supported displays (incl. the notebook display) | 4                                                                                                                                                                                                                                                                                                                                |
| Max. resolutions supported                                      | (4) 4K @60Hz*<br>(2) 4K @ 120Hz*<br>(3) QHD @ 120Hz*<br>(1) QHD @ 360Hz*                                                                                                                                                                                                                                                         |
| Dock Connectors                                                 | 1x HDMI 2.1, 2x DisplayPort 1.4, 1x Thunderbolt 4                                                                                                                                                                                                                                                                                |
| HP Quick Connect Support                                        | Yes                                                                                                                                                                                                                                                                                                                              |
| Technical limitations                                           | <b>HP Quick Connect is supported on this platform.</b><br>*Requires DisplayPort 1.4 support with Display Stream Compression (DSC).<br>Bluetooth required for HP Quick Connect. HP Quick Connect available on select HP notebooks. Maximum resolution and display support is dependent on the maximum capability of the notebook. |

Maximum of (4) displays with maximum resolution of 5K@ 30Hz running

Thunderbolt Hosts:  
Maximum resolution possible is dual 8K displays @ 60Hz running Thunderbolt host or running a non-Thunderbolt host in high resolution mode @30Hz Non-Thunderbolt hosts:  
**The highest resolution for dual displays running a non-Thunderbolt host in multi-function mode is**  
(1) 5K dual cable (using both DP ports) +(1) 4K on USB-C DP port Non-Thunderbolt hosts support (3) displays with a maximum resolution of (2) 5K single cable + (1) 4K UHD @ 60 Hz in high resolution mode. In multi-function mode the maximum resolution for (3) displays is (2) 5K single cable @ 30Hz + (1) 4K UHD @ 30Hz.

|                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|--------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Docking station model #2                                           | HP Thunderbolt Dock G4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Total number of supported displays (incl.the notebook)<br>display) | 4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Max.resolutions supported                                          | Quad 4K @60Hz<br>Dual 8K single cable@30 for Thunderbolt hosts or USB-C hosts DisplayPort 1.4 with Display Stream Compression in High-Resolution Mode                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Dock Connectors                                                    | 2x HDMI 2.0, 2x DisplayPort 1.4, 1x Thunderbolt 4, 1x USB-C 3.2 Gen 2 DisplayPort                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Technical limitations                                              | Maximum resolution and display support is dependent on the maximum capability of the notebook.<br><br>Thunderbolt Hosts:<br>Maximum of (4) displays with maximum resolution of 5K@ 30Hz running Thunderbolt host.<br>Maximum resolution possible is dual 8K displays @ 60Hz running Thunderbolt host or running a non-Thunderbolt host in high resolution mode @30Hz<br>Non-Thunderbolt hosts:<br>The highest resolution for dual displays running a non-Thunderbolt host in multi-function mode is<br>(1) 5K dual cable (using both DP ports) +(1) 4K on USB-C DP port<br>Non-Thunderbolt hosts support (3) displays with a maximum resolution of (2) 5K single cable + (1) 4K UHD @ 60 Hz in high resolution mode. In multi-function mode the maximum resolution for (3) displays is (2) 5K single cable @ 30Hz + (1) 4K UHD @ 30Hz. |
| Docking station model #3                                           | HP USB-C Dock G5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Total number of supported displays (incl.the notebook)<br>display) | 3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Max.resolutions supported                                          | Multi-Function Mode: (2) 5k @ 30Hz and (1) 4k UHD @ 30Hz on any port<br>High-Resolution Mode: (2) 5k @ 60Hz on DisplayPort ports and (1) 4k UHD @ 60Hz on HDMI port                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Dock Connectors       | 1x HDMI 2.0, 2x DisplayPort 1.4                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Technical limitations | <p>Maximum resolution and display support is dependent on the maximum capability of the notebook.</p> <p>Highest resolution with dual displays is two 8K@ 60Hz host in High Resolution mode.</p> <p>Three maximum displays supported are two 5K@ 30 Hz on DP ports plus one 4K UHD@ 30 Hz on HDMI in Multi-function mode</p> <p>The highest resolution for a non-Thunderbolt host in Multi-function mode is a single 5K dual cable (using both DP ports) + (1) 4K on HDMI port.</p> |



STORAGE AND DRIVES

All Gen5 SSDs on this system run at Gen4 speed.  
For all SSDs, read and write speeds are an average of the maximum values measured under full load conditions. Actual performance may vary +/- 20%.

Primary Storage

- 2 TB PCIe® Gen5 NVMe™ SSD Value <sup>9</sup>
- 2 TB PCIe® Gen4x4 NVMe™ SSD Three Layer Cell <sup>9</sup>
- 1 TB PCIe® Gen5 NVMe™ SSD Value <sup>9</sup>
- 1 TB PCIe® Gen5x4 NVMe™ Performance Self Encrypted OPAL2 SSD <sup>9</sup>
- 1 TB PCIe® Gen4x4 NVMe™ SSD Three Layer Cell <sup>9</sup>
- 1 TB PCIe® NVMe™ SSD Value <sup>9</sup>
- 512 GB PCIe® Gen5 NVMe™ Self Encrypted OPAL2 SSD Value <sup>9</sup>
- 512 GB PCIe® Gen5 NVMe™ SSD Value <sup>9</sup>
- 512 GB PCIe® Gen4x4 NVMe™ SSD Three Layer Cell <sup>9</sup>
- 512 GB PCIe® Gen4x4 NVMe™ Self Encrypted OPAL2 SSD Three Layer Cell <sup>9</sup>
- 512 GB PCIe® NVMe™ SSD Value <sup>9</sup>
- 256 GB PCIe® NVMe™ SSD Value <sup>9</sup>

9. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 32 GB is reserved for system recovery software.

### MEMORY

#### Maximum Memory

32GB LPDDR5X- 8533 MT/s

#### Memory

32GB LPDDR5X- 8533 MT/s

16GB LPDDR5X- 8533 MT/s

#### Memory Slots

No memory slots. Memory on package.

System runs at 8533 MT/s

Supports Dual Channel Memory.

The memory is non-accessible / non-upgradeable.



### NETWORKING / COMMUNICATIONS

Optional feature.

#### WLAN

Intel® BE201 Wi-Fi 7 Bluetooth® 5.4 vPro WW WLAN <sup>10</sup>

Intel® BE201 Wi-Fi 7 Bluetooth® 5.4 non-vPro WW WLAN <sup>10</sup>

#### WWAN

MediaTek T700 5G NR WWAN <sup>11</sup>

MediaTek T700 5G NR with HP Go WWAN <sup>11</sup>

MediaTek T700 4G LTE-Advanced Pro WWAN <sup>12</sup>

#### LPWAN

Qualcomm 9205 LTE-M (CAT-M1 fSVC) <sup>13</sup>

#### NFC (optional)

NFC Mirage WNC XRAV-1

#### Miracast

Native Miracast Support <sup>14</sup>

10. Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 7 (802.11BE) functionality requires compatible Windows OS, select Intel® processor, and a Wi-Fi 7 router, sold separately. Wi-Fi 7 is backwards compatible with prior 802.11 specs. Available in countries where Wi-Fi 7 is supported. The specification for 802.11BE is a draft specification and is not final. If the final specification differs from the draft specification, it may affect the ability of the device to communicate with other 802.11BE devices.

11. 5G module is optional. WWAN-ready configuration must be selected at purchase to add WWAN module at a later date (WWAN After Market Option Kit). Module designed for 5G NR SA(standalone) and 5G NR NSA (non-standalone) Public and Private networks including Evolved-Universal Terrestrial Radio Access New Radio Dual Connectivity (ENDC) with both 100Mhz of 5G NR and LTE channel bandwidth, using 256QAM 4x4 as defined by 3GPP. Module includes embedded eSIM. Module requires activation and separately purchased service contract. Check with service provider for coverage and availability in your area. Data connection, upload and download speeds will vary due to network, location, environment, network conditions, and other factors. Backwards compatible to 4G LTE and 3G HSPA technologies. 5G module planned to be available in select platforms and select countries, where



carrier and frequency bands supported.

12. 4G module is optional. WWAN-ready configuration must be selected at purchase to add WWAN at a later date. Check with service provider for coverage and availability in your area. Connection, upload and download speeds will vary due to network, location, environment, network conditions, and other factors. 4G LTE not available on all products, in all regions.

13. Cat M1 LPWAN (Mobile Narrowband) cards support select platforms with the HP Protect & Trace with Wolf Connect service, but do not support mobile broadband/Internet use.

14. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming.



---

### AUDIO/MULTIMEDIA

Select product only (Privacy panel SKU).

#### Audio

Audio by Poly Studio

4 Integrated stereo speakers

Discrete Amplifiers

2 Integrated dual array microphone

#### Speaker Power

1W / 8 ohm per speaker

#### Camera

5MP camera with Image Signal Processing (ISP) and AI Presence Detection, IR camera

#### Sensors

Ambient Light Sensor

Color Sensor with Ambient Light Sensing

Fingerprint Sensor (optional)

Gyroscope

Hall Effect Sensor

Inertial Measurement Unit Sensor

Thermal Sensor



---

### KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

#### Keyboard

HP Premium Keyboard, spill-resistant, Backlit, Durakey keyboard.

HP Premium Keyboard, spill-resistant, Privacy, Backlit, Durakey keyboard

#### Pointing Device

Clickpad

Microsoft Precision Touchpad Default Gestures Support

Multi-touch gesture support

#### Function Keys

Copilot+ in Windows requires Windows 11. Some features require an NPU. Timing of feature delivery and availability varies by market and device. Requires Microsoft account to log in. Where Microsoft in Windows is not available, the Copilot key will lead to the Bing search engine. See [aka.ms/copilotpluspcs](https://aka.ms/copilotpluspcs)

ESC - System information

F1 - Display Switching

F2 - Blank or Privacy

F3 - Brightness Down

F4 - Brightness Up

F5 - Keyboard Backlight

F6 - Audio Mute

F7 - Volume Down

F8 - Volume Up

F9 - Mic Mute

F10 - Play and Pause

F11 - Programmable key

F12 - HOME

End

Insert

Delete



Power Button (with LED)

Microsoft Copilot

### Hidden Function Keys

Fn+R - Break, Fn+S - Sys Rq, Fn+C - Scroll Lock



---

### SOFTWARE AND SECURITY

#### Application Software

Buy Microsoft Office (Sold Separately )

Edge Customization

HP AI Companion

HP Connection Optimizer

HP Hotkey Support

HP Mac Address Manager

HP Notifications

HP PC Hardware Diagnostics UEFI

HP PC Hardware Diagnostics Windows

HP Privacy Settings

HP Services Scan <sup>15</sup>

HP Smart Support <sup>16</sup>

HP Support Assistant <sup>17</sup>

HSA Fusion for Commercial

HSA Telemetry for Commercial

myHP <sup>18</sup>

Poly Camera Pro

Poly Lens <sup>19</sup>

#### Manageability Features

HP Client Catalog ([download](#)) <sup>20</sup>

HP Client Management Script Library ([download](#)) <sup>21</sup>

HP Cloud Recovery <sup>22</sup>

HP Connect for Microsoft Endpoint Manager <sup>23</sup>

HP Driver Packs ([download](#)) <sup>24</sup>

HP Image Assistant ([download](#)) <sup>25</sup>

HP Manageability Integration Kit ([download](#)) <sup>26</sup>

HP Power Manager with Battery Health Manager ([download](#)) <sup>27</sup>



### Security Management

Secured-Core PC Enable <sup>28</sup>

Windows Hello Enhanced Sign-In Security (ESS)

HP Wolf Security for Business which includes: <sup>29</sup>

HP Sure Admin <sup>30</sup>

HP Sure Click <sup>31</sup>

HP Sure Recover <sup>32</sup>

HP Sure Run <sup>33</sup>

HP Sure Sense <sup>34</sup>

HP Sure Start <sup>35</sup>

HP Tamper Lock <sup>36</sup>

### Security- TPM

Model: Nuvoton NPCT760HABYX

TCG TPM 2.0

Firmware Version: 7.2.4.0

FIPS 140-2 Compliant: Yes

### BIOS

Absolute Persistence Module <sup>37</sup>

Audio Permanent Disable

BIOS Update via Network

HP BIOS Recovery

HP BIOSphere-<sup>38</sup>

HP DriveLock & Automatic DriveLock

HP Fingerprint Sensor <sup>39</sup>

HP Secure Erase <sup>40</sup>

HP Wake on WLAN

### IPv6 Support

Yes



**FirstNet Certified**

Yes

**Does the BIOS implement the ISO/IEC 19678:2015 (formerly NIST 800-147) guidelines?:** Yes**UEFI version:** 2.7b

HP BIOS UEFI Specification Level version 2.9 supported with BIOS update

**Class:** 3

15. HP Services Scan is preinstalled and/or provided thru Windows Update and checks for service entitlement on each hardware device and downloads the HP Insights agent automatically. To disable this feature, please follow the instructions at <http://www.hpdaas.com/requirements>. The HP Insights agent is a telemetry and analytics platform that provides critical data around devices and applications and is not sold as a standalone service. Select HP Workforce Solutions require an HP Insights agent for Windows, Mac, & Android, available for download at <https://admin.hp.com/software>. For full system requirements and services that require the agent, please visit <https://admin.hp.com/requirements>. The agent collects telemetry and analytics around devices and applications that integrate into the Workforce Experience platform and is not sold as a standalone service. Internet access with connection to the Workforce Experience platform is required. HP follows stringent GDPR privacy regulations, and the platform is ISO27001, ISO27701, ISO27017 and SOC2 Type2 certified for Information Security. Not available in China.

16. HP Smart Support requires the HP Insights agent to be installed. For more information about how to enable or to download HP Smart Support, please visit <http://www.hp.com/smart-support>. HP Services Scan is preinstalled and/or provided thru Windows Update and will check entitlement on each hardware device to determine if an HP Insights agent-enabled service has been purchased, and will download applicable software automatically. HP Insights agent is a telemetry and analytics platform that provides critical data around devices and applications and is not sold as a standalone service. HP follows stringent GDPR privacy regulations and is ISO27001, ISO27701, ISO27017 and SOC2 Type2 certified for Information Security. Internet access is required. For full system requirements or to disable this feature, please visit <https://www.hpdaas.com/requirements>.

17. HP Support Assistant is available on Windows. For more information, please visit <http://www.support.hp.com/help/hp-support-assistant>.

18. MyHP requires Windows 10 or higher OS.

19. Poly Lens Desktop requires a Windows OS.

20. HP Client Catalog not preinstalled, however available for download at (<https://www.hp.com/us-en/solutions/client-management-solutions.html>)

21. HP Client Management Script Library (<https://www.hp.com/us-en/solutions/client-management->



[solutions.html#tab=manageability-tools](#)).

22. HP Cloud Recovery is available for Z by HP, HP Elite and Pro desktops and laptops PCs with Intel® or AMD processors and requires an open, network connection. **NOTE:** You must back up important files, data, photos, videos, etc. before use to avoid loss of data. Detail please refer to: <https://support.hp.com/us-en/computer>.

23. HP Connect for Microsoft Endpoint Manager is available from the Azure Market Place for HP Pro, Elite, Z and Point-of-Sale PCs managed with Microsoft Endpoint Manager. Subscription to Microsoft Endpoint Manager required and sold separately. Network connection required.

24. HP Driver Packs not preinstalled, however available for download at <http://www.hp.com/go/clientmanagement>.

25. HP Image Assistant not preinstalled, however available for download at <https://ftp.ext.hp.com/pub/caps-softpaq/cmit/HPIA.html>

26. HP Manageability Integration Kit not presintalled, however available for downloaded from <https://www.hp.com/us-en/solutions/client-management-solutions.html#tab=manageability-tools>.

27. HP Power Manager with Battery Health can be downloaded by entering your system information here:[https://support.hp.com/in-en/document/ish\\_4449597-3519507-16](https://support.hp.com/in-en/document/ish_4449597-3519507-16)

28. Secured-Core PC Enable requires an Intel® vPro®, AMD Ryzen™ Pro processor or Qualcomm® processor with SD850 or higher and requires 8 GB or more system memory. Secured-core PC is enabled from the factory.

29. HP Wolf Security for Business requires Windows 10 or 11 Pro or higher, includes various HP security features and is available on HP Pro, Elite, RPOS and Workstation products. See product details for included security features.

30. HP Sure Admin requires HP G8 or newer platforms, Windows 10 or higher, HP BIOS, HP Manageability Kit or KMS Service from <http://www.hp.com/go/clientmanagement> and HP Sure Admin Local Access Authenticator smartphone app from the Android or Apple store.

31. HP Sure Click requires Windows 10 and higher. See [https://bit.ly/2PrLT6A\\_SureClick](https://bit.ly/2PrLT6A_SureClick) for complete details.

32. HP Sure Recover is available on select HP PCs and requires Windows 10 or 11 and an open network connection. You must back up important files, data, photos, videos, etc. before using HP Sure Recover to avoid loss of data. HP Sure Recover Gen6 with Embedded Reimaging is an optional feature on select HP PCs which requires Windows 10 or 11 must be configured at purchase. You must back up important files, data, photos, videos, etc. before use to avoid loss of data.

33. HP Sure Run is available on select HP PCs and requires Windows 10 and higher.

34. HP Sure Sense requires Windows 10 and higher. See product specifications for availability. On units with WWAN shipping to China, HP Sure Sense is only available via Softpaq download.

35. HP Sure Start is available on select HP PCs and requires Windows 10 and higher.

36. HP Tamper Lock must be enabled by the customer or your administrator.

37. Absolute Persistence firmware module is shipped turned off and can only be activated with the purchase a license subscription and full activation of the software agent. License subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. Certain conditions apply. For full details visit:



<https://www.absolute.com/about/legal/agreements/absolute/>

38. HP BIOSphere features may vary depending on the platform and configuration.

39. HP Fingerprint Reader is an optional feature that requires Windows 10 or 11 and must be configured at purchase.

40. HP Secure Erase implements the methods outlined in the National Institute of Standards and Technology Special Publication 800-88r "Clear" sanitation method. HP Secure Erase does not support platforms with Intel® Optane™.



### POWER

Power supply availability may vary by country.

Battery is internal and not replaceable by customer. Serviceable by warranty.

#### Power Supply

HP 100W Slim USB Type-C® AC power adapter

HP 65W Standard USB Type-C® AC power adapter

HP 65W USB Type-C® Gallium Nitride AC power adapter

HP 65W Slim USB Type-C® AC power adapter

HP 65W Standard USB Type-C® Halogen Free AC power adapter

#### Battery

HP Long Life 6 cell, 68Whr Polymer

HP Long Life 3 cell, 56Whr Polymer

#### Battery Recharge Time

Supports battery HP Fast Charge: approximately 50% in 30 minutes <sup>41</sup>

#### Power Cord

3-wired plug- 1.0m

#### Battery life

Up to 24 hours 30 minutes with 68Whr battery (Intel Ultra 7 vPro, UMA graphic, brightness set to 250nits on a WUXGA 400nits LCD display, 16GB LPDDR5x memory, 256GB SSD) <sup>42</sup>

Up to 19 hours 30 minutes with 56Whr battery (Intel Ultra 7 vPro, UMA graphic, brightness set to 250nits on a WUXGA 400nits LCD display, 16GB LPDDR5x memory, 256GB SSD) <sup>42</sup>

41. Recharges your battery up to 50% within 30 minutes when the system is off or in standby mode.

Power adapter minimum of 65 watts required for battery capacities 56Whr or less.

Power adapter minimum of 100 watts required for battery capacities greater than 56Whr and less than 83Whr.

Power adapter minimum of 120 watts required for battery capacities greater than 83Whr and less than 100Whr.

After charging has reached 50% capacity, charging will return to normal. Charging time may vary +/-10% due to System tolerance."

42. MobileMark 25 battery life will vary depending on various factors including product model, configuration, loaded applications,



---

features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See [www.bapco.com](http://www.bapco.com) for additional details.



### WEIGHT & DIMENSIONS

#### Product Weight

Starting at 1.18 kg (2.6 lb) with 56.00 Wh battery

Weight will vary by configuration. Does not include power adapter.

#### Product Dimensions (w x d x h) <sup>43</sup>

313.9 mm (W) x 219.90 mm (D) x 10.50 mm (front)/ 14.90 mm (rear) (12.36 in (W) x 8.66 in (D) x 0.41 in (front)/ 0.59 in (rear))

Maximum height 17.55 mm (0.69 in)

#### Packaging and Pallet Dimensions

Product packaging size varies based on options chosen. Please contact your HP representative for your packaging size details. For detailed packaging information, access the [HP Commercial Notebooks Packaging Guide](#).



---

### PORTS/SLOTS

#### Left side

- 2 x Thunderbolt™ 4 with USB Type-C® 40Gbps signaling rate (USB Power Delivery, DisplayPort™ 2.1) <sup>44</sup>
- 1 x HDMI 2.1
- 1 x Headphone/mic combo jack

#### Right side

- 1 x USB Type-C® 10Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4)
- 1 x USB Type-A 5Gbps signaling rate (Powered)
- 1 x Nano SIM card slot (optional)
- 1 x Nano Security Slot

<sup>44</sup>. USB 20Gbps signaling rate is not available with Thunderbolt™ 4. Actual throughput may vary.



#### ENVIRONMENTAL DATA

| <b>Eco-Label Certifications &amp; declarations</b>                                                            | <p>This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:</p> <ul style="list-style-type: none"> <li>• IT ECO declaration</li> <li>• US ENERGY STAR®</li> <li>• US Federal Energy Management Program (FEMP)</li> <li>• EPEAT® Gold registered in the United States. See <a href="http://www.epeat.net">http://www.epeat.net</a> for registration status in your country.</li> <li>• TCO Certified</li> <li>• China Energy Conservation Program (CECP)</li> <li>• China State Environmental Protection Administration (SEPA)</li> <li>• Taiwan Green Mark</li> <li>• Korea Eco-label</li> <li>• Japan PC Green label*</li> </ul>                                                                                                                                                                  |              |              |  |              |              |              |                              |        |        |        |                              |     |     |     |       |        |        |        |     |        |        |        |
|---------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|--------------|--|--------------|--------------|--------------|------------------------------|--------|--------|--------|------------------------------|-----|-----|-----|-------|--------|--------|--------|-----|--------|--------|--------|
| <b>Sustainable Impact Specifications</b>                                                                      | <ul style="list-style-type: none"> <li>• <a href="#">Product Carbon Footprint</a></li> <li>• At least 50% ocean bound plastic in the (CPU Fan)<sup>1</sup> and 30% ocean bound plastic in the (Speaker)<sup>1</sup></li> <li>• At least 35% post-consumer recycled plastic<sup>2</sup></li> <li>• At least 90% recycled metal<sup>3</sup></li> <li>• Low Halogen<sup>4</sup></li> <li>• 100% of HP paper-based packaging is from recycled or certified sustainable sources<sup>5</sup></li> <li>• Bulk packaging available</li> </ul>                                                                                                                                                                                                                                                                                                                                                      |              |              |  |              |              |              |                              |        |        |        |                              |     |     |     |       |        |        |        |     |        |        |        |
| <b>System Configuration</b><br><br><b>Energy Consumption (in accordance with US ENERGY STAR® test method)</b> | <p>The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a “Typically Configured Notebook”.</p> <table> <tr> <th></th><th>115VAC, 60Hz</th><th>230VAC, 50Hz</th><th>100VAC, 50Hz</th></tr> <tr> <td>Normal Operation (Sort idle)</td><td>5.87 W</td><td>6.20 W</td><td>6.00 W</td></tr> <tr> <td>Normal Operation (Long idle)</td><td>N/A</td><td>N/A</td><td>N/A</td></tr> <tr> <td>Sleep</td><td>0.75 W</td><td>0.81 W</td><td>0.74 W</td></tr> <tr> <td>Off</td><td>0.27 W</td><td>0.32 W</td><td>0.26 W</td></tr> </table> <p><b>NOTE:</b> Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for</p> |              |              |  | 115VAC, 60Hz | 230VAC, 50Hz | 100VAC, 50Hz | Normal Operation (Sort idle) | 5.87 W | 6.20 W | 6.00 W | Normal Operation (Long idle) | N/A | N/A | N/A | Sleep | 0.75 W | 0.81 W | 0.74 W | Off | 0.27 W | 0.32 W | 0.26 W |
|                                                                                                               | 115VAC, 60Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 230VAC, 50Hz | 100VAC, 50Hz |  |              |              |              |                              |        |        |        |                              |     |     |     |       |        |        |        |     |        |        |        |
| Normal Operation (Sort idle)                                                                                  | 5.87 W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 6.20 W       | 6.00 W       |  |              |              |              |                              |        |        |        |                              |     |     |     |       |        |        |        |     |        |        |        |
| Normal Operation (Long idle)                                                                                  | N/A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | N/A          | N/A          |  |              |              |              |                              |        |        |        |                              |     |     |     |       |        |        |        |     |        |        |        |
| Sleep                                                                                                         | 0.75 W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 0.81 W       | 0.74 W       |  |              |              |              |                              |        |        |        |                              |     |     |     |       |        |        |        |     |        |        |        |
| Off                                                                                                           | 0.27 W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 0.32 W       | 0.26 W       |  |              |              |              |                              |        |        |        |                              |     |     |     |       |        |        |        |     |        |        |        |



|                                                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                 |              |
|---------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|--------------|
|                                                                           | computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                 |              |
| Heat Dissipation*                                                         | 115VAC, 60Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 230VAC, 50Hz                                    | 100VAC, 50Hz |
| Normal Operation (Short idle)                                             | 20 BTU/hr                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 21 BTU/hr                                       | 21 BTU/hr    |
| Normal Operation (Long idle)                                              | N/A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | N/A                                             | N/A          |
| Sleep                                                                     | 3 BTU/hr                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 3 BTU/hr                                        | 3 BTU/hr     |
| Off                                                                       | 1 BTU/hr                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 1 BTU/hr                                        | 1 BTU/hr     |
|                                                                           | *NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                 |              |
| Declared Noise Emissions<br>(in accordance with<br>ISO 7779 and ISO 9296) | Sound Power<br>(L <sub>WAd</sub> , bels)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Sound Pressure<br>(L <sub>pAm</sub> , decibels) |              |
| Typically Configured – Idle                                               | 2.6                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 13.3                                            |              |
| Fixed Disk – Random writes                                                | 3.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 19.5                                            |              |
| Optical Drive – Sequential reads                                          | N/A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | N/A                                             |              |
| Longevity and Upgrading                                                   | This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the<br><br>Spare parts are available throughout the warranty period and or for up to “5” years after the end of production.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                 |              |
| Additional Information                                                    | <ul style="list-style-type: none"><li>• This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.</li><li>• This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.</li><li>• This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).</li><li>• This product is in compliance with the IEEE 1680 (EPEAT) standard at the Gold level, see www.epeat.net</li><li>• Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.</li><li>• This product is 92.9% recycle-able when properly disposed of at end of life.</li></ul> |                                                 |              |
| Packaging Materials                                                       | External:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | PAPER/Corrugated                                | 255 g        |



|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                   |      |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|------|
|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | PAPER/Molded Pulp | 90 g |
|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | PAPER/Paper       | 24 g |
|                        | The plastic packaging material contains at least 0.00% recycled content.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                   |      |
|                        | The corrugated paper packaging materials contains at least 54.5% recycled content.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                   |      |
| <b>RoHS Compliance</b> | <p>HP Inc. complies fully with materials regulations. We were among the first companies to extend the restrictions in the European Union (EU) Restriction of Hazardous Substances (RoHS) Directive to our products worldwide through the HP GSE. HP has contributed to the development of related legislation in Europe, as well as China, India, and Vietnam.</p> <p>We believe the RoHS directive and similar laws play an important role in promoting industry-wide elimination of substances of concern. We have supported the inclusion of additional substances—including PVC, BFRs, and certain phthalates—in future RoHS legislation that pertains to electrical and electronics products.</p> <p>We met our voluntary objective to achieve worldwide compliance with the new EU RoHS requirements for virtually all relevant products by July 2013, and we will continue to extend the scope of the commitment to include further restricted substances as regulations continue to evolve.</p> <p>To obtain a copy of the HP RoHS Compliance Statement, see <a href="#">HP RoHS position statement</a>.</p> |                   |      |
| <b>Material Usage</b>  | <p>This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at <a href="https://h20195.www2.hp.com/v2/GetDocument.aspx?docname=c05998906">https://h20195.www2.hp.com/v2/GetDocument.aspx?docname=c05998906</a>):</p> <ul style="list-style-type: none"> <li>• Asbestos</li> <li>• Certain Azo Colorants</li> <li>• Certain Brominated Flame Retardants - may not be used as flame retardants in plastics</li> <li>• Cadmium</li> <li>• Chlorinated Hydrocarbons</li> <li>• Chlorinated Paraffins</li> <li>• Bis(2-Ethylhexyl) phthalate (DEHP)</li> <li>• Benzyl butyl phthalate (BBP)</li> <li>• Dibutyl phthalate (DBP)</li> <li>• Diisobutyl phthalate (DIBP)</li> <li>• Formaldehyde</li> </ul>                                                                                                                                                                                                                                                                                                                   |                   |      |



|                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                             | <ul style="list-style-type: none"> <li>• Halogenated Diphenyl Methanes</li> <li>• Lead carbonates and sulfates</li> <li>• Lead and Lead compounds</li> <li>• Mercuric Oxide Batteries</li> <li>• Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.</li> <li>• Ozone Depleting Substances</li> <li>• Polybrominated Biphenyls (PBBs)</li> <li>• Polybrominated Biphenyl Ethers (PBBEs)</li> <li>• Polybrominated Biphenyl Oxides (PBBOs)</li> <li>• Polychlorinated Biphenyl (PCB)</li> <li>• Polychlorinated Terphenyls (PCT)</li> <li>• Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.</li> <li>• Radioactive Substances</li> <li>• Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)</li> </ul> |
| <b>Packaging Usage</b>                      | <p>HP follows these guidelines to decrease the environmental impact of product packaging:</p> <ul style="list-style-type: none"> <li>• Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.</li> <li>• Eliminate the use of ozone-depleting substances (ODS) in packaging materials.</li> <li>• Design packaging materials for ease of disassembly.</li> <li>• Maximize the use of post-consumer recycled content materials in packaging materials.</li> <li>• Use readily recyclable packaging materials such as paper and corrugated materials.</li> <li>• Reduce size and weight of packages to improve transportation fuel efficiency.</li> <li>• Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.</li> </ul>                                                                          |
| <b>End-of-life Management and Recycling</b> | <p>HP offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to:</p> <p><a href="https://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c05403198">https://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c05403198</a> or contact your nearest HP sales office. Products returned to HP will be recycled,</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |



|                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|-----------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                     | <p>recovered or disposed of in a responsible manner.</p> <p>The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <a href="#">HP Product Disassembly Instruction Website</a>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>HP, Inc. Corporate Environmental Information</b> | <p>For more information about HP's commitment to the environment:</p> <ul style="list-style-type: none"> <li>• Sustainable Impact Report <ul style="list-style-type: none"> <li>◦ <a href="https://h20195.www2.hp.com/v2/GetDocument.aspx?docname=c06040843">https://h20195.www2.hp.com/v2/GetDocument.aspx?docname=c06040843</a></li> </ul> </li> <li>• Eco-label certifications <ul style="list-style-type: none"> <li>◦ <a href="https://www.hp.com/us-en/sustainable-impact/document-reports.html#filters_documents_reports=document_type-type_energy_star,type_epeat,type_tcoISO">https://www.hp.com/us-en/sustainable-impact/document-reports.html#filters_documents_reports=document_type-type_energy_star,type_epeat,type_tcoISO</a></li> </ul> </li> <li>• ISO 14001 certificates <ul style="list-style-type: none"> <li>◦ <a href="https://h20195.www2.hp.com/v2/GetDocument.aspx?docname=c04777932">https://h20195.www2.hp.com/v2/GetDocument.aspx?docname=c04777932</a></li> </ul> </li> </ul>                                                                                                                                                                                                                                                                         |
| <b>footnotes</b>                                    | <ol style="list-style-type: none"> <li>1. Percentage of ocean-bound plastic contained in each component varies by product. Ocean Bound plastic is expressed as a percentage of the total weight plastic. Ocean Bound plastic is based on the definition set by the UL2809 standard.</li> <li>2. Recycled plastic is expressed as a percentage of the total weight plastic. Post-consumer recycled is based on the definition set in the EPEAT standard for computers, IEEE 1680.1-2018 standard.</li> <li>3. Recycled metal is expressed as a percentage of the total weight of the metal according to ISO 14021 definitions for metal parts over 25 grams.</li> <li>4. External power supplies, WWAN modules, power cords, cables and peripherals excluded. Service parts obtained after purchase may not be Low Halogen.</li> <li>5. HP paper and fiber-based packaging for PCs, displays, home and office print, and supplies is reported by suppliers as recycled or certified, with a minimum of 97% by volume verified by HP. Packaging is the box that comes with the product and all paper-based materials inside the box. Packaging for personal systems accessories and spare parts is not included. Plastic cushions are made from &gt;90% recycled plastic.</li> </ol> |



---

### SERVICE AND SUPPORT

1-year warranty and 90 day software limited warranty options depending on country. Batteries have a default one year limited warranty. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/cpc> <sup>45</sup>

45. HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit <http://www.hp.com/go/cpc>. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

---



SYSTEM UNIT

Stand-Alone Power Requirements (AC  
Power)

|                           |                       |
|---------------------------|-----------------------|
| Nominal Operating Voltage | 20.0V                 |
| Max Operating Power       | UMA 65W<br>Discrete W |

Temperature

|               |                                                                                                     |
|---------------|-----------------------------------------------------------------------------------------------------|
| Operating     | Operating: 0° to 35° C (32° to 95° F) System performance may be reduced above 32°C (89.6°F)         |
| Non-operating | Non-operating: -20° to 60° C ( -4° to 140° F) System performance may be reduced above 32°C (89.6°F) |

Relative Humidity

|               |                                                                            |
|---------------|----------------------------------------------------------------------------|
| Operating     | Operating: 10% to 90 % (non-condensing)                                    |
| Non-operating | Non-operating: 5% to 95 %, 38.7° C (101.6° F) maximum wet bulb temperature |

Shock

|               |                                       |
|---------------|---------------------------------------|
| Operating     | Operating: 40 G, 2 ms, half-sine      |
| Non-operating | Non-operating: 240 G, 2 ms, half-sine |

Random Vibration

|               |                           |
|---------------|---------------------------|
| Operating     | Operating: 1.043 grms     |
| Non-operating | Non-operating: 3.500 grms |

Altitude (unpressurized)

|               |                    |
|---------------|--------------------|
| Operating     | 3048 m (10000 ft)  |
| Non-operating | 12192 m (40000 ft) |

Planned Industry Standard Certifications

|                         |                   |
|-------------------------|-------------------|
| Regulatory Model Number | HSN-I60C          |
| CSA/UL 62368-1          | Yes               |
| ENERGY STAR®            | Yes <sup>46</sup> |
| FCC/ICES/CISPR/VCCI     | Yes               |
| CE MARKING              | Yes               |
| GS Mark                 | No                |
| China CCC/SRRC          | Yes               |
| Taiwan BSMI/NCC         | Yes               |
| Korea KCC/KC/KES        | Yes               |



|                                                   |                                                |
|---------------------------------------------------|------------------------------------------------|
| Ukraine NSoC/TEC                                  | Yes                                            |
| EAEU Compliance                                   | Yes                                            |
| Saudi Arabian Compliance                          | Yes                                            |
| TCO                                               | Yes                                            |
| EPEAT®                                            | EPEAT® Gold in the United States <sup>47</sup> |
| Low Blue Light                                    | Yes                                            |
| WW RoHS                                           | Yes                                            |
| CECP                                              | Yes                                            |
| Medical EMC: IEC 60601-1-2:2014 EN60601-1-2: 2015 | Yes                                            |
| MIL-STD Testing                                   | MIL-STD 810H <sup>48</sup>                     |

46. Configurations that are ENERGY STAR® qualified are identified as ENERGY STAR on HP websites and on <http://www.energystar.gov>

47. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. EPEAT® status varies by country. Visit <http://www.epeat.net> for more information.

48. MIL STD 810H testing is not intended to demonstrate fitness for U.S. Department of Defense contract requirements or for military use. Test results are not a guarantee of future performance under these test conditions. Accidental damage requires an optional HP Accidental Damage Protection Care Pack.

DISPLAYS

|                                                                                                                                                  |                                                             |                         |
|--------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------|-------------------------|
| 35.6 cm (14") diagonal,<br>WUXGA (1920 x 1200), LCD,<br>UWVA, Anti-Glare, Low Blue<br>Light, 800 nits, sRGB 100%,<br>HP Sure View 5 <sup>1</sup> | Outline Dimensions (W x H)                                  | 306.890 x 197.900 (max) |
|                                                                                                                                                  | Active Area                                                 | 301.590 X 188.500 (typ) |
|                                                                                                                                                  | Weight                                                      | 260 (max)               |
|                                                                                                                                                  | Diagonal Size                                               | 14                      |
|                                                                                                                                                  | Surface Treatment                                           | Anti-Glare              |
|                                                                                                                                                  | Touch Enabled                                               | No                      |
|                                                                                                                                                  | Contrast Ratio                                              | 1500 : 1 (typ)          |
|                                                                                                                                                  | Refresh Rate                                                | 60 (typ)                |
|                                                                                                                                                  | Brightness                                                  | 8                       |
|                                                                                                                                                  | Pixel Resolution                                            | RGB                     |
|                                                                                                                                                  | Pixel Resolution - Format                                   | 1920 x 1200 (WUXGA)     |
|                                                                                                                                                  | Aspect Ratio                                                | 16:10                   |
|                                                                                                                                                  | Backlight                                                   | WLED                    |
|                                                                                                                                                  | Color Gamut Coverage                                        | sRGB 100%               |
|                                                                                                                                                  | Color Depth                                                 | 8 bit                   |
|                                                                                                                                                  | Viewing Angle                                               | UWVA 89/89/89/89        |
|                                                                                                                                                  | Low Blue Light                                              | Yes                     |
|                                                                                                                                                  | Power Consumption (W,<br>EBL@ 150nits max/ 200nits<br>max)) | 1.48 (max)/1.8(max)     |

|                                                                                                                                                          |                            |                         |
|----------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|-------------------------|
| 35.6 cm (14") diagonal, 2.5K<br>(2560 x 1600), LCD, UWVA,<br>120Hz (VRR), Anti-Glare,<br>WLED + Low Blue Light, 400<br>nits, DCI-P3 100% + Adobe<br>100% | Outline Dimensions (W x H) | 306.890 x 197.900 (max) |
|                                                                                                                                                          | Active Area                | 301.594 x 188.496 (typ) |
|                                                                                                                                                          | Weight                     | 200 (max)               |
|                                                                                                                                                          | Diagonal Size              | 14                      |
|                                                                                                                                                          | Surface Treatment          | Anti-Glare              |
|                                                                                                                                                          | Touch Enabled              | No                      |
|                                                                                                                                                          | Contrast Ratio             | 2000:1 (typ)            |
|                                                                                                                                                          | Refresh Rate               | 120 (typ)               |
|                                                                                                                                                          | Brightness                 | 400 (typ)               |
|                                                                                                                                                          | Pixel Resolution           | 216                     |
|                                                                                                                                                          | Pixel Resolution - Format  | 2560 x 1600 (2.5K)      |



|  |                                                       |                              |
|--|-------------------------------------------------------|------------------------------|
|  | Aspect Ratio                                          | 16:10                        |
|  | Backlight                                             | WLED                         |
|  | Color Gamut Coverage                                  | Adobe RGB 100% + DCI-P3 100% |
|  | Color Depth                                           | 8                            |
|  | Viewing Angle                                         | UWVA 89/89/89/89             |
|  | Low Blue Light                                        | Yes                          |
|  | Power Consumption (W, EBL@ 150nits max/ 200nits max)) | 2.3 (max)/ 2.7 (max)         |

35.6 cm (14") diagonal,  
WUXGA (1920 x 1200), LCD,  
UWVA, Anti-Glare, WLED +  
Low Blue Light, 400 nits, Low  
power, sRGB 100%

|                                                       |                         |
|-------------------------------------------------------|-------------------------|
| Outline Dimensions (W x H)                            | 307.590 x 199.550 (max) |
| Active Area                                           | 301.590 x 188.500 (typ) |
| Weight                                                | 210 (max)               |
| Diagonal Size                                         | 14                      |
| Surface Treatment                                     | Anti-Glare              |
| Touch Enabled                                         | No                      |
| Contrast Ratio                                        | 1000:1(typ)             |
| Refresh Rate                                          | 60 (typ)                |
| Brightness                                            | 400 (typ)               |
| Pixel Resolution                                      | RGB                     |
| Pixel Resolution - Format                             | 1920 x 1200 (WUXGA)     |
| Aspect Ratio                                          | 16:10:00                |
| Backlight                                             | WLED                    |
| Color Gamut Coverage                                  | sRGB 100%               |
| Color Depth                                           | 8                       |
| Viewing Angle                                         | UWVA 89/89/89/89        |
| Low Blue Light                                        | Yes                     |
| Power Consumption (W, EBL@ 150nits max/ 200nits max)) | 1.29 (max) / 1.66 (max) |

35.6 cm (14") diagonal,  
WUXGA (1920 x 1200), LCD,

|                            |                         |
|----------------------------|-------------------------|
| Outline Dimensions (W x H) | 306.890 x 197.900 (max) |
| Active Area                | 301.590 X 188.500 (typ) |



|                                                                                                                         |                                                                      |                         |
|-------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------|-------------------------|
| <b>UWVA, Touch, Anti-Glare,<br/>Low Blue Light, 800 nits,<br/>sRGB 100%, HP Sure View 5<sup>1</sup></b>                 | <b>Weight</b>                                                        | 260 (max)               |
|                                                                                                                         | <b>Diagonal Size</b>                                                 | 14                      |
|                                                                                                                         | <b>Surface Treatment</b>                                             | Anti-Glare              |
|                                                                                                                         | <b>Touch Enabled</b>                                                 | Yes                     |
|                                                                                                                         | <b>Contrast Ratio</b>                                                | 1500 : 1 (typ)          |
|                                                                                                                         | <b>Refresh Rate</b>                                                  | 60 (typ)                |
|                                                                                                                         | <b>Brightness</b>                                                    | 800 (typ)               |
|                                                                                                                         | <b>Pixel Resolution</b>                                              | RGB                     |
|                                                                                                                         | <b>Pixel Resolution - Format</b>                                     | 1920 x 1200 (WUXGA)     |
|                                                                                                                         | <b>Aspect Ratio</b>                                                  | 16:10:00                |
|                                                                                                                         | <b>Backlight</b>                                                     | WLED                    |
|                                                                                                                         | <b>Color Gamut Coverage</b>                                          | sRGB 100%               |
|                                                                                                                         | <b>Color Depth</b>                                                   | 8 bit                   |
|                                                                                                                         | <b>Viewing Angle</b>                                                 | UWVA 89/89/89/89        |
|                                                                                                                         | <b>Low Blue Light</b>                                                | Yes                     |
|                                                                                                                         | <b>Power Consumption (W,<br/>EBL@ 150nits max/ 200nits<br/>max))</b> | 1.60 (max)/ 1.97 (max)  |
| <b>35.6 cm (14") diagonal,<br/>WUXGA (1920 x 1200), LCD,<br/>UWVA, Touch, Anti-Glare,<br/>WLED, 500 nits, sRGB 100%</b> | <b>Outline Dimensions (W x H)</b>                                    | 306.594 x 197.596 (max) |
|                                                                                                                         | <b>Active Area</b>                                                   | 301.59 x 188.5 (typ.)   |
|                                                                                                                         | <b>Weight</b>                                                        | 220(max)                |
|                                                                                                                         | <b>Diagonal Size</b>                                                 | 14                      |
|                                                                                                                         | <b>Surface Treatment</b>                                             | Anti-Glare              |
|                                                                                                                         | <b>Touch Enabled</b>                                                 | Yes                     |
|                                                                                                                         | <b>Contrast Ratio</b>                                                | 1500 : 1 (typ)          |
|                                                                                                                         | <b>Refresh Rate</b>                                                  | 60 (typ)                |
|                                                                                                                         | <b>Brightness</b>                                                    | 500 (typ)               |
|                                                                                                                         | <b>Pixel Resolution</b>                                              | RGB                     |
|                                                                                                                         | <b>Pixel Resolution - Format</b>                                     | 1920 x 1200 (WUXGA)     |
|                                                                                                                         | <b>Aspect Ratio</b>                                                  | 16:10:00                |
|                                                                                                                         | <b>Backlight</b>                                                     | WLED                    |
|                                                                                                                         | <b>Color Gamut Coverage</b>                                          | sRGB 100%               |



---

|                                                             |                         |
|-------------------------------------------------------------|-------------------------|
| Color Depth                                                 | 8                       |
| Viewing Angle                                               | UWVA 89/89/89/89        |
| Low Blue Light                                              | Yes                     |
| Power Consumption (W,<br>EBL@ 150nits max/ 200nits<br>max)) | 1.37 (max) / 1.68 (max) |

1. HP Sure View integrated privacy screen is an optional feature that must be configured at purchase and is designed to function in landscape orientation.

---



STORAGE

All Gen5 SSDs on this system run at Gen4 speed.

For all SSDs, read and write speeds are an average of the maximum values measured under full load conditions. Actual performance may vary +/- 20%.

1. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 32 GB is reserved for system recovery software.

|                                                 |                          |                                      |
|-------------------------------------------------|--------------------------|--------------------------------------|
| 2 TB PCIe® Gen5 NVMe™ SSD<br>Value <sup>1</sup> | Form Factor              | M.2 2280                             |
|                                                 | Capacity                 | 2 TB                                 |
|                                                 | NAND Type                | Value                                |
|                                                 | Interface                | PCIe Gen5 NVMe                       |
|                                                 | Maximum Sequential Read  | 7000 MB/s ±20% (in PCIe Gen4x4 slot) |
|                                                 | Maximum Sequential Write | 6800 MB/s ±20% (in PCIe Gen4x4 slot) |
|                                                 | Logical Blocks           | 4,00,07,97,360                       |
|                                                 | Features                 | Pyrite 2.0; TRIM; L1.2               |

|                                                              |                          |                        |
|--------------------------------------------------------------|--------------------------|------------------------|
| 2 TB PCIe® Gen4x4 NVMe™<br>SSD Three Layer Cell <sup>1</sup> | Form Factor              | M.2 2280               |
|                                                              | Capacity                 | 2TB                    |
|                                                              | NAND Type                | TLC                    |
|                                                              | Interface                | PCIe NVMe Gen4X4       |
|                                                              | Maximum Sequential Read  | 6400 MB/s ±20%         |
|                                                              | Maximum Sequential Write | 5000 MB/s ±20%         |
|                                                              | Logical Blocks           | 4,000,797,360          |
|                                                              | Features                 | Pyrite 2.0; TRIM; L1.2 |

|                                                 |                          |                                      |
|-------------------------------------------------|--------------------------|--------------------------------------|
| 1 TB PCIe® Gen5 NVMe™ SSD<br>Value <sup>1</sup> | Form Factor              | M.2 2280                             |
|                                                 | Capacity                 | 1 TB                                 |
|                                                 | NAND Type                | Value                                |
|                                                 | Interface                | PCIe Gen5 NVMe                       |
|                                                 | Maximum Sequential Read  | 7000 MB/s ±20% (in PCIe Gen4x4 slot) |
|                                                 | Maximum Sequential Write | 6600 MB/s ±20% (in PCIe Gen4x4 slot) |
|                                                 | Logical Blocks           | 2,00,04,09,264                       |
|                                                 | Features                 | Pyrite 2.0; TRIM; L1.2               |

|                                                                                          |                                 |                                      |
|------------------------------------------------------------------------------------------|---------------------------------|--------------------------------------|
| <b>1 TB PCIe® Gen5x4 NVMe™<br/>Performance Self Encrypted<br/>OPAL2 SSD <sup>1</sup></b> | <b>Form Factor</b>              | M.2 2280                             |
|                                                                                          | <b>Capacity</b>                 | 1 TB                                 |
|                                                                                          | <b>NAND Type</b>                | Performance                          |
|                                                                                          | <b>Interface</b>                | PCIe Gen5X4 NVMe                     |
|                                                                                          | <b>Maximum Sequential Read</b>  | 7000 MB/s ±20% (in PCIe Gen4x4 slot) |
|                                                                                          | <b>Maximum Sequential Write</b> | 7000 MB/s ±20% (in PCIe Gen4x4 slot) |
|                                                                                          | <b>Logical Blocks</b>           | 2,00,04,09,264                       |
|                                                                                          | <b>Features</b>                 | TCG OPAL 2.0; TRIM; L1.2             |

|                                                                      |                                 |                        |
|----------------------------------------------------------------------|---------------------------------|------------------------|
| <b>1 TB PCIe® Gen4x4 NVMe™<br/>SSD Three Layer Cell <sup>1</sup></b> | <b>Form Factor</b>              | M.2 2280               |
|                                                                      | <b>Capacity</b>                 | 1TB                    |
|                                                                      | <b>NAND Type</b>                | TLC                    |
|                                                                      | <b>Interface</b>                | PCIe NVMe Gen4X4       |
|                                                                      | <b>Maximum Sequential Read</b>  | 6400 MB/s ±20%         |
|                                                                      | <b>Maximum Sequential Write</b> | 5000 MB/s ±20%         |
|                                                                      | <b>Logical Blocks</b>           | 2,000,409,264          |
|                                                                      | <b>Features</b>                 | Pyrite 2.0; TRIM; L1.2 |

|                                                    |                                 |                        |
|----------------------------------------------------|---------------------------------|------------------------|
| <b>1 TB PCIe® NVMe™ SSD<br/>Value <sup>1</sup></b> | <b>Form Factor</b>              | M.2 2280               |
|                                                    | <b>Capacity</b>                 | 1TB                    |
|                                                    | <b>NAND Type</b>                | TLC                    |
|                                                    | <b>Interface</b>                | PCIe NVMe Gen4X4       |
|                                                    | <b>Maximum Sequential Read</b>  | 2200 MB/s ±20%         |
|                                                    | <b>Maximum Sequential Write</b> | 1600 MB/s ±20%         |
|                                                    | <b>Logical Blocks</b>           | 2,000,409,264          |
|                                                    | <b>Features</b>                 | Pyrite 2.0; TRIM; L1.2 |

|                                                                                    |                                |                                      |
|------------------------------------------------------------------------------------|--------------------------------|--------------------------------------|
| <b>512 GB PCIe® Gen5 NVMe™<br/>Self Encrypted OPAL2 SSD<br/>Value <sup>1</sup></b> | <b>Form Factor</b>             | M.2 2280                             |
|                                                                                    | <b>Capacity</b>                | 512 GB                               |
|                                                                                    | <b>NAND Type</b>               | Value                                |
|                                                                                    | <b>Interface</b>               | PCIe Gen5 NVMe                       |
|                                                                                    | <b>Maximum Sequential Read</b> | 7000 MB/s ±20% (in PCIe Gen4x4 slot) |



|  |                          |                                      |
|--|--------------------------|--------------------------------------|
|  | Maximum Sequential Write | 6000 MB/s ±20% (in PCIe Gen4x4 slot) |
|  | Logical Blocks           | 1,00,02,15,216                       |
|  | Features                 | TCG OPAL 2.0; TRIM; L1.2             |

|                                                   |                          |                                      |
|---------------------------------------------------|--------------------------|--------------------------------------|
| 512 GB PCIe® Gen5 NVMe™<br>SSD Value <sup>1</sup> | Form Factor              | M.2 2280                             |
|                                                   | Capacity                 | 512 GB                               |
|                                                   | NAND Type                | Value                                |
|                                                   | Interface                | PCIe Gen5 NVMe                       |
|                                                   | Maximum Sequential Read  | 7000 MB/s ±20% (in PCIe Gen4x4 slot) |
|                                                   | Maximum Sequential Write | 6000 MB/s ±20% (in PCIe Gen4x4 slot) |
|                                                   | Logical Blocks           | 1,00,02,15,216                       |
|                                                   | Features                 | Pyrite 2.0; TRIM; L1.2               |

|                                                                   |                          |                        |
|-------------------------------------------------------------------|--------------------------|------------------------|
| 512 GB PCIe® Gen4x4<br>NVMe™ SSD Three Layer Cell<br><sup>1</sup> | Form Factor              | M.2 2280               |
|                                                                   | Capacity                 | 512GB                  |
|                                                                   | NAND Type                | TLC                    |
|                                                                   | Interface                | PCIe NVMe Gen4X4       |
|                                                                   | Maximum Sequential Read  | 6400 MB/s ±20%         |
|                                                                   | Maximum Sequential Write | 3500 MB/s ±20%         |
|                                                                   | Logical Blocks           | 1,000,215,215          |
|                                                                   | Features                 | Pyrite 2.0; TRIM; L1.2 |

|                                                                                           |                          |                          |
|-------------------------------------------------------------------------------------------|--------------------------|--------------------------|
| 512 GB PCIe® Gen4x4<br>NVMe™ Self Encrypted<br>OPAL2 SSD Three Layer Cell<br><sup>1</sup> | Form Factor              | M.2 2280                 |
|                                                                                           | Capacity                 | 512GB                    |
|                                                                                           | NAND Type                | TLC                      |
|                                                                                           | Interface                | PCIe NVMe Gen4X4         |
|                                                                                           | Maximum Sequential Read  | 6400 MB/s ±20%           |
|                                                                                           | Maximum Sequential Write | 3500 MB/s ±20%           |
|                                                                                           | Logical Blocks           | 1,000,215,215            |
|                                                                                           | Features                 | TCG Opal 2.0; TRIM; L1.2 |

|                                              |             |          |
|----------------------------------------------|-------------|----------|
| 512 GB PCIe® NVMe™ SSD<br>Value <sup>1</sup> | Form Factor | M.2 2280 |
|                                              | Capacity    | 512 GB   |

|                                              |                          |                        |
|----------------------------------------------|--------------------------|------------------------|
| 256 GB PCIe® NVMe™ SSD<br>Value <sup>1</sup> | NAND Type                | TLC                    |
|                                              | Interface                | PCIe NVMe Gen4X4       |
|                                              | Maximum Sequential Read  | 2200 MB/s ±20%         |
|                                              | Maximum Sequential Write | 1000 MB/s ±20%         |
|                                              | Logical Blocks           | 1,000,215,215          |
|                                              | Features                 | Pyrite 2.0; TRIM; L1.2 |
|                                              | Form Factor              | M.2 2280               |
|                                              | Capacity                 | 256 GB                 |
|                                              | NAND Type                | TLC                    |
|                                              | Interface                | PCIe NVMe Gen4X4       |
|                                              | Maximum Sequential Read  | 2000 MB/s ±20%         |
|                                              | Maximum Sequential Write | 900 MB/s ±20%          |
|                                              | Logical Blocks           | 500,118,192            |
|                                              | Features                 | Pyrite 2.0; TRIM; L1.2 |
|                                              |                          |                        |
|                                              |                          |                        |

NETWORKING / COMMUNICATION

|                        |                        |                                                         |
|------------------------|------------------------|---------------------------------------------------------|
| Intel® BE201 Wi-Fi 7   | Wireless LAN Standards | IEEE 802.11a                                            |
| Bluetooth® 5.4 vPro WW |                        | IEEE 802.11ac                                           |
| WLAN <sup>1</sup>      |                        | IEEE 802.11ax                                           |
|                        |                        | IEEE 802.11b                                            |
|                        |                        | IEEE 802.11be                                           |
|                        |                        | IEEE 802.11d                                            |
|                        |                        | IEEE 802.11e                                            |
|                        |                        | IEEE 802.11g                                            |
|                        |                        | IEEE 802.11h                                            |
|                        |                        | IEEE 802.11i                                            |
|                        |                        | IEEE 802.11k                                            |
|                        |                        | IEEE 802.11n                                            |
|                        |                        | IEEE 802.11r                                            |
|                        |                        | IEEE 802.11v                                            |
|                        | Interoperability       | Wi-Fi certified                                         |
|                        | Frequency Band         | ▪ 802.11b/g/n/ax<br>2.402 - 2.482 GHz                   |
|                        |                        | ▪ 802.11a/n/ac/ax<br>4.9 - 4.95 GHz (Japan)             |
|                        |                        | 5.15 - 5.25 GHz                                         |
|                        |                        | 5.25 - 5.35 GHz                                         |
|                        |                        | 5.47 - 5.725 GHz                                        |
|                        |                        | 5.825 - 5.850 GHz                                       |
|                        |                        | 5.955 - 6.415 GHz                                       |
|                        |                        | 6.435 - 6.515 GHz                                       |
|                        |                        | 6.535 - 6.875 GHz                                       |
|                        |                        | 6.895 - 7.115 GHz                                       |
|                        | Data Rates             | ▪ 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps            |
|                        |                        | ▪ 802.11ac: MCS0 ~ MCS9, (20MHz, 40MHz, 80MHz, 160MHz)  |
|                        |                        | ▪ 802.11ax: MCS0 ~ MCS11, (20MHz, 40MHz, 80MHz, 160MHz) |
|                        |                        | ▪ 802.11b: 1, 2, 5.5, 11 Mbps                           |
|                        |                        | ▪ 802.11be: MCS0~13, (20MHz, 40MHz, 80MHz, 160MHz,      |

|                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                      | 320MHz)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|                      | ▪ 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|                      | ▪ 802.11n: MCS 0 ~ MCS 15, (20MHz, 40MHz)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Modulation           | Direct Sequence Spread Spectrum<br>1024QAM, 16-QAM, 256-QAM, 4096QAM, 64-QAM, BPSK, CCK,<br>Direct Sequence Spread Spectrum, OFDM, QPSK                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Security             | ▪ 802.1x authentication<br>▪ AES-CCMP: 128 bit in hardware<br>▪ IEEE 802.11i<br>▪ IEEE and WiFi certified 64 / 128 bit WEP encryption for a/b/g<br>mode only<br>▪ WAPI<br>▪ WPA, WPA2: 802.1x, WPA-PSK, WPA2-PSK, TKIP, and AES.<br>▪ WPA2 certification<br>▪ WPA3 (personal) certification                                                                                                                                                                                                                                                                                                                                                                                          |
| Network Architecture | Ad-hoc (Peer to Peer)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Models               | Infrastructure (Access Point Required)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Roaming              | IEEE 802.11 compliant roaming between access points                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Output Power         | ▪ 802.11b, 1Mbps : +17dBm minimum<br>▪ 802.11g, 6Mbps : +16dBm minimum<br>▪ 802.11a, 6Mbps : +17dBm minimum<br>▪ 802.11n, MCS7(HT20) : +14dBm minimum<br>▪ 802.11n, MCS7(HT40) : +13.5dBm minimum<br>▪ 802.11ac MCS9(VHT20) : 13.5dBm minimum<br>▪ 802.11ac MCS9(VHT40) : +13.5dBm minimum<br>▪ 802.11ac MCS9(VHT80) : +12.5dBm minimum<br>▪ 802.11ac MCS9(VHT160) : +10.5dBm minimum<br>▪ 802.11ax MCS11(HE20)(6GHz) : +11.5dBm minimum<br>▪ 802.11ax MCS11(HE40)(6GHz) : +7.5dBm minimum<br>▪ 802.11ax MCS11(HE80)(6GHz) : +7.5dBm minimum<br>▪ 802.11ax MCS11(HE160)(6GHz) : +7.5dBm minimum<br>▪ 802.11be MCS13(EHT20)(6GHz) : 11.5dBm<br>▪ 802.11be MCS13(EHT40)(6GHz) : 7.5dBm |



Power Consumption

- 802.11be MCS13(EHT80)(6GHz) : 7.5dBm
  - 802.11be MCS13(EHT160)(6GHz) : 6.5dBm
  - 802.11be MCS13(EHT320)(6GHz) : 4.5dBm
- Transmit mode : 3.4 W
- Receive mode : 1.8 W
- Idle mode (PSP) : 180 mW (WLAN Associated)
- Idle mode: 50 mW (WLAN unassociated)
- Connected Standby/Modern Standby : 10 mW
- Radio disabled : 8 mW

Power Management

ACPI and PCI Express compliant power management

Receiver Sensitivity <sup>2</sup>

- 802.11b, 1Mbps : -93.5dBm maximum
- 802.11b, 11Mbps : -85dBm maximum
- 802.11a/g, 6Mbps : -90.5dBm maximum
- 802.11a/g, 54Mbps : -72.5dBm maximum
- 802.11n, MCS0(HT20) : -90dBm maximum
- 802.11n, MCS7(HT20) : -71.5dBm maximum
- 802.11n, MCS0(HT40) : -88.5dBm maximum
- 802.11n, MCS7(HT40) : -68.5dBm maximum
- 802.11ac, MCS9(VHT20) : -88.5dBm maximum
- 802.11ac, MCS9(VHT40) : -65.5dBm maximum
- 802.11ac, MCS9(VHT80) : -60.5dBm maximum
- 802.11ac, MCS9(VHT160) : -58.5dBm maximum
- 802.11ax, MCS11(HE20)(6GHz) : -59.5dBm maximum
- 802.11ax, MCS11(HE40)(6GHz) : -56.5dBm maximum
- 802.11ax, MCS11(HE80)(6GHz) : -53.5dBm maximum
- 802.11ax, MCS11(HE160)(6GHz) : -51.5dBm maximum
- 802.11be, MCS13(EHT20)(6GHz) : -55.5dBm maximum
- 802.11be, MCS13(EHT40)(6GHz) : -53.5dBm maximum
- 802.11be, MCS13(EHT80)(6GHz) : -51.5dBm maximum
- 802.11be, MCS13(EHT160)(6GHz) : -48.5dBm maximum
- 802.11be, MCS13(EHT320)(6GHz) : -45.5dBm maximum

Antenna type

High efficiency antenna with spatial diversity

Two embedded tri-band 2.4/5/6 GHz antennas are provided to



|                   |                                                                           |
|-------------------|---------------------------------------------------------------------------|
|                   | the card to support WLAN MIMO communications and Bluetooth communications |
| Form Factor       | PCI-Express M.2 MiniCard with CNVi Interface                              |
| Dimensions        | 30.00 x 22.00 x 2.30 mm (1.18 x 0.87 x 0.09 inch)                         |
| Weight            | 1. Type 2230: 3.1 g<br>2. Type 1216: 0.8 g                                |
| Operating Voltage | 3.3 v +/- 5 %                                                             |

HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2/5.3/5.4 Wireless Technology

|                              |                                                                                                                                                                                                                                                                                                                      |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Bluetooth Specification      | 4.0<br>4.1<br>4.2<br>5.0<br>5.1<br>5.2<br>5.3<br>5.4                                                                                                                                                                                                                                                                 |
| Frequency Band               | 2042 to 2480 MHz                                                                                                                                                                                                                                                                                                     |
| Number of Available Channels | Legacy : 0~79 (1 MHz/CH)<br>BLE : 0~39 (2 MHz/CH)                                                                                                                                                                                                                                                                    |
| Data Rates and Throughput    | Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps<br>BLE : 1 Mbps data rate; throughput up to 0.2 Mbps<br>Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels<br>Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5) |
| Transmit Power               | The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.                                                                                                                                                                                        |
| Power Consumption            | Peak (Tx): 330 mW<br>Peak (Rx): 230 mW<br>Selective Suspend: 17 mW                                                                                                                                                                                                                                                   |
| Bluetooth Software           | Microsoft Windows Bluetooth Software                                                                                                                                                                                                                                                                                 |



|                              |                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|------------------------------|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supported Link Topology      |                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Power Management             |                        | Microsoft Windows ACPI, and USB Bus Support                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Certifications               |                        | FCC (47 CFR) Part 15C/E, Section 15.247, 15.249, 15.407; ETSI 300 328, ETSI 301 893, ETSI 303 687                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Bluetooth Profiles Supported |                        | 2Mbps LE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|                              |                        | Advanced Audio Distribution Profile (A2DP)<br>Basic Imaging Profile (BIP)<br>Channel Selection Algo<br>Encryption key size control enhancements<br>ESR9/10 Compliance<br>FAX Profile (FAX)<br>Hands Free Profile (HFP)<br>Headset Profile (HSP)<br>LE Advertisement Extensions<br>LE Data Packet Length Extension<br>LE Dual Mode<br>LE L2CAP Connection Oriented Channels<br>LE Link Layer<br>LE Link Layer Ping<br>LE Long Range<br>LE Low Duty Cycle Directed Advertising<br>LE Privacy 1.2 -Extended Scanner Filter Policies<br>LE Privacy 1.2 -Link Layer Privacy<br>LE Secure Connection- Basic/Full<br>Limited High Duty Cycle Non-Connectable Advertising<br>Train Nudging & Interlaced Scan |
| Intel® BE201 Wi-Fi 7         | Wireless LAN Standards | IEEE 802.11a                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Bluetooth® 5.4 non-vPro WW   |                        | IEEE 802.11ac                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| WLAN <sup>1</sup>            |                        | IEEE 802.11ax                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|                              |                        | IEEE 802.11b                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|                              |                        | IEEE 802.11be                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |



|                  |                                                            |
|------------------|------------------------------------------------------------|
|                  | IEEE 802.11d                                               |
|                  | IEEE 802.11e                                               |
|                  | IEEE 802.11g                                               |
|                  | IEEE 802.11h                                               |
|                  | IEEE 802.11i                                               |
|                  | IEEE 802.11k                                               |
|                  | IEEE 802.11n                                               |
|                  | IEEE 802.11r                                               |
|                  | IEEE 802.11v                                               |
| Interoperability | Wi-Fi certified                                            |
| Frequency Band   | ▪ 802.11b/g/n/ax<br>2.402 - 2.482 GHz                      |
|                  | ▪ 802.11a/n/ac/ax<br>4.9 - 4.95 GHz (Japan)                |
|                  | 5.15 - 5.25 GHz                                            |
|                  | 5.25 - 5.35 GHz                                            |
|                  | 5.47 - 5.725 GHz                                           |
|                  | 5.825 - 5.850 GHz                                          |
|                  | 5.955 - 6.415 GHz                                          |
|                  | 6.435 - 6.515 GHz                                          |
|                  | 6.535 - 6.875 GHz                                          |
|                  | 6.895 - 7.115 GHz                                          |
| Data Rates       | ▪ 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps               |
|                  | ▪ 802.11ac: MCS0 ~ MCS9, (20MHz, 40MHz, 80MHz, 160MHz)     |
|                  | ▪ 802.11ax: MCS0 ~ MCS11, (20MHz, 40MHz, 80MHz, 160MHz)    |
|                  | ▪ 802.11b: 1, 2, 5.5, 11 Mbps                              |
|                  | ▪ 802.11be: MCS0~13, (20MHz, 40MHz, 80MHz, 160MHz, 320MHz) |
|                  | ▪ 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps               |
|                  | ▪ 802.11n: MCS 0 ~ MCS 15, (20MHz, 40MHz)                  |
| Modulation       | Direct Sequence Spread Spectrum                            |
|                  | 1024QAM, 16-QAM, 256-QAM, 4096QAM, 64-QAM, BPSK, CCK,      |
|                  | Direct Sequence Spread Spectrum, OFDM, QPSK                |



|                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Security             | <ul style="list-style-type: none"><li>▪ 802.1x authentication</li><li>▪ AES-CCMP: 128 bit in hardware</li><li>▪ IEEE 802.11i</li><li>▪ IEEE and WiFi certified 64 / 128 bit WEP encryption for a/b/g mode only</li><li>▪ WAPI</li><li>▪ WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.</li><li>▪ WPA2 certification</li><li>▪ WPA3 (personal) certification</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Network Architecture | Ad-hoc (Peer to Peer)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Models               | Infrastructure (Access Point Required)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Roaming              | IEEE 802.11 compliant roaming between access points                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Output Power         | <ul style="list-style-type: none"><li>▪ 802.11b, 1Mbps : +17dBm minimum</li><li>▪ 802.11g, 6Mbps : +16dBm minimum</li><li>▪ 802.11a, 6Mbps : +17dBm minimum</li><li>▪ 802.11n, MCS7(HT20) : +14dBm minimum</li><li>▪ 802.11n, MCS7(HT40) : +13.5dBm minimum</li><li>▪ 802.11ac MCS9(VHT20) : 13.5dBm minimum</li><li>▪ 802.11ac MCS9(VHT40) : +13.5dBm minimum</li><li>▪ 802.11ac MCS9(VHT80) : +12.5dBm minimum</li><li>▪ 802.11ac MCS9(VHT160) : +10.5dBm minimum</li><li>▪ 802.11ax MCS11(HE20)(6GHz) : +11.5dBm minimum</li><li>▪ 802.11ax MCS11(HE40)(6GHz) : +7.5dBm minimum</li><li>▪ 802.11ax MCS11(HE80)(6GHz) : +7.5dBm minimum</li><li>▪ 802.11ax MCS11(HE160)(6GHz) : +7.5dBm minimum</li><li>▪ 802.11be MCS13(EHT20)(6GHz) : 11.5dBm</li><li>▪ 802.11be MCS13(EHT40)(6GHz) : 7.5dBm</li><li>▪ 802.11be MCS13(EHT80)(6GHz) : 7.5dBm</li><li>▪ 802.11be MCS13(EHT160)(6GHz) : 6.5dBm</li><li>▪ 802.11be MCS13(EHT320)(6GHz) : 4.5dBm</li></ul> |
| Power Consumption    | <p>Transmit mode : 3.4 W</p> <p>Receive mode : 1.8 W</p> <p>Idle mode (PSP) : 180 mW (WLAN Associated)</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |



Power Management  
Receiver Sensitivity<sup>2</sup>

- Idle mode: 50 mW (WLAN unassociated)  
Connected Standby/Modern Standby: 10 mW  
Radio disabled: 8 mW  
ACPI and PCI Express compliant power management
- 802.11b, 1Mbps: -93.5dBm maximum
  - 802.11b, 11Mbps: -85dBm maximum
  - 802.11a/g, 6Mbps: -90.5dBm maximum
  - 802.11a/g, 54Mbps: -72.5dBm maximum
  - 802.11n, MCS0(HT20): -90dBm maximum
  - 802.11n, MCS7(HT20): -71.5dBm maximum
  - 802.11n, MCS0(HT40): -88.5dBm maximum
  - 802.11n, MCS7(HT40): -68.5dBm maximum
  - 802.11ac, MCS9(VHT20): -88.5dBm maximum
  - 802.11ac, MCS9(VHT40): -65.5dBm maximum
  - 802.11ac, MCS9(VHT80): -60.5dBm maximum
  - 802.11ac, MCS9(VHT160): -58.5dBm maximum
  - 802.11ax, MCS11(HE20)(6GHz): -59.5dBm maximum
  - 802.11ax, MCS11(HE40)(6GHz): -56.5dBm maximum
  - 802.11ax, MCS11(HE80)(6GHz): -53.5dBm maximum
  - 802.11ax, MCS11(HE160)(6GHz): -51.5dBm maximum
  - 802.11be, MCS13(EHT20)(6GHz): -55.5dBm maximum
  - 802.11be, MCS13(EHT40)(6GHz): -53.5dBm maximum
  - 802.11be, MCS13(EHT80)(6GHz): -51.5dBm maximum
  - 802.11be, MCS13(EHT160)(6GHz): -48.5dBm maximum
  - 802.11be, MCS13(EHT320)(6GHz): -45.5dBm maximum

Antenna type

High efficiency antenna with spatial diversity  
Two embedded tri-band 2.4/5/6 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications

Form Factor  
Dimensions  
Weight

PCI-Express M.2 MiniCard with CNVi Interface  
30.00 x 22.00 x 2.30 mm (1.18 x 0.87 x 0.09 inch)  
1. Type 2230: 3.1 g  
2. Type 1216: 0.8 g



|                                                                                         |                                                                                                                                                                                            |
|-----------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating Voltage                                                                       | 3.3 v +/- 5 %                                                                                                                                                                              |
| HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2/5.3/5.4 Wireless Technology |                                                                                                                                                                                            |
| Bluetooth Specification                                                                 | 4.0                                                                                                                                                                                        |
|                                                                                         | 4.1                                                                                                                                                                                        |
|                                                                                         | 4.2                                                                                                                                                                                        |
|                                                                                         | 5.0                                                                                                                                                                                        |
|                                                                                         | 5.1                                                                                                                                                                                        |
|                                                                                         | 5.2                                                                                                                                                                                        |
|                                                                                         | 5.3                                                                                                                                                                                        |
| Frequency Band                                                                          | 5.4                                                                                                                                                                                        |
|                                                                                         | 2042 to 2480 MHz                                                                                                                                                                           |
|                                                                                         | Legacy : 0~79 (1 MHz/CH)                                                                                                                                                                   |
|                                                                                         | BLE : 0~39 (2 MHz/CH)                                                                                                                                                                      |
|                                                                                         | Data Rates and Throughput                                                                                                                                                                  |
|                                                                                         | Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy :                                                                           |
|                                                                                         | Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5) |
| Transmit Power                                                                          | The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.                                                              |
| Power Consumption                                                                       | Peak (Tx): 330 mW                                                                                                                                                                          |
|                                                                                         | Peak (Rx): 230 mW                                                                                                                                                                          |
|                                                                                         | Selective Suspend: 17 mW                                                                                                                                                                   |
| Bluetooth Software                                                                      | Microsoft Windows Bluetooth Software                                                                                                                                                       |
| Supported Link Topology                                                                 |                                                                                                                                                                                            |
| Power Management                                                                        | Microsoft Windows ACPI, and USB Bus Support                                                                                                                                                |
| Certifications                                                                          | FCC (47 CFR) Part 15C/E, Section 15.247, 15.249, 15.407; ETSI 300 328, ETSI 301 893, ETSI 303 687                                                                                          |
| Bluetooth Profiles                                                                      | 2Mbps LE                                                                                                                                                                                   |
| Supported                                                                               | Advanced Audio Distribution Profile (A2DP)                                                                                                                                                 |
|                                                                                         | Basic Imaging Profile (BIP)                                                                                                                                                                |



- Channel Selection Algo
- Encryption key size control enhancements
- ESR9/10 Compliance
- FAX Profile (FAX)
- Hands Free Profile (HFP)
- Headset Profile (HSP)
- LE Advertisement Extensions
- LE Data Packet Length Extension
- LE Dual Mode
- LE L2CAP Connection Oriented Channels
- LE Link Layer
- LE Link Layer Ping
- LE Long Range
- LE Low Duty Cycle Directed Advertising
- LE Privacy 1.2 –Extended Scanner Filter Policies
- LE Privacy 1.2 –Link Layer Privacy
- LE Secure Connection- Basic/Full
- Limited High Duty Cycle Non-Connectable Advertising
- Train Nudging & Interlaced Scan

1. Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 7 (802.11BE) functionality requires compatible Windows OS, select Intel® processor, and a Wi-Fi 7 router, sold separately. Wi-Fi 7 is backwards compatible with prior 802.11 specs. Available in countries where Wi-Fi 7 is supported. The specification for 802.11BE is a draft specification and is not final. If the final specification differs from the draft specification, it may affect the ability of the device to communicate with other 802.11BE devices.
2. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

|                                          |                               |                                                                                                                                                                                                                                                              |
|------------------------------------------|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MediaTek T700 5G NR<br>WWAN <sup>3</sup> | Technology/Operating<br>bands | WCDMA/HSPA+ operating bands:<br><br>Band 1: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL)<br>Band 2: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL)<br>Band 4: 1710 to 1755 MHz (UL), 2110 to 2155 MHz (DL)<br>Band 5: 824 to 849 MHz (UL), 869 to 894 MHz (DL) |
|------------------------------------------|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Band 8: 880 to 915 MHz (UL), 925 to 960 MHz (DL)

LTE FDD/TDD operating bands:

Band 1: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL)

Band 12: 699 to 716 MHz (UL), 729 to 746 MHz (DL)

Band 13: 777 to 787 MHz (UL), 746 to 756 MHz (DL)

Band 14: 788 to 798 MHz (UL), 758 to 768 MHz (DL)

Band 17: 704 to 716 MHz (UL), 734 to 746 MHz (DL)

Band 18: 815 to 830 MHz (UL), 860 to 875 MHz (DL)

Band 19: 830 to 845 MHz (UL), 875 to 890 MHz (DL)

Band 2: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL)

Band 20: 832 to 862 MHz (UL), 791 to 821 MHz (DL)

Band 25: 1850 to 1915 MHz (UL), 1930 to 1995 MHz (DL)

Band 26: 814 to 849 MHz (UL), 859 to 894 MHz (DL)

Band 28: 703 to 748 MHz (UL), 758 to 803 MHz (DL)

Band 29: 717 to 728 MHz (DL)

Band 3: 1710 to 1785 MHz (UL), 1805 to 1880 MHz (DL)

Band 30: 2305 to 2315 MHz (UL) 2350 to 2360 MHz (DL)

Band 34: 2010 to 2025 MHz (UL/DL)

Band 38: 2570 to 2620 MHz (UL/DL)

Band 39: 1880 to 1920 MHz (UL/DL)

Band 4: 1710 to 1755 MHz (UL), 2110 to 2155 MHz (DL)

Band 40: 2300 to 2400 MHz (UL/DL)

Band 41: 2496 to 2690 MHz (UL/DL)

Band 42: 3400 to 3600 MHz (UL/DL)

Band 43: 3400 to 3800 MHz (UL/DL)

Band 46: 5150 to 5925 MHz (DL)

Band 48: 3550 to 3700 MHz (UL/DL)

Band 5: 824 to 849 MHz (UL), 869 to 894 MHz (DL)

Band 66: 1710 to 1800 MHz (UL), 2110 to 2200 MHz (DL)

Band 7: 2500 to 2570 MHz (UL), 2620 to 2690 MHz (DL)

Band 71: 663 to 698 MHz (UL), 617 to 652 MHz (DL)

Band 8: 880 to 915 MHz (UL), 925 to 960 MHz (DL)



|                                                           |                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-----------------------------------------------------------|----------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                           | <b>Wireless protocol standards</b>                 | 5G NR Air Interface<br>3GPP Rel15 5G NR sub-6<br>LTE Rel15<br>3GPP Release 8 UMTS Specification                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|                                                           | <b>GPS</b>                                         | Standalone/A-GPS (MS-A, MS-B)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|                                                           | <b>GPS bands</b>                                   | GPS L1 (1575.42MHz), GLONASS L1 (1602MHz), Beidou B1 (1561.098MHz), Galileo E1 (1575.42MHz), QZSS (1575.42MHz)                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|                                                           | <b>Maximum data rates</b>                          | SA 5G/NR sub-6 Peak: 4.67 Gbps(Download), 1.25 Gbps(Upload)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|                                                           | <b>Maximum output power</b>                        | HSPA+: 23.5 dBm ()<br>LTE (all bands except B41): 23.0 dBm (Not support HPUE)<br>NR (all band except n41, n77, n78, n79): 23.0 dBm (Not support HPUE)<br>NR n41, n77, n78, n79 HPUE: 26.0 dBm (Support HPUE)                                                                                                                                                                                                                                                                                                                                                        |
|                                                           | <b>Maximum power consumption</b>                   | 5G Sub 6: 3,500 mA<br>LTE: 2,500 mA (peak)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|                                                           | <b>Form Factor</b>                                 | M.2; 3052-S3 Key B                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|                                                           | <b>Weight</b>                                      | 8.6 g (0.303 oz)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|                                                           | <b>Dimensions<br/>(Length x Width x Thickness)</b> | 30.00 x 52.00 x 2.30 mm (1.18 x 2.05 x 0.09 inch)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|                                                           | <b>embedded eSIM</b>                               | Yes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>MediaTek T700 4G LTE-Advanced Pro WWAN<sup>4</sup></b> | <b>Technology/Operating bands</b>                  | WCDMA/HSPA+ operating bands:<br>Band 1: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL)<br>Band 2: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL)<br>Band 4: 1710 to 1755 MHz (UL), 2110 to 2155 MHz (DL)<br>Band 5: 824 to 849 MHz (UL), 869 to 894 MHz (DL)<br>Band 8: 880 to 915 MHz (UL), 925 to 960 MHz (DL)<br>LTE FDD/TDD operating bands:<br>Band 1: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL)<br>Band 12: 699 to 716 MHz (UL), 729 to 746 MHz (DL)<br>Band 13: 777 to 787 MHz (UL), 746 to 756 MHz (DL)<br>Band 14: 788 to 798 MHz (UL), 758 to 768 MHz (DL) |
|                                                           |                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|                                                           |                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|                                                           |                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|                                                           |                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|                                                           |                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|                                                           |                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|                                                           |                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|                                                           |                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|                                                           |                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |



|                             |                                                                                                                |
|-----------------------------|----------------------------------------------------------------------------------------------------------------|
|                             | Band 17: 704 to 716 MHz (UL), 734 to 746 MHz (DL)                                                              |
|                             | Band 18: 815 to 830 MHz (UL), 860 to 875 MHz (DL)                                                              |
|                             | Band 19: 830 to 845 MHz (UL), 875 to 890 MHz (DL)                                                              |
|                             | Band 2: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL)                                                           |
|                             | Band 20: 832 to 862 MHz (UL), 791 to 821 MHz (DL)                                                              |
|                             | Band 25: 1850 to 1915 MHz (UL), 1930 to 1995 MHz (DL)                                                          |
|                             | Band 26: 814 to 849 MHz (UL), 859 to 894 MHz (DL)                                                              |
|                             | Band 28: 703 to 748 MHz (UL), 758 to 803 MHz (DL)                                                              |
|                             | Band 29: 717 to 728 MHz (DL)                                                                                   |
|                             | Band 3: 1710 to 1785 MHz (UL), 1805 to 1880 MHz (DL)                                                           |
|                             | Band 30: 2305 to 2315 MHz (UL) 2350 to 2360 MHz (DL)                                                           |
|                             | Band 34: 2010 to 2025 MHz (UL/DL)                                                                              |
|                             | Band 38: 2570 to 2620 MHz (UL/DL)                                                                              |
|                             | Band 39: 1880 to 1920 MHz (UL/DL)                                                                              |
|                             | Band 4: 1710 to 1755 MHz (UL), 2110 to 2155 MHz (DL)                                                           |
|                             | Band 40: 2300 to 2400 MHz (UL/DL)                                                                              |
|                             | Band 41: 2496 to 2690 MHz (UL/DL)                                                                              |
|                             | Band 42: 3400 to 3600 MHz (UL/DL)                                                                              |
|                             | Band 43: 3400 to 3800 MHz (UL/DL)                                                                              |
|                             | Band 46: 5150 to 5925 MHz (DL)                                                                                 |
|                             | Band 48: 3550 to 3700 MHz (UL/DL)                                                                              |
|                             | Band 5: 824 to 849 MHz (UL), 869 to 894 MHz (DL)                                                               |
|                             | Band 66: 1710 to 1800 MHz (UL), 2110 to 2200 MHz (DL)                                                          |
|                             | Band 7: 2500 to 2570 MHz (UL), 2620 to 2690 MHz (DL)                                                           |
|                             | Band 71: 663 to 698 MHz (UL), 617 to 652 MHz (DL)                                                              |
|                             | Band 8: 880 to 915 MHz (UL), 925 to 960 MHz (DL)                                                               |
| Wireless protocol standards | LTE Rel15<br>3GPP Release 8 UMTS Specification                                                                 |
| GPS                         | Standalone/A-GPS (MS-A, MS-B)                                                                                  |
| GPS bands                   | GPS L1 (1575.42MHz), GLONASS L1 (1602MHz), Beidou B1 (1561.098MHz), Galileo E1 (1575.42MHz), QZSS (1575.42MHz) |
| Maximum data rates - LTE    | UE Category DL 19 (1.6 Gbps Download). UE Category UL 18 (211 Mbps Upload)                                     |



|                                                |                                                         |
|------------------------------------------------|---------------------------------------------------------|
| <b>Maximum output power</b>                    | LTE (all bands except B41): 23.0 dBm (Not support HPUE) |
| <b>Maximum power consumption</b>               | LTE: 2,500 mA (peak)                                    |
| <b>Form Factor</b>                             | M.2; 3052-S3 Key B                                      |
| <b>Weight</b>                                  | 8.4 g (0.296 oz)                                        |
| <b>Dimensions (Length x Width x Thickness)</b> | 30.00 x 52.00 x 2.30 mm (1.18 x 2.05 x 0.09 inch)       |
| <b>embedded eSIM</b>                           | Yes                                                     |

3. 5G module is optional. WWAN-ready configuration must be selected at purchase to add WWAN module at a later date (WWAN After Market Option Kit). Module designed for 5G NR SA(standalone) and 5G NR NSA (non-standalone) Public and Private networks including Evolved-Universal Terrestrial Radio Access New Radio Dual Connectivity (ENDC) with both 100Mhz of 5G NR and LTE channel bandwidth, using 256QAM 4x4 as defined by 3GPP. Module includes embedded eSIM. Module requires activation and separately purchased service contract. Check with service provider for coverage and availability in your area. Data connection, upload and download speeds will vary due to network, location, environment, network conditions, and other factors. Backwards compatible to 4G LTE and 3G HSPA technologies. 5G module planned to be available in select platforms and select countries, where carrier and frequency bands supported.

4. 4G module is optional. WWAN-ready configuration must be selected at purchase to add WWAN at a later date. Check with service provider for coverage and availability in your area. Connection, upload and download speeds will vary due to network, location, environment, network conditions, and other factors. 4G LTE not available on all products, in all regions.

|                              |                               |                                                    |
|------------------------------|-------------------------------|----------------------------------------------------|
| <b>NFC Mirage WNC XRAV-1</b> | <b>Dimensions (L x W x H)</b> | 17.00 x 10.00 x 2.00 mm (0.67 x 0.39 x 0.08 inch)  |
|                              | <b>Chipset</b>                | NPC300                                             |
|                              | <b>System interface</b>       | I2C                                                |
|                              | <b>NFC RF standards</b>       | ISO/IEC 14443 A                                    |
|                              |                               | ISO/IEC 14443 B                                    |
|                              |                               | ISO/IEC 15693                                      |
|                              |                               | ISO/IEC 18092                                      |
|                              |                               | ECMA-340 NFCIP-1 Target and Initiator              |
|                              |                               | ECMA-320 NFCIP-2                                   |
|                              | <b>NFC Forum Support</b>      | Type 1, Type 2, Type 3 / Type 4, NFCIP-1 / NFCIP-2 |
|                              | <b>Reader (PCD-VCD) Mode</b>  | ISO/IEC 14443 A                                    |



|                                   |                                                                                           |
|-----------------------------------|-------------------------------------------------------------------------------------------|
|                                   | ISO/IEC 14443 B                                                                           |
|                                   | ISO/IEC 15693                                                                             |
|                                   | MIFARE 1K                                                                                 |
|                                   | MIFARE 4K                                                                                 |
|                                   | MIFARE DESFire                                                                            |
|                                   | FeliCa                                                                                    |
|                                   | Jewel and Topaz                                                                           |
| <b>Card Emulation (PICC-VICC)</b> | ISO/IEC 14443 A                                                                           |
| <b>Mode</b>                       | ISO/IEC 14443 B and B'                                                                    |
|                                   | MIFARE                                                                                    |
|                                   | FeliCa                                                                                    |
| <b>Frequency</b>                  | 13.56 MHz                                                                                 |
| <b>NFC Modes Supported</b>        | Reader/Writer, Peer-to-Peer                                                               |
| <b>Raw RF Data Rates</b>          | 106 kbps, 212 kbps, 424 kbps, 848 kbps                                                    |
| <b>Operating temperature</b>      | Operating: 0 °C to 70 °C (32 °F to 158 °F)<br>Storage: -20 °C to 125 °C (-4 °F to 257 °F) |
| <b>Storage temperature</b>        | Operating: 10% - 90% (non-condensing)<br>Non-Operating: 5% - 95% (non-condensing)         |
| <b>Humidity</b>                   | Operating: 10% - 90% (non-condensing)<br>Non-Operating: 5% - 95% (non-condensing)         |
| <b>Supply Operating voltage</b>   | 4.35 to 5.25 Volts                                                                        |
| <b>I/O Voltage</b>                | 1.8V or 3.3V                                                                              |
|                                   | <b>Power Consumption</b><br>(Booster enable, VBAT= 3.3V, VCC_BOOST = 5V)                  |
| <b>Mode</b>                       | Power Consumption, Typical                                                                |
| <b>Polling</b>                    | 7.3 mA                                                                                    |
| <b>Detected Test Tag Type 1</b>   | Total 283.8 mA<br>Net Module 236.8 mA                                                     |
| <b>Detected Test Tag Type 2</b>   | Total 288.8 mA<br>Net Module 241.8 mA                                                     |
| <b>Detected Test Tag Type 3</b>   | Total 287.7 mA<br>Net Module 240.7 mA                                                     |
| <b>Detected Test Tag Type 4</b>   | Total 282.3 mA                                                                            |



|                                                |                                            |                                                                                                                                                                                    |
|------------------------------------------------|--------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                |                                            | Net Module 235.3 mA                                                                                                                                                                |
| Antenna                                        |                                            | Antenna connector, 0.5mm pitch, 7 connector FPC. Antenna matching is external to module.                                                                                           |
| Qualcomm 9205 LTE-M (CAT-M1 fSVC) <sup>5</sup> | Technology/Operating bands-FDD             | Band 1: 2100                                                                                                                                                                       |
|                                                | LTE                                        | Band 2: 1900                                                                                                                                                                       |
|                                                |                                            | Band 3: 1800                                                                                                                                                                       |
|                                                |                                            | Band 4: 1700/2100                                                                                                                                                                  |
|                                                |                                            | Band 5: 850                                                                                                                                                                        |
|                                                |                                            | Band 8: 900                                                                                                                                                                        |
|                                                |                                            | Band 12 lower: 700                                                                                                                                                                 |
|                                                |                                            | Band 13 upper: 700                                                                                                                                                                 |
|                                                |                                            | Band 14 upper: 700                                                                                                                                                                 |
|                                                |                                            | Band 18 lower: 850                                                                                                                                                                 |
|                                                |                                            | Band 19 upper: 850                                                                                                                                                                 |
|                                                |                                            | Band 20: 800                                                                                                                                                                       |
|                                                |                                            | Band 25: 1900                                                                                                                                                                      |
|                                                |                                            | Band 26: 850                                                                                                                                                                       |
|                                                |                                            | Band 27: 800                                                                                                                                                                       |
|                                                |                                            | Band 28: 700                                                                                                                                                                       |
|                                                |                                            | Band 66: 1700/2100                                                                                                                                                                 |
|                                                |                                            | Band 85: 700                                                                                                                                                                       |
|                                                | Technology/Operating bands-GSM/GPRS/EGPRS: | 850                                                                                                                                                                                |
|                                                |                                            | 900                                                                                                                                                                                |
|                                                |                                            | 1800                                                                                                                                                                               |
|                                                |                                            | 1900                                                                                                                                                                               |
|                                                | Wireless protocol standards                | 3GPP TS 21.111 V10.0.0: USIM and IC card requirements                                                                                                                              |
|                                                |                                            | 3GPP TS 27.005 V10.0.1: Use of Data Terminal Equipment - Data Circuit terminating Equipment (DTE - DCE) interface for Short Message Service (SMS) and Cell Broadcast Service (CBS) |
|                                                |                                            | 3GPP TS 27.007 V10.0.8: AT command set for User Equipment (UE)                                                                                                                     |
|                                                |                                            | 3GPP TS 31.102 V10.11.0: Characteristics of the Universal                                                                                                                          |



|                                |                                                                                                                                                                         |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                | Subscriber Identity Module (USIM) application                                                                                                                           |
|                                | 3GPP TS 31.11 V10.16.0: Universal Subscriber Identity Module (USIM) Application Toolkit (USAT)                                                                          |
|                                | 3GPP TS 36.124 V10.3.0: Electro Magnetic Compatibility (EMC) requirements for mobile terminals and ancillary equipment                                                  |
|                                | 3GPP TS 36.521-1 V14.3.0: User Equipment (UE) conformance specification; Radio transmission and reception; Part 1: Conformance testing                                  |
|                                | 3GPP TS 51.010-1 10.5.0: Mobile Station (MS) conformance specification; 1551.mas. fictification of the Subscriber Identity Module - Mobile Equipment (SIM-ME) interface |
| GPS                            | Standalone GPS/Beidou/GLONASS                                                                                                                                           |
|                                | A-GPS (XTRA)                                                                                                                                                            |
| GPS bands                      | 1575.42 MHz ± 1.023 MHz                                                                                                                                                 |
|                                | GLONASS 1596-1607MHz                                                                                                                                                    |
|                                | Beidou 1561.098 MHz                                                                                                                                                     |
| Maximum data rates             | LTD FDD: 375 Kbps (download); 1119.00 Kbps (upload)                                                                                                                     |
|                                | GPRS: 107.00 Kbps (download); 85.60 Kbps (upload)                                                                                                                       |
|                                | EGPRS: 296.00 Kbps (download); 236.80 Kbps (upload)                                                                                                                     |
| Maximum output power           | LTE (all bands except B41): 21.5 dBm                                                                                                                                    |
|                                | GSM: 34.0 dBm                                                                                                                                                           |
| Maximum power consumption      | LTE: 151 mA (peak) ; 16 mA (average)                                                                                                                                    |
| Form Factor                    | M.2                                                                                                                                                                     |
| Dimensions (L x W x Thickness) | 22.00 x 42.00 x 2.30mm ( 0.87 x 1.65 x 0.09 inch )                                                                                                                      |
| Weight                         | 4.0g (0.141 oz)                                                                                                                                                         |
| Embedded eSIM                  | Yes                                                                                                                                                                     |

5 Cat M1 LPWAN (Mobile Narrowband) cards support select platforms with the HP Protect & Trace with Wolf Connect service, but do not support mobile broadband/Internet use.

POWER

|                                              |                                     |                                                               |
|----------------------------------------------|-------------------------------------|---------------------------------------------------------------|
| HP 100W Slim USB Type-C®<br>AC power adapter | Weight                              | 380g ± 10g                                                    |
|                                              | Input                               | 100-240Vac                                                    |
|                                              | Input Efficiency                    | 81.50% min at 115 Vac/ 230 Vac @5.00V                         |
|                                              |                                     | 86.70% min at 115 Vac/ 230 Vac @9.00V                         |
|                                              |                                     | 88.00% min at 115 Vac/ 230 Vac @12.00V                        |
|                                              |                                     | 89.00% min at 115 Vac/ 230 Vac @15.00V                        |
|                                              |                                     | 89.00% min at 115 Vac/ 230 Vac @20.00V                        |
|                                              | Input frequency range               | 47-63Hz                                                       |
|                                              | Input AC current                    | Max. 1.6 A at 90 Vac                                          |
|                                              | Output                              |                                                               |
|                                              | Output power                        | 5V/15W                                                        |
|                                              |                                     | 9V/27W                                                        |
|                                              |                                     | 12V/60W                                                       |
|                                              |                                     | 15V/75W                                                       |
|                                              |                                     | 20V/100W                                                      |
|                                              | DC output                           | 5V/9V/12V/15V/20V                                             |
|                                              | Hold-up time                        | 100% load 5ms at 115 Vac input/80% load 10ms at 115 Vac input |
|                                              | Output Over Current Protection      | 5V/9V/12V/15V<125% max current, 20V<135% max current          |
|                                              | AC Inlet Type                       | C6                                                            |
|                                              | DC Cable Connector                  | USB type C                                                    |
|                                              | DC Cable Material                   | PVC                                                           |
|                                              | Connector                           | C6                                                            |
|                                              | Environmental Design                |                                                               |
|                                              | Operating temperature               | 0° to 35° C (32° to 95° F)                                    |
|                                              | Non-operating (storage) temperature | -20° to 85° C (-4° to 185° F)                                 |
|                                              | Altitude                            | 0 to 5,000 m (0 to 16,400 ft)                                 |
|                                              | Humidity                            | 20% to 95%                                                    |
|                                              | Storage Humidity                    | 10% to 95%                                                    |
|                                              | EMI and Safety Certifications       | CE Mark - full compliance with LVD and EMC directives         |



Worldwide safety standards - IEC60950-1, IEC 62368-1:2014 and IEC62368-1 : 2018, EN62368-1:2020+A11, UL 62368-1  
Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, CU(EAC), KCC(Safety+EMC), NOM-001 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia RCM, BIS, BSMI, UAE, UKCA DoC, Ukraine(CoC+DoC+RoHS+ECO)

|                                              |                       |                                        |
|----------------------------------------------|-----------------------|----------------------------------------|
| HP 65W Standard USB Type-C® AC power adapter | Weight                | 240g ± 10g                             |
|                                              | Input                 | 100-240Vac                             |
|                                              | Input Efficiency      | 81.50% min at 115 Vac/ 230 Vac @5.00V  |
|                                              |                       | 86.70% min at 115 Vac/ 230 Vac @9.00V  |
|                                              |                       | 88.00% min at 115 Vac/ 230 Vac @12.00V |
|                                              |                       | 89.00% min at 115 Vac/ 230 Vac @15.00V |
|                                              |                       | 89.00% min at 115 Vac/ 230 Vac @20.00V |
|                                              | Input frequency range | 47-63Hz                                |
|                                              | Input AC current      | Max. 1.6 A at 90 Vac                   |
|                                              | Output                |                                        |
|                                              | Output power          | 5V/15W                                 |
|                                              |                       | 9V/27W                                 |
|                                              |                       | 12V/60W                                |
|                                              |                       | 15V/65W                                |
|                                              |                       | 20V/65W                                |
|                                              | DC output             | 5V/9V/12V/15V/20V                      |
|                                              | Hold-up time          | 100% load 5ms at 115 Vac input         |
|                                              | Output Over Current   | < 8.0A                                 |
|                                              | Protection            |                                        |
|                                              | AC Inlet Type         | C6                                     |
|                                              | DC Cable Connector    | USB type C                             |
|                                              | DC Cable Material     | PVC                                    |
|                                              | Connector             | C6                                     |
|                                              | Environmental Design  |                                        |
|                                              | Operating temperature | 0° to 35° C (32° to 95° F)             |



|                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|-----------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Non-operating (storage) temperature                 | -20° to 85° C (-4° to 185° F)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Altitude                                            | 0 to 5,000 m (0 to 16,400 ft)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Humidity                                            | 20% to 95%                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Storage Humidity                                    | 10% to 95%                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| EMI and Safety Certifications                       | CE Mark - full compliance with LVD and EMC directives<br>Worldwide safety standards - IEC60950-1 and IEC62368-1 : 2018, EN62368-1:2014+A11, UL 62368-1<br>Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECPC, CU(EAC), EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia RCM, BIS, BSMI, UAE, UKCA DoC                                                                                                                                                                                    |
| HP 65W USB Type-C* Gallium Nitride AC power adapter | Weight<br>105g(+/-10g) (Not including power cord. Power cord varies by country.)<br>Input<br>100-240Vac<br>Input Efficiency<br>81.50% min at 115 Vac/ 230 Vac @5.00V<br>86.70% min at 115 Vac/ 230 Vac @9.00V<br>89.00% min at 115 Vac/ 230 Vac @15.00V<br>89.00% min at 115 Vac/ 230 Vac @20.00V<br>Input frequency range<br>47-63Hz<br>Input AC current<br>Max. 1.6 A at 90 Vac<br>Output<br>Output power<br>5V/15W<br>9V/27W<br>15V/65W<br>20V/65W<br>DC output<br>5V/9V/15V/20V<br>Hold-up time<br>100% load 5ms at 115 Vac input<br>Output Over Current<br>115%-125%<br>Protection<br>AC Inlet Type<br>C6 |



|                                          |                                                                                                                                                                                                                                                                                                                                                                                                                               |
|------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DC Cable Connector                       | USB type C                                                                                                                                                                                                                                                                                                                                                                                                                    |
| DC Cable Material                        | PVC                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Connector                                | C6                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Environmental Design                     |                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Operating temperature                    | 0° to 35° C (32° to 95° F)                                                                                                                                                                                                                                                                                                                                                                                                    |
| Non-operating (storage) temperature      | -20° to 85° C (-4° to 185° F)                                                                                                                                                                                                                                                                                                                                                                                                 |
| Altitude                                 | 0 to 5,000 m (0 to 16,400 ft)                                                                                                                                                                                                                                                                                                                                                                                                 |
| Humidity                                 | 20% to 95%                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Storage Humidity                         | 10% to 95%                                                                                                                                                                                                                                                                                                                                                                                                                    |
| EMI and Safety Certifications            | CE Mark - full compliance with LVD and EMC directives<br>Worldwide safety standards - IEC60950-1 and IEC62368-1 :<br>2018, EN62368-1:2014+A11, UL 62368-1<br>Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECF, CU(EAC), EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia RCM, BIS, BSMI, UAE, UKCA DoC |
| HP 65W Slim USB Type-C® AC power adapter | Weight<br>Input<br>Input Efficiency<br><br>Input frequency range<br>Input AC current<br>Output<br>Output power                                                                                                                                                                                                                                                                                                                |
|                                          | 220g ± 10g<br>100-240Vac<br>81.50% min at 115 Vac/ 230 Vac @5.00V<br>86.70% min at 115 Vac/ 230 Vac @9.00V<br>88.00% min at 115 Vac/ 230 Vac @12.00V<br>89.00% min at 115 Vac/ 230 Vac @15.00V<br>89.00% min at 115 Vac/ 230 Vac @20.00V<br>47-63Hz<br>Max. 1.6 A at 90 Vac<br>5V/15W<br>9V/27W<br>12V/60W<br>15V/65W                                                                                                         |



|                                                           |                       |                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-----------------------------------------------------------|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                           |                       | 20V/65W                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| DC output                                                 |                       | 5V/9V/12V/15V/20V                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Hold-up time                                              |                       | 100% load 5ms at 115 Vac input                                                                                                                                                                                                                                                                                                                                                                                                           |
| Output Over Current                                       |                       | < 8.0A                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Protection                                                |                       |                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| AC Inlet Type                                             |                       | C6                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| DC Cable Connector                                        |                       | USB type C                                                                                                                                                                                                                                                                                                                                                                                                                               |
| DC Cable Material                                         |                       | PVC                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Connector                                                 |                       | C6                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Environmental Design                                      |                       |                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Operating temperature                                     |                       | 0° to 35° C (32° to 95° F)                                                                                                                                                                                                                                                                                                                                                                                                               |
| Non-operating (storage) temperature                       |                       | -20° to 85° C (-4° to 185° F)                                                                                                                                                                                                                                                                                                                                                                                                            |
| Altitude                                                  |                       | 0 to 5,000 m (0 to 16,400 ft)                                                                                                                                                                                                                                                                                                                                                                                                            |
| Humidity                                                  |                       | 20% to 95%                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Storage Humidity                                          |                       | 10% to 95%                                                                                                                                                                                                                                                                                                                                                                                                                               |
| EMI and Safety Certifications                             |                       | CE Mark - full compliance with LVD and EMC directives<br>Worldwide safety standards - IEC60950-1 and IEC62368-1 :<br>2018, EN62368-1:2014+A11, UL 62368-1<br>Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class<br>B, FCC Class B, CISPR32 Class B, CCC and CEC, CU(EAC),<br>EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE,<br>NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia RCM,<br>BIS, BSMI, UAE, UKCA DoC |
| HP 65W Standard USB Type-C® Halogen Free AC power adapter | Weight                | 240g ± 10g                                                                                                                                                                                                                                                                                                                                                                                                                               |
|                                                           | Input                 | 100-240Vac                                                                                                                                                                                                                                                                                                                                                                                                                               |
|                                                           | Input Efficiency      | 81.50% min at 115 Vac/ 230 Vac @5.00V<br>86.70% min at 115 Vac/ 230 Vac @9.00V<br>88.00% min at 115 Vac/ 230 Vac @12.00V<br>89.00% min at 115 Vac/ 230 Vac @15.00V<br>89.00% min at 115 Vac/ 230 Vac @20.00V                                                                                                                                                                                                                             |
|                                                           | Input frequency range | 47-63Hz                                                                                                                                                                                                                                                                                                                                                                                                                                  |



|                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Input AC current                    | Max. 1.6 A at 90 Vac                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Output                              |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Output power                        | 5V/15W<br>9V/27W<br>12V/60W<br>15V/65W<br>20V/65W                                                                                                                                                                                                                                                                                                                                                                                         |
| DC output                           | 5V/9V/12V/15V/20V                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Hold-up time                        | 100% load 5ms at 115 Vac input                                                                                                                                                                                                                                                                                                                                                                                                            |
| Output Over Current                 | < 8.0A                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Protection                          |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| AC Inlet Type                       | C6                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| DC Cable Connector                  | USB type C                                                                                                                                                                                                                                                                                                                                                                                                                                |
| DC Cable Material                   | Halogen Free                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Connector                           | C6                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Environmental Design                |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Operating temperature               | 0° to 35° C (32° to 95° F)                                                                                                                                                                                                                                                                                                                                                                                                                |
| Non-operating (storage) temperature | -20° to 85° C (-4° to 185° F)                                                                                                                                                                                                                                                                                                                                                                                                             |
| Altitude                            | 0 to 5,000 m (0 to 16,400 ft)                                                                                                                                                                                                                                                                                                                                                                                                             |
| Humidity                            | 20% to 95%                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Storage Humidity                    | 10% to 95%                                                                                                                                                                                                                                                                                                                                                                                                                                |
| EMI and Safety Certifications       | CE Mark - full compliance with LVD and EMC directives<br>Worldwide safety standards - IEC60950-1 and IEC62368-1 :<br>2018, EN62368-1:2014+A11, UL 62368-1<br>Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class<br>B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC),<br>EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE,<br>NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia RCM,<br>BIS, BSMI, UAE, UKCA DoC |



|                                       |                                   |                                                  |
|---------------------------------------|-----------------------------------|--------------------------------------------------|
| HP Long Life 3 cell, 56Whr<br>Polymer | Dimensions                        | 255.8 x 67.8 x 6.68mm (10.07 x 2.67 x 0.26 inch) |
|                                       | Weight                            | 0.205kg +/- 10g (0.474 lb)                       |
|                                       | Cells/Type                        | 3cell Lithium-Ion Polymer cell / 586075          |
|                                       | Energy                            |                                                  |
|                                       | Voltage                           | 11.58V                                           |
|                                       | Amp-hour capacity                 | 4.84Ah                                           |
|                                       | Watt-hour capacity                | 56.04Wh                                          |
|                                       | Temperature                       |                                                  |
|                                       | Operating (Charging)              | 32° to 113° F (0° to 45° C)                      |
|                                       | Operating (Discharging)           | 14° to 140° F (-10° to 60° C)                    |
|                                       | Optional Travel Battery Available | No                                               |
| HP Long Life 6 cell, 68Whr<br>Polymer | Dimensions                        | 275.3 x 87.5 x 6.79mm (10.83 x 3.44 x 0.26 inch) |
|                                       | Weight                            | 0.255kg +/- 10g (0.562 lb)                       |
|                                       | Cells/Type                        | 6cell Lithium-Ion Polymer cell / 594461          |
|                                       | Energy                            |                                                  |
|                                       | Voltage                           | 11.58V                                           |
|                                       | Amp-hour capacity                 | 5.88Ah                                           |
|                                       | Watt-hour capacity                | 68Wh                                             |
|                                       | Temperature                       |                                                  |
|                                       | Operating (Charging)              | 0° to 45° C (32° to 113° F)                      |
|                                       | Operating (Discharging)           | -10° to 60° C (14° to 140° F)                    |
|                                       | Optional Travel Battery Available | No                                               |

|                            |                                                                                                                                                                                             |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AUDIO                      |                                                                                                                                                                                             |
| Codec                      | Realtek ALC3315                                                                                                                                                                             |
| Audio I/O Ports            | 3.5mm Headset: CTIA only; Headphone-out                                                                                                                                                     |
| Internal Speaker Amplifier | Cirrus Logic High-Efficiency Boosted Class D Amplifier                                                                                                                                      |
| Multi-streaming Capable    | Playback multi-streaming can be enabled in the audio control panel to allow independent audio streams to be sent to/from the front jacks or integrated speaker.,<br>Following MSFT Behavior |
| Sampling                   | DAC: Supports resolutions from 16-bit to 24-bit;48.0 kHz to 48.0 kHz<br>ADC: Supports resolutions from 16-bit to 24-bit;44.1 kHz to 48.0 kHz                                                |
| Internal Speaker           | Yes                                                                                                                                                                                         |

FINGERPRINT READER

|                             |                                    |
|-----------------------------|------------------------------------|
| Sensor vendor               | SYNAPTICS                          |
| Sensor type                 | Capacitive                         |
| DPI resolution              | 363 DPI                            |
| Scan area                   | 104 x 86 pixels                    |
| False Rejection Rate        | < 3%                               |
| False Acceptance Rate       | < 0.001%                           |
| Mobile Voltage Operation    | 2.7 V ~ 3.6 V                      |
| Operating Temperature       | 5°C ~ 60°C (41°F ~ 140°F)          |
| Current Consumption Image   | 100 mA max                         |
| Low Latency Wait For Finger | 260 uA                             |
| Capture Rate                | 50 frames/sec                      |
| ESD Resistance              | IEC 61000-4-2 4B (+15KV)           |
| Detection Matrix            | 363 dpi / 7.4 x 6.0 mm sensor area |



## OPTIONS

| Category        | Description                                                                   | Part Number     |
|-----------------|-------------------------------------------------------------------------------|-----------------|
| Adapters        | HP HDMI to VGA Adapter                                                        | H4F02AA         |
|                 | HP USB 3.0 to Gigabit RJ45 Adapter G2                                         | 4Z7Z7AA         |
|                 | HP USB-C to DisplayPort Adapter G2                                            | 8Y8Y1AA         |
|                 | HP USB-C to HDMI 2.0 Adapter                                                  | 1WC36AA         |
|                 | HP USB-C to RJ45 Adapter G2                                                   | 4Z527AA         |
|                 | HP USB-C to USB 3.0 Adapter                                                   | N2Z63AA         |
|                 | HP USB-C to VGA Adapter                                                       | N9K76AA         |
| Audio - Earbuds | Poly Voyager Free 60/60+ Black Earbuds (2 Pieces)                             | 8L5A6AA         |
|                 | Poly Voyager Free 60/60+ Black Earbuds (2 Pieces)                             | 8L649AA,8L5A6AA |
|                 | Poly Voyager Free 60/60+ Microsoft Teams Certified Black Earbuds (2 Pieces)   | 8L5A8AA         |
|                 | Poly Voyager Free 60/60+ Microsoft Teams Certified White Earbuds (2 Pieces)   | 8L5B0AA         |
|                 | Poly Voyager Free 60/60+ White Earbuds (2 Pieces)                             | 8L5B1AA         |
|                 | Poly Voyager Free 60 Carbon Black Earbuds                                     | 7Y8H3AA         |
|                 | Poly Voyager Free 60 Carbon Black Earbuds                                     | 7Y8H4AA         |
|                 | Poly Voyager Free 60 Carbon Black Earbuds                                     | 7Y8L7AA         |
|                 | Poly Voyager Free 60 Carbon Black Earbuds                                     | 7Y8L8AA         |
|                 | Poly Voyager Free 60 Carbon Black Earbuds +Basic Charge Case                  | 7Y8M2AA         |
|                 | Poly Voyager Free 60 UC Black Earbuds +BT700 USB-C Adapter +Basic Charge Case | 7Y8M0AA         |
|                 | Poly Voyager Free 60 White Sand Earbuds                                       | 7Y8L3AA         |
|                 | Poly Voyager Free 60 White Sand Earbuds                                       | 7Y8L4AA         |
|                 | Poly Voyager Free 60 White Sand Earbuds                                       | 7Y8L5AA         |
|                 | Poly Voyager Free 60 White Sand Earbuds                                       | 7Y8L6AA         |
|                 | Poly Voyager Free 60+ Carbon Black Earbuds                                    | 7Y8G3AA         |
|                 | Poly Voyager Free 60+ Carbon Black Earbuds                                    | 7Y8G4AA         |
|                 | Poly Voyager Free 60+ Carbon Black Earbuds                                    | 7Y8G9AA         |
|                 | Poly Voyager Free 60+ Carbon Black Earbuds                                    | 7Y8H0AA         |



|                                          |         |
|------------------------------------------|---------|
| Poly Voyager Free 60+ White Sand Earbuds | 7Y8G5AA |
| Poly Voyager Free 60+ White Sand Earbuds | 7Y8G6AA |
| Poly Voyager Free 60+ White Sand Earbuds | 7Y8G7AA |
| Poly Voyager Free 60+ White Sand Earbuds | 7Y8G8AA |

## Audio - Headset

|                                                                                                 |         |
|-------------------------------------------------------------------------------------------------|---------|
| Poly Blackwire 3210 Monaural USB-C Headset +USB-C/A Adapter                                     | 8X214AA |
| Poly Blackwire 3215 Monaural USB-C Headset                                                      | 8X227AA |
| Poly Blackwire 3220 Stereo USB-C Headset                                                        | 8X228AA |
| Poly Blackwire 3225 Stereo USB-C Headset                                                        | 8X229AA |
| Poly Blackwire 3310 Monaural USB-C Headset                                                      | 8X215AA |
| Poly Blackwire 3310 Monaural USB-C Headset                                                      | 8X216AA |
| Poly Blackwire 3315 Monaural USB-C Headset                                                      | 8X217AA |
| Poly Blackwire 3315 Monaural USB-C Headset                                                      | 8X218AA |
| Poly Blackwire 3320 Stereo USB-C Headset                                                        | 8X219AA |
| Poly Blackwire 3320 Stereo USB-C Headset                                                        | 8X220AA |
| Poly Blackwire 3325 Stereo Microsoft Teams Certified USB-C Headset +3.5mm Plug +USB-C/A Adapter | 8X222AA |
| Poly Blackwire 3325 Stereo USB-C Headset +3.5mm Plug +USB-C/A Adapter                           | 8X221AA |
| Poly Blackwire 5210 Monaural USB-C Headset +3.5mm Plug +USB-C/A Adapter                         | 8X230AA |
| Poly Blackwire 5220 Stereo USB-C Headset                                                        | 8X231AA |
| Poly Blackwire 8225 Stereo USB-C Headset                                                        | 8X223AA |
| Poly Blackwire 8225 Stereo USB-C Headset                                                        | 8X225AA |
| Poly EncorePro 310 Monaural USB-A Headset                                                       | 767G1AA |
| Poly EncorePro 320 Binaural Headset                                                             | 77T26AA |
| Poly EncorePro 320 Stereo USB-A Headset                                                         | 767G0AA |
| Poly EncorePro 320 Stereo USB-C Headset                                                         | 767F9AA |
| Poly EncorePro 510 Monaural Headset                                                             | 783Q2AA |
| Poly EncorePro 510 Monoaural Headset                                                            | 783Q1AA |
| Poly EncorePro 520 Binaural Headset                                                             | 783P6AA |
| Poly EncorePro 520 Binaural Headset                                                             | 783P7AA |



|                                                                          |         |
|--------------------------------------------------------------------------|---------|
| Poly EncorePro 530 Discreet Headset                                      | 783P2AA |
| Poly EncorePro 530 Headset                                               | 783P3AA |
| Poly EncorePro 540 Convertible Headset                                   | 783P1AA |
| Poly EncorePro 710 Monoaural Headset                                     | 783N9AA |
| Poly EncorePro 715 USB-A Monoaural Headset                               | 783N5AA |
| Poly EncorePro 720 Binaural Headset                                      | 8R707AA |
| Poly EncorePro 725 USB-A Stereo Headset                                  | 783M6AA |
| Poly EncorePro HW710 Single Ear Headset +Carry Case +Quick Disconnect    | 8R708AA |
| Poly EncorePro Monoaural 310 Headset                                     | 77T43AA |
| Poly EncorePro Monoaural 515 with USB-A Headset                          | 783R0AA |
| Poly EncorePro Monoaural 515 with USB-A Headset                          | 783R1AA |
| Poly EncorePro Stereo 525 with USB-A Headset                             | 783R2AA |
| Poly EncorePro USB-A Stereo 525 Headset                                  | 783R3AA |
| Poly EncorePro USB-C Monoaural 310 Headset                               | 760Q8AA |
| Poly Savi 7210 Office DECT 1880-1900 MHz Single Ear Headset (EMEA + APJ) | 8D3G9AA |
| Poly Savi 7210 Office DECT 1920-1930 MHz Single Ear Headset (NA)         | 7W6D4AA |
| Poly Savi 7220 Office Binaural DECT 1880-1900 MHz Headset (EMEA + APJ)   | 8D3G8AA |
| Poly Savi 7220 Office Binaural DECT 1920-1930 MHz Headset (NA)           | 7W6D5AA |
| Poly Savi 7310 DECT 1880-1900 MHz Single Ear Headset                     | 8D3G3AA |
| Poly Savi 7310 DECT 1910-1920 MHz Single Ear Headset                     | 8D3G5AA |
| Poly Savi 7310 Headset                                                   | 77T40AA |
| Poly Savi 7310 Monoaural DECT 1880-1900 MHz Headset                      | 8L561AA |
| Poly Savi 7310 Monoaural DECT 1880-1900 MHz Headset                      | 8L575AA |
| Poly Savi 7310 Monoaural DECT 1893-1906 MHz Headset                      | 8L565AA |
| Poly Savi 7310 Monoaural DECT 1893-1906 MHz Headset                      | 8L578AA |
| Poly Savi 7310 Monoaural DECT 1910-1920 MHz Headset                      | 8L566AA |
| Poly Savi 7310 Monoaural DECT 1910-1920 MHz Headset                      | 8L581AA |
| Poly Savi 7310 Monoaural DECT 1920-1930 MHz Headset                      | 7S430AA |



|                                                        |         |
|--------------------------------------------------------|---------|
| Poly Savi 7310 Monaural DECT 1920-1930 MHz Headset     | 8L570AA |
| Poly Savi 7310 Monaural DECT 1920-1930 MHz Headset     | 8L585AA |
| Poly Savi 7310-M DECT 1880-1900 MHz Single Ear Headset | 8D3K7AA |
| Poly Savi 7310-M DECT 1893-1906 MHz Single Ear Headset | 8D3K9AA |
| Poly Savi 7310-M DECT 1910-1920 MHz Single Ear Headset | 8D3L0AA |
| Poly Savi 7310-M DECT 1920-1930 MHz Single Ear Headset | 7S439AA |
| Poly Savi 7320 Stereo DECT 1880-1900 MHz Headset       | 8D3F7AA |
| Poly Savi 7320 Stereo DECT 1880-1900 MHz Headset       | 8L545AA |
| Poly Savi 7320 Stereo DECT 1880-1900 MHz Headset       | 8L553AA |
| Poly Savi 7320 Stereo DECT 1893-1906 MHz Headset       | 8D3F8AA |
| Poly Savi 7320 Stereo DECT 1893-1906 MHz Headset       | 8L546AA |
| Poly Savi 7320 Stereo DECT 1893-1906 MHz Headset       | 8L555AA |
| Poly Savi 7320 Stereo DECT 1910-1920 MHz Headset       | 8D3G0AA |
| Poly Savi 7320 Stereo DECT 1910-1920 MHz Headset       | 8L548AA |
| Poly Savi 7320 Stereo DECT 1910-1920 MHz Headset       | 8L557AA |
| Poly Savi 7320 Stereo DECT 1920-1930 MHz Headset       | 7S429AA |
| Poly Savi 7320 Stereo DECT 1920-1930 MHz Headset       | 8L549AA |
| Poly Savi 7320 Stereo DECT 1920-1930 MHz Headset       | 8L559AA |
| Poly Savi 7320-M Stereo DECT 1880-1900 MHz Headset     | 8D3J6AA |
| Poly Savi 7320-M Stereo DECT 1893-1906 MHz Headset     | 8D3K2AA |
| Poly Savi 7320-M Stereo DECT 1910-1920 MHz Headset     | 8D3K0AA |
| Poly Savi 7320-M Stereo DECT 1920-1930 MHz Headset     | 7S435AA |
| Poly Savi 7410 Monaural DECT 1880-1900 MHz Headset     | 8L589AA |
| Poly Savi 7410 Monaural DECT 1880-1900 MHz Headset     | 8L593AA |
| Poly Savi 7410 Monaural DECT 1893-1906 MHz Headset     | 8L591AA |
| Poly Savi 7410 Monaural DECT 1893-1906 MHz Headset     | 8L594AA |
| Poly Savi 7410 Monaural DECT 1910-1920 MHz Headset     | 8L592AA |
| Poly Savi 7410 Monaural DECT 1910-1920 MHz Headset     | 8L597AA |
| Poly Savi 7410 Monaural DECT 1920-1930 MHz Headset     | 8L7D5AA |
| Poly Savi 7410 Monaural DECT 1920-1930 MHz Headset     | 8L7D7AA |
| Poly Savi 7420 Stereo DECT 1880-1900 MHz Headset       | 8L560AA |
| Poly Savi 7420 Stereo DECT 1880-1900 MHz Headset       | 8L574AA |
| Poly Savi 7420 Stereo DECT 1893-1906 MHz Headset       | 8L563AA |



|                                                                                           |         |
|-------------------------------------------------------------------------------------------|---------|
| Poly Savi 7420 Stereo DECT 1893-1906 MHz Headset                                          | 8L576AA |
| Poly Savi 7420 Stereo DECT 1910-1920 MHz Headset                                          | 8L564AA |
| Poly Savi 7420 Stereo DECT 1910-1920 MHz Headset                                          | 8L579AA |
| Poly Savi 7420 Stereo DECT 1920-1930 MHz Headset                                          | 8L567AA |
| Poly Savi 7420 Stereo DECT 1920-1930 MHz Headset                                          | 8L583AA |
| Poly Savi 8210 Office DECT 1880-1890 MHz Single Ear Headset (EMEA + APJ)                  | 8D3K3AA |
| Poly Savi 8210 Office DECT 1880-1900 MHz Single Ear Headset (EMEA + APJ)                  | 8D3K5AA |
| Poly Savi 8210 Office DECT 1910-1920 MHz Single Ear Headset (NA)                          | 8D3K6AA |
| Poly Savi 8210 Office DECT 1920-1930 MHz Single Ear Headset (NA)                          | 7S445AA |
| Poly Savi 8210 UC DECT 1880-1900 MHz USB-A Headset (EMEA + APJ)                           | 8D3E9AA |
| Poly Savi 8210 UC DECT 1920-1930 MHz USB-A Headset (NA)                                   | 77T29AA |
| Poly Savi 8210 UC Microsoft Teams Certified DECT 1880-1900 MHz USB-A Headset (EMEA + APJ) | 8D3F1AA |
| Poly Savi 8210 UC Microsoft Teams Certified DECT 1920-1930 MHz USB-A Headset (NA)         | 77T31AA |
| Poly Savi 8210-M Office DECT 1880-1900 MHz Single Ear Headset (EMEA + APJ)                | 8D3J8AA |
| Poly Savi 8210-M Office DECT 1910-1920 MHz Single Ear Headset (NA)                        | 8D3K1AA |
| Poly Savi 8210-M Office DECT 1920-1930 MHz Single Ear Headset (NA)                        | 7S447AA |
| Poly Savi 8220 Office Stereo DECT 1880-1890 MHz Headset (EMEA + APJ)                      | 8D3J1AA |
| Poly Savi 8220 Office Stereo DECT 1880-1900 MHz Headset (EMEA + APJ)                      | 8D3J2AA |
| Poly Savi 8220 Office Stereo DECT 1910-1920 MHz Headset (NA)                              | 8D3J4AA |
| Poly Savi 8220 Office Stereo DECT 1920-1930 MHz Headset                                   | 7S4B5AA |



|                                                                                                 |         |
|-------------------------------------------------------------------------------------------------|---------|
| (NA)                                                                                            |         |
| Poly Savi 8220 Stereo DECT 1880-1900 MHz Top +Charging Cradle (EMEA + APJ)                      | 8Y9C4AA |
| Poly Savi 8220 UC DECT 1880-1900 MHz USB-A Headset (EMEA + APJ)                                 | 8D3F2AA |
| Poly Savi 8220 UC DECT 1920-1930 MHz USB-A Headset (NA)                                         | 77T33AA |
| Poly Savi 8220 UC Microsoft Teams Certified DECT 1880-1900 MHz USB-A Headset (EMEA + APJ)       | 8D3F5AA |
| Poly Savi 8220 UC Microsoft Teams Certified DECT 1920-1930 MHz USB-A Headset (NA)               | 77Y82AA |
| Poly Savi 8220-M Office Stereo DECT 1880-1900 MHz Headset (EMEA + APJ)                          | 8D3H8AA |
| Poly Savi 8220-M Office Stereo DECT 1910-1920 MHz Headset (NA)                                  | 8D3J0AA |
| Poly Savi 8220-M Office Stereo DECT 1920-1930 MHz Headset (NA)                                  | 7S4B6AA |
| Poly Savi 8245 DECT 1880-1900 MHz Headset +USB-A to USB-C Cable +D400 (EMEA + APJ)              | 8D3H2AA |
| Poly Savi 8245 Office DECT 1880-1900 MHz USB-A Headset (EMEA + APJ)                             | 8D3H1AA |
| Poly Savi 8245 Office DECT 1910-1920 MHz USB-A Headset (NA)                                     | 8Q005AA |
| Poly Savi 8245 Office DECT 1920-1930 MHz USB-A Headset (NA)                                     | 7W6D1AA |
| Poly Savi 8245-M Microsoft Teams Certified DECT 1880-1900 MHz USB-A Headset +D200 (EMEA + APJ)  | 8D3F4AA |
| Poly Savi 8245-M Office Microsoft Teams Certified DECT 1880-1900 MHz USB-A Headset (EMEA + APJ) | 8D3H7AA |
| Poly Savi 8245-M Office Microsoft Teams Certified DECT 1910-1920 MHz USB-A Headset (NA)         | 8Q006AA |
| Poly Savi 8245-M Office Microsoft Teams Certified DECT 1920-1930 MHz USB-A Headset (NA)         | 7W069AA |
| Poly Savi 8410 Monaural DECT 1880-1900 MHz Headset                                              | 8L5A7AA |



|                                                                       |         |
|-----------------------------------------------------------------------|---------|
| Poly Savi 8410 Monaural DECT 1880-1900 MHz Headset                    | 8L5A9AA |
| Poly Savi 8410 Monaural DECT 1920-1930 MHz Headset                    | 8L7E6AA |
| Poly Savi 8410 Monaural DECT 1920-1930 MHz Headset                    | 8L7E9AA |
| Poly Savi 8420 Stereo DECT 1880-1900 MHz Headset                      | 8L5B2AA |
| Poly Savi 8420 Stereo DECT 1880-1900 MHz Headset                      | 8L5B3AA |
| Poly Savi 8420 Stereo DECT 1920-1930 MHz Headset                      | 8L7F2AA |
| Poly Savi 8420 Stereo DECT 1920-1930 MHz Headset                      | 8L7F5AA |
| Poly Savi 8445 DECT 1880-1890 MHz Convertible Headset                 | 8L5B7AA |
| Poly Savi 8445 DECT 1880-1900 MHz Convertible Headset                 | 8L5B4AA |
| Poly Savi 8445 DECT 1880-1900 MHz Convertible Headset                 | 8L5B6AA |
| Poly Savi 8445 DECT 1910-1920 MHz Convertible Headset                 | 8L5B5AA |
| Poly Savi 8445 DECT 1910-1920 MHz Convertible Headset                 | 8L5B8AA |
| Poly Savi 8445 DECT 1920-1930 MHz Convertible Headset                 | 8L7F1AA |
| Poly Savi 8445 DECT 1920-1930 MHz Convertible Headset                 | 8L7F8AA |
| Poly Voyager 4310 Headset                                             | 77Y93AA |
| Poly Voyager 4310 Monaural Headset                                    | 77Y92AA |
| Poly Voyager 4310 USB-A Headset                                       | 76U48AA |
| Poly Voyager 4310 USB-A Headset                                       | 77Y91AA |
| Poly Voyager 4310 USB-C Headset                                       | 77Y94AA |
| Poly Voyager 4310 USB-C Headset                                       | 77Y95AA |
| Poly Voyager 4310 USB-C Headset                                       | 77Y96AA |
| Poly Voyager 4310-M UC Headset +USB-A to USB-C Cable<br>+BT700 dongle | 7Y210AA |
| Poly Voyager 4310-M USB-C Headset                                     | 77Y97AA |
| Poly Voyager 4320 Headset                                             | 77Z00AA |
| Poly Voyager 4320 Stereo USB-A Headset                                | 77Y99AA |
| Poly Voyager 4320 USB-A Headset                                       | 76U49AA |
| Poly Voyager 4320 USB-A Headset                                       | 77Y98AA |
| Poly Voyager 4320 USB-C Headset                                       | 76U50AA |
| Poly Voyager 4320 USB-C Headset                                       | 77Z30AA |
| Poly Voyager 4320 USB-C Headset                                       | 77Z31AA |
| Poly Voyager 4320-M Headset                                           | 77Z32AA |
| Poly Voyager 4320-M +USB-A to USB-C Cable +BT700 dongle               | 7Y211AA |



|                                                                                            |         |
|--------------------------------------------------------------------------------------------|---------|
| Poly Voyager Focus 2 USB-C-C Headset                                                       | 9T9J3AA |
| Poly Voyager Focus 2 USB-C-C Headset                                                       | 9T9J5AA |
| Poly Voyager Focus 2 USB-C-C Headset                                                       | 9T9J6AA |
| Poly Voyager Surround 80 UC Microsoft Teams Certified USB-C Black Headset +USB-C/A Adapter | 9D452AA |
| Poly Voyager Surround 80 UC Microsoft Teams Certified USB-C Headset +USB-C/A Adapter Demo  | 9C6W5AA |
| Poly Voyager Surround 80 USB-C Headset                                                     | 8G7T9AA |
| Poly Voyager Surround 80 USB-C Headset                                                     | 8G7U0AA |
| Poly Voyager Surround 85 USB-C Headset                                                     | 8G7T7AA |
| Poly Voyager Surround 85 USB-C Headset                                                     | 8G7T8AA |

#### Audio - Speaker phone

|                                                                        |         |
|------------------------------------------------------------------------|---------|
| Poly Sync 10 Speakerphone                                              | 77P34AA |
| Poly Sync 10 Speakerphone +USB-A to USB-C Cable                        | 7S4M6AA |
| Poly Sync 20 USB-C Speakerphone                                        | 7F0J7AA |
| Poly Sync 20+M Speakerphone +USB-A to USB-C Cable +BT700 dongle +Pouch | 7Y215AA |
| Poly Sync 20-M Speakerphone +USB-A to USB-C Cable                      | 7S4M1AA |
| Poly Sync 20-M USB-C Speakerphone                                      | 7F0J8AA |
| Poly Sync 40 Speakerphone                                              | 77P35AA |
| Poly Sync 40+ USB-A USB-C Speakerphone                                 | 77P36AA |
| Poly Sync 40+ USB-A USB-C Speakerphone                                 | 772C5AA |
| Poly Sync 60 Speakerphone                                              | 772C2AA |
| Poly Sync 60 Speakerphone                                              | 77P41AA |
| Poly Sync USB-A 20 Speakerphone                                        | 772C8AA |
| Poly Sync USB-A 20 Speakerphone                                        | 772D2AA |
| Poly Sync USB-A 20+ Speakerphone                                       | 772C6AA |
| Poly Sync USB-A 20+ Speakerphone                                       | 772C9AA |
| Poly Sync USB-A USB-C 10 Speakerphone                                  | 772C3AA |
| Poly Sync USB-A USB-C 40 Speakerphone                                  | 772C4AA |
| Poly Sync USB-C 20+ Speakerphone                                       | 772D0AA |
| Poly Sync USB-C 20+ Speakerphone                                       | 772D1AA |



|           |                                                   |                         |
|-----------|---------------------------------------------------|-------------------------|
| Camera    | HP 625 Webcam                                     | 6Y7L1AA                 |
|           | HP USB-A 325 Webcam                               | 53X27AA,53X27UT         |
| Cases     | HP 14 Convertible Laptop Backpack Tote            | 9C2H1AA                 |
|           | HP 14 Modular Laptop Sleeve                       | 9J499AA                 |
|           | HP 15.6 Modular Laptop Backpack                   | 9J496AA                 |
|           | HP 15.6 Modular Laptop Bag                        | 9J497AA                 |
|           | HP 15.6 Modular Laptop Sleeve                     | 9J498AA                 |
|           | HP Campus blue Backpack                           | 7K0E5AA                 |
|           | HP Campus green Backpack                          | 7K0E4AA                 |
|           | HP Campus XL Marble Stone Backpack                | 7K0E2AA                 |
|           | HP Campus XL Tie Dye Backpack                     | 7K0E3AA                 |
|           | HP Convertible Laptop Stand                       | 9C2H2AA                 |
|           | HP Prelude 15.6 Backpack                          | 1E7D6AA,1E7D6UT,50P32AA |
|           | HP Prelude 15.6 Top Load                          | 1E7D7AA,50P31AA         |
|           | HP Prelude Pro Recycled 15.6 Backpack             | 1X644AA,1X644UT         |
|           | HP Prelude Pro Recycled 15.6 Top Load             | 1X645AA,1X645UT         |
|           | HP Renew Business 14.1 Laptop Bag                 | 3E5F9AA                 |
|           | HP Renew Business 14.1 Laptop Sleeve              | 3E2U7AA                 |
|           | HP Renew Business 15.6 Laptop Bag                 | 3E5F8AA                 |
|           | HP Renew Business 17.3 Laptop Backpack            | 3E2U5UT                 |
|           | HP Renew Business 17.3 Laptop Bag                 | 3E2U6AA                 |
|           | HP Renew Executive 14.1 Laptop Sleeve             | 6B8Y3AA                 |
|           | HP Renew Executive 16 Laptop Backpack             | 6B8Y1AA,6B8Y1UT         |
|           | HP Renew Executive 16 Laptop Bag                  | 6B8Y2AA                 |
|           | HP Travel 18 Liter 15.6 iron gray Laptop Backpack | 6H2D9AA                 |
|           | HP Travel 25 Liter 15.6 iron gray Laptop Backpack | 6H2D8AA                 |
| Commodity | HP USB DVD-Writer External ODD                    | F2B56AA                 |
|           | HP Combination Nano Cable Lock                    | 63B28AA                 |
|           | HP Essential Combination Nano Cable Lock          | 63B31AA                 |
|           | HP Nano Keyed Cable Lock                          | 1AJ39AA                 |
|           | HP Nano Master Keyed Cable Lock                   | 1AJ40AA                 |



|                        |                                                  |                                 |
|------------------------|--------------------------------------------------|---------------------------------|
|                        | HP SureKey Standard/Nano/Wedge Cable Lock        | 6UW42AA                         |
| Docking                | HP Thunderbolt 4 100W G6 Dock                    | 9X472UT                         |
|                        | HP Thunderbolt 4 Ultra 180W G6 Dock              | 9X481UT                         |
|                        | HP Thunderbolt 4 Ultra 280W G6 Dock              | AW5M5UT                         |
|                        | HP Thunderbolt™ 120W G4 Dock                     | 4J0A2AA                         |
|                        | HP Thunderbolt™ 280W G4 Dock w/Combo Cable       | 4J0G4AA                         |
|                        | HP USB-C™ 120W G5 Dock                           | 5TW10AA                         |
|                        | HP USB-C™ G5 Essential Dock                      | 72C71AA                         |
|                        | HP USB-C™/A 120W G2 Universal Dock               | 5TW13AA                         |
| Hub                    | HP 4K USB-C Multiport Hub                        | 6G843AA,6G843UT                 |
|                        | HP Universal USB-C Hub and Laptop Charger Combo  | 9H0H9AA                         |
|                        | HP Universal USB-C Multiport Hub                 | 50H55AA,50H55UT,<br>50H55PT#ACJ |
|                        | HP USB-C to USB-A Hub                            | Z6A00AA                         |
|                        | HP USB-C Travel Hub G3                           | 86S97AA,86S97UT                 |
| Keyboard               | HP 125 Wired Keyboard                            | 266C9AA                         |
|                        | HP 320K USB Wired Keyboard                       | 9SR37AA,9SR37UT                 |
|                        | HP 965 black Ergonomic Wireless Keyboard         | 7E756AA                         |
|                        | HP 975 Dual-Mode USB+Bluetooth Wireless Keyboard | 3Z726AA                         |
| Keyboard & Mouse Combo | HP 225 Wired Mouse and Keyboard Combo            | 286J4AA                         |
|                        | HP 225 Wired Mouse and Keyboard Combo            | 86J24AA                         |
|                        | HP 655 Wireless Keyboard and Mouse Combo         | 860P8AA                         |
|                        | HP Wired Desktop 320MK Mouse and Keyboard        | 9SR36AA,9SR36UT                 |
| Mouse                  | HP 105 Mouse Pad                                 | 8X595AA                         |
|                        | HP 125 Wired Mouse                               | 265A9AA,265A9AT,265A9UT         |
|                        | HP 128 Laser Wired Mouse                         | 265D9AA                         |
|                        | HP 205 Desk Mat                                  | 8X597AA                         |
|                        | HP 320M Wired Mouse                              | 9VA80AA                         |



|                            |                                                  |                 |
|----------------------------|--------------------------------------------------|-----------------|
|                            | HP 685 Comfort Dual-Mode Mouse                   | 8T6M0UT         |
|                            | HP 695 Qi-Charging Wireless Mouse                | 8F1Y4AA         |
|                            | HP 715 Rechargeable Multi-Device Bluetooth Mouse | 6E6F0AA         |
|                            | HP 925 Ergonomic Vertical Wireless Mouse         | 6H1A5AA         |
|                            | HP Creator Black 935 Wireless Mouse              | 1D0K8AA         |
|                            | HP Multi-Device Black 635 Wireless Mouse         | 1D0K2AA         |
| Power                      | HP 110W USB-C Laptop Charger                     | 8B3Y2AA,8B3Y2UT |
|                            | HP 65W LC USB-C AC power adapter                 | 1P3K6AA         |
|                            | HP 65W USB-C Laptop Charger                      | 600Q8UT         |
|                            | HP 65W USB-C Laptop Charger                      | 671R3AA,671R3UT |
| Networking /Communications | HP 4G LTE-Advanced Pro Cat19 WWAN                | B8BD3AA         |
|                            | HP 5G Sub-6 WWAN                                 | B8BD4AA         |



CHANGELOG

| Date of change     | Version History |         | Description of change                 |
|--------------------|-----------------|---------|---------------------------------------|
| February 12, 2025  | V1 to V2        | Updated | Graphics<br>Weight and Dimensions     |
| February 19, 2025  | V2 to V3        | Updated | Power                                 |
| March 3, 2025      | V3 to V4        | Updated | Power                                 |
| April 23, 2025     | V4 to V5        | Added   | Image                                 |
| May 20, 2025       | V5 to V6        | Updated | Docking                               |
| May 21, 2025       | V6 to v7        | Updated | Camera                                |
| June 8, 2025       | V7 to V8        | Removed | Pen Accessory                         |
| July 9, 2025       | V8 to V9        | Updated | Overview                              |
| August 18, 2025    | V9 to V10       | Updated | Software and Security                 |
| September 2, 2025  | V10 to V11      | Updated | Networking /Communications<br>Options |
| September 4, 2025  | V11 to V12      | Updated | Networking /Communications            |
| September 19, 2025 | V12 to V13      | Updated | Software and Security                 |
| October 3, 2025    | V13 to V14      | Updated | Processors                            |
| December 17, 2025  | V14 to V15      | Updated | Graphics                              |
| January 23, 2026   | V15 to V16      | Updated | Callouts<br>Ports                     |
| May 20, 2026       | V16 to V17      | Updated | Storage and Drives                    |
| August 11, 2026    | V17 to V18      | Updated | Networking /Communications            |
| August 17, 2026    | V18 to V19      | Updated | Storage and Drives                    |
| August 20, 2026    | V19 to V20      | Updated | Networking /Communications            |
| September 10, 2026 | V20 to V21      | Updated | Storage and Drives                    |

© Copyright 2026 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Core, Thunderbolt and Intel vPro are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. USB Type-C® and USB-C® are trademarks of USB Implementers Forum. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.