

# **Product Datasheet**

## HDD 1.8TB 3.5in SAS 10000RPM in Hot Swap Caddy



• Product Code: IBM-1800SAS/10-S21

• Product EAN: 5059902178527

• Warranty:

## **Technical Specifications**

Weight & Dimensions

**Width:** 70.1 mm

| Height:  | 15 mm  |
|--|--|
| Depth:   | 100.5 mm   |
| Weight:  | 220 g  |
|  |  |
| Power  |  |
| Power Consumption (typical):   | 7.8 W  |
| Power Consumption (read):  | 6.46 W   |
| Power Consumption (write):   | 7.05 W   |
| Power Consumption (idle):  | 4.55 W   |
| Operating Voltage:   | 5 V  |
| Start-up Current:  | 0.47 A   |
| Operational Conditions   |  |
| Operating Temperature (T-T):   | 5 - 55 °C  |
|  | 0 00 0   |
| Storage Temperature (T-T):   | -40 - 70 °C  |
|  |  |
| Storage Temperature (T-T):   | -40 - 70 °C  |
| Storage Temperature (T-T):  Operating Relative Humidity (H-H):   | -40 - 70 °C<br>5 - 95%   |
| Storage Temperature (T-T):  Operating Relative Humidity (H-H):  Storage Relative Humidity (H-H):   | -40 - 70 °C<br>5 - 95%<br>5 - 95%  |
| Storage Temperature (T-T):  Operating Relative Humidity (H-H):  Storage Relative Humidity (H-H):  Operating Vibration:   | -40 - 70 °C<br>5 - 95%<br>5 - 95%<br>0.5 G   |
| Storage Temperature (T-T):  Operating Relative Humidity (H-H):  Storage Relative Humidity (H-H):  Operating Vibration:  Non-operating Vibration:   | -40 - 70 °C<br>5 - 95%<br>5 - 95%<br>0.5 G<br>3 G  |
| Storage Temperature (T-T):  Operating Relative Humidity (H-H):  Storage Relative Humidity (H-H):  Operating Vibration:  Non-operating Vibration:  Operating Altitude:  | -40 - 70 °C<br>5 - 95%<br>5 - 95%<br>0.5 G<br>3 G<br>-304.8 - 3048 m                             |
| Storage Temperature (T-T):  Operating Relative Humidity (H-H):  Storage Relative Humidity (H-H):  Operating Vibration:  Non-operating Vibration:  Operating Altitude:  Non-operating Altitude:                   | -40 - 70 °C<br>5 - 95%<br>5 - 95%<br>0.5 G<br>3 G<br>-304.8 - 3048 m<br>-304.8 - 12192 m         |
| Storage Temperature (T-T):  Operating Relative Humidity (H-H):  Storage Relative Humidity (H-H):  Operating Vibration:  Non-operating Vibration:  Operating Altitude:  Non-operating Altitude:  Operating Shock: | -40 - 70 °C<br>5 - 95%<br>5 - 95%<br>0.5 G<br>3 G<br>-304.8 - 3048 m<br>-304.8 - 12192 m<br>40 G |

#### Other Features

| Compliance Certificates:           | RoHS               |
|------------------------------------|--------------------|
| Features                           |                    |
| HDD Capacity:                      | 1.8 TB             |
| HDD Speed:                         | 10000 RPM          |
| HDD Size:                          | 3.5"               |
| Interface:                         | SAS                |
| Туре:                              | HDD                |
| Component For:                     | Server/workstation |
| Hot-swap:                          | No                 |
| Storage Drive Buffer Size:         | 128 MB             |
| HDD Interface Transfer Rate:       | 12 Gbit/s          |
| Mean Time Between Failures (MTBF): | 2000000 h          |
| Refurbished:                       | No                 |

## **Origin Storage Limited**

2-4 Rutherford Centre, Rutherford Road, Basingstoke, Hampshire, RG24 8PB UK

Tel: <u>+44 (0)1256 351500</u> | E-Mail: <u>sales@originstorage.com</u> | Web: <u>www.originstorage.com</u>

Copyright 2025 - Origin Storage Limited | All trademarks are the property of their respective owners, E&OE.