
INFORMATION

15.6" portable Full HD IPS monitor with USB-C, built-in speakers & leather cover



Work anywhere with the iiyama ProLite P1670HSC-B1, a 15.6" portable Full HD IPS monitor weighing just 0.7 kg. Slim and light, it's ideal for travel, remote work, or hot-desking.


Quick to set up, it offers two viewing angles (45° or 60°) and a leather cover that protects the screen and doubles as a stand. Built-in speakers deliver clear audio for calls and media, removing the need for extra devices.

A USB-C cable handles the display signal from your laptop to the monitor, while the crisp panel, flicker-free technology, and blue light reduction ensure comfort and productivity all day.




Travel light and stay productive anywhere

Take this 0.7 kg portable monitor with you and create a 15.6" Full HD dual-screen setup perfect for boosting productivity on the go.



Adjust your view for better comfort

Choose between 45° and 60° viewing angles to reduce neck strain and find the most comfortable position for work or entertainment.



Connect with ease, work in comfort

With USB-C delivering up to 15W, your laptop stays charged while you work, using just a single, clutter-free connection. The reversible design means you never have to fumble or check which way to plug it in. It's a simple, reliable solution that keeps your focus on what matters most.



Reduced eye strain & fatigue

Work, study or play longer without eye fatigue, thanks to flicker-free technology and reduced blue light emissions. These features help minimize eye strain and improve visual comfort, allowing you to stay focused and productive throughout the day.

SPECIFICATION

01 DISPLAY CHARACTERISTICS

Diagonal	15.6", 39.5cm
Panel	IPS LED, matte finish
Native resolution	1920 x 1080 @60Hz (2.1 megapixel Full HD)
Aspect ratio	16:9
Panel brightness	250 cd/m ²
Static contrast	1000:1
Advanced contrast	5M:1
Response time (GTG)	3ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	16.7mIn (sRGB: 99%; NTSC: 72%)
Horizontal Sync	15 - 82kHz
Viewable area W x H	344.1 x 193.5mm, 13.5 x 7.6"
Pixel pitch	0.17925mm
Colour	matte, black

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	Mini HDMI (Type-C) x1 (v.1.4) USB-C x2 (v.3.1, PD 15W)
HDCP	yes
Headphone connector	yes

03 FEATURES

Flicker free	yes
Adaptive Sync support	yes
Extra	leather cover
OSD languages	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL, UA
Control buttons	Power/ Signal Select/ Exit, Menu: Scroll Up/ Brightness, Scroll Down/ Volume
User controls	picture adjust (brightness, contrast, Eco, ACR, OD, X-Res technology, black tuner), colour settings (6-axis, i-Style colour, blue light reducer, gamma, colour temp.), OSD settings (H. position, V. position, OSD background, OSD time, OSD control, DDC/CI control, display information), language, miscellaneous (sharpness, video mode adjust, opening logo, power LED), input select, audio settings (volume, mute), recall (recall all)
Speakers	2 x 1W

04 MECHANICAL

Display position adjustments	tilt
Tilt angle	60° up; 45° down

05 ACCESSORIES INCLUDED

Cables	USB-C (1.5m)
Other	quick start guide, safety guide

06 POWER MANAGEMENT


Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	8W typical, 0.5W stand by, 0.3W off mode

07 SUSTAINABILITY


Regulations	CE, TÜV-Bauart, EAC, RoHS support, ErP, WEEE, VCCI, REACH, UKCA
Energy efficiency class (Regulation (EU) 2017/1369)	D

08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	355.5 x 211 x 12mm
Weight (without box)	0.7kg
EAN code	4948570126309







All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © **Iiyama Corporation. All Rights Reserved**