



### Level up work and play with the Red Eagle 32" 4K GB3261UHSCP

Step into the game with the G-MASTER Red Eagle GB3261UHSCP 32" 4K gaming monitor. It's a monitor that fits as easily into a workday setup as it does into a late-night gaming session, built to deliver both enhanced productivity and outstanding visuals. The Ultra HD 3840x2160 resolution panel provides a sharp, detailed image with a high 3000:1 contrast ratio, bringing games and media to life, benefiting from the VA panels deep blacks and vivid highlights. A fast 144Hz Refresh Rate and 0.6ms MPRT response time offer fluid motion and sharp detail, whilst AMD FreeSync™ Premium technology ensures smooth, tear-free gameplay with no distracting artifacts.

Seamlessly switch between devices with the built-in KVM functionality, keeping your setup efficient and organised. Connect your laptop or other devices with a single USB-C cable that carries video and audio while charging at up to 95W.



144Hz

Enjoy ultra-smooth, fluid visuals with a blazing 144Hz refresh rate - perfect for fast-paced gaming, reducing motion blur and delivering sharper, more responsive action.

4K clarity for next-level immersion

Ultra HD resolution delivers crystal-clear visuals and stunning detail, bringing your games to life with incredible sharpness and realism. Whether you're exploring open worlds or battling online!

## 01 DISPLAY CHARACTERISTICS

Design	3-side borderless
Diagonal	31.5", 80cm
Panel	VA, haze 25%
Native resolution	3840 x 2160 @144Hz (8.3 megapixel 4K UHD)
Aspect ratio	16:9
Panel brightness	400 cd/m <sup>2</sup>
Static contrast	3000:1
Advanced contrast	80M:1
Response time (MPRT)	0.6ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	1.07B 8bit+FRC
Horizontal Sync	30 - 340kHz
Viewable area W x H	697.3 x 392.2mm, 27.5 x 15.4"
Pixel pitch	0.182mm
Colour	matte, black

## 02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x2 (v.2.1, max. 3840 x 2160 @144H) DisplayPort x1 (v.1.4 max 3840 x 2160 @144Hz) USB-C x1 (PD 95W, max 3840 x 2160 @144Hz)
USB HUB	x4 (2x Type-A v.3.2 Gen 1 (5Gbps, 4.5W) 2x Type-C (5Gbps, 7.5W))
HDCP	yes
Headphone connector	yes

## 03 FEATURES

KVM switch	yes
Blue light reducer	yes
Flicker free	yes
Adaptive Sync support	FreeSync Premium, DisplayPort Only
Extra	i-Style Colour
HDR	HDR10
OSD languages	EN, DE, FR, ES, IT, PT, RU, JP, CZ, NL, PL
Control buttons	Joystick: power / menu (center), up / signal select, down, left / i-Style colour / night mode / blue light reducer, right / volume
User controls	picture adjust (contrast, brightness, overdrive, HDR, FreeSync Premium, adv. contrast, night mode, blue light reducer, motion blur reduction, gamma), input select (auto, manual / HDMI1, HDMI2, DP, USB-C), audio adjust (volume, mute), store user setting (user modes), colour settings (6-axis, colour temperature, user preset, black tuner), image adjust (i-Style color, X-Res Technology, sharpness, HDMI range, direct drive mode, video mode adjust), language, setup menu (OSD horizontal position, OSD vertical position, OSD time, opening logo, power LED, USB-C speed, DDCI/CI control, USB charge), setup menu (PIP/PBP, KVM, DSC compression), display information, reset (reset all)
Speakers	2 x 5W
Convenience	Kensington-lock™ prepared, DDC/CI, DDC2B

## 04 MECHANICAL

Display position adjustments	height, swivel, tilt
------------------------------	----------------------

<b>Height adjustment</b>	150mm
<b>Swivel stand</b>	90°; 45° left; 45° right
<b>Tilt angle</b>	23° up; 5° down
<b>VESA mounting</b>	100 x 100mm
<b>Cable management system</b>	yes

## 05 ACCESSORIES INCLUDED

<b>Cables</b>	power (1.85m), USB (1m), HDMI (1.85m), DP (1.85m)
<b>Other</b>	quick start guide, safety guide

## 06 POWER MANAGEMENT


<b>Power supply unit</b>	internal
<b>Power supply</b>	AC 100 - 240V, 50/60Hz
<b>Power usage</b>	48W typical, 0.5W stand by, 0.3W off mode

## 07 SUSTAINABILITY

<b>Regulations</b>	CE, TÜV-Bauart, EAC, PSE, RoHS support, ErP, WEEE, VCCI, REACH, UKCA
<b>Energy efficiency class (Regulation (EU) 2017/1369)</b>	G
<b>REACH SVHC</b>	above 0.1%: Lead

## 08 DIMENSIONS / WEIGHT

<b>Product dimensions W x H x D</b>	714 x 453 (603) x 290mm
<b>Box dimensions W x H x D</b>	790 x 510 x 143mm
<b>Weight (without box)</b>	8.6kg
<b>Weight (with box)</b>	12.08kg
<b>EAN code</b>	4948570126286



*All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.*

© IIYAMA CORPORATION. ALL RIGHTS RESERVED