

Specificaties

Eaton FLXTMIC20C2

Eaton Metered Input FlexPDU Gen2, 0U, 27U, C20 input, 2.5m cord, 1ph, 3.7kW, 16A, 200-240V, 24 outlets (20)C13, (4)C19



Foto is representatief



Algemene specificaties

PRODUCT NAME	Eaton Flex PDU G2
CATALOG NUMBER	FLXTMIC20C2
EAN	3553340697395
PRODUCT LENGTH/DEPTH	44.4 mm
PRODUCT HEIGHT	1167 mm
PRODUCT WIDTH	52 mm
PRODUCT WEIGHT	2.4 kg
COMPLIANCES	LVD Directive (CB) EMC Directive RoHS Directive REACH WEEE Directive Packaging Directive
CERTIFICATIONS	EN IEC 63000 EN 55032 RCM Ukr CE EAC Cm IEC 62368-1
MODEL CODE	PDU FLXG2 MI 0U C20 1P 16A 20xC13,4xC19

Elektrische ingang

INPUT CONNECTION	IEC-320 C20
WATTAGE	3.7 kW max
AMPERAGE RATING	16A
INPUT VOLTAGE	200-240V
PHASE	Single-phase
CIRCUIT BREAKER	0
FREQUENCY RATING	50/60 Hz
CORD LENGTH	2.5m

Technologie en communicatie

TYPE	Rack PDU
OUTLET CONTROL	No

SPECIAL FEATURES

- Locking outlets
- Pure copper used for main circuit conductors
- High-temperature resilience up to 50°C
- Measurement accuracy $\pm 1\%$
- Ethernet port speed 10/100 Mbps
- Supported protocols and standards: HTTPS, SSH v2, SNMP, SMTP, DHCP, RADIUS, NTP, TELNET, as well as IPv4 and IPv6
- Full-featured network management through Web or SNMP
- Hot-swappable network Management module
- Metered input measurement (current, power, energy consumption, power factor, etc.)

ETHERNET INTERFACE	Yes
SNMP	Yes
COMMUNICATION	Yes

Elektrische uitgang

OUTLETS	24 outlets (20)C13 (4)C19
NUMBER OF OUTPUTS C13	20
NUMBER OF OUTPUTS C19	4
NUMBER OF OUTLETS WITH EARTH PIN	24

Aanvullende specificaties

OPERATING TEMPERATURE	32° to 122°F (0° to 50°C)
COLOR	Black

PROJECTNAAM:

PROJECTNUMMER:

BEREID DOOR:

DATUM:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. Alle rechten voorbehouden.

Volg ons op sociale media om de laatste product- en ondersteuningsinformatie te ontvangen.

