

Specifications

Eaton FLXTBA332C4



Photo is representative

Eaton Basic FlexPDU G2, 0U, 39U, IEC60309 input, 3m cord, 3ph, 22kW, 32A, 415/240V, 36 outlets (30)C13, (6)C19

General Specifications

PRODUCT NAME	Eaton Flex PDU G2
CATALOG NUMBER	FLXTBA332C4
EAN	3553340697371
PRODUCT LENGTH/DEPTH	44.4 mm
PRODUCT HEIGHT	1729 mm
PRODUCT WIDTH	52 mm
PRODUCT WEIGHT	5.1 kg
COMPLIANCES	LVD Directive (CB) EMC Directive RoHS Directive REACH WEEE Directive Packaging Directive
CERTIFICATIONS	EN IEC 63000 EN 55032 RCM Ukr CE EAC Cm IEC 62368-1
MODEL CODE	PDU FLXG2 BA 0U 309 3P 32A 30xC13,6xC19

Product specifications

SPECIAL FEATURES

- Locking outlets
- Pure copper used for main circuit conductors
- Hydraulic-magnetic circuit breakers (models ≥ 32A) provided
- High-temperature resilience up to 50°C

TYPE Rack PDU

FORM FACTOR 0U (Vertical)

OUTLET CONTROL No

PACKAGE CONTENTS

- Rack PDU
- Mounting accessories
- Quickstart guide
- Safety Instructions

OPERATING TEMPERATURE 32° to 122°F (0° to 50°C)

MOUNTING DIRECTION Vertical

COLOR Black

INPUT CONNECTION IEC-60309 32A 3Ph

CORD LENGTH 3m

WATTAGE 22 kW max

AMPERAGE RATING 32 A

ELECTRIC CURRENT - MAX 32 A

INPUT VOLTAGE 346-415V

PHASE Three-phase

FREQUENCY RATING 50/60 Hz

OUTLETS 36 outlets (30)C13 (6)C19

NUMBER OF OUTPUTS 5-15R 0

NUMBER OF OUTPUTS 5-20R 0

NUMBER OF OUTPUTS 6-15R 0

NUMBER OF OUTPUTS 6-20R 0

NUMBER OF OUTPUTS L14-30R 0

NUMBER OF OUTPUTS L5-20R 0

Resources

BROCHURES

[Eaton FlexPDU G2 Brochure](#)

[Eaton FlexPDU G2 Quick Start Guide](#)

DECLARATIONS OF CONFORMITY

[Eaton FlexPDU G2 EU Declaration of Conformity](#)

DRAWINGS

[FlexPDU G2 FLXTBA332C4 model drawing](#)

MANUALS AND USER GUIDES

[Eaton FlexPDU G2 management operation instructions](#)

NUMBER OF OUTPUTS L5-30R	0
NUMBER OF OUTPUTS L6-20R	0
NUMBER OF OUTPUTS L6-30R	0
NUMBER OF OUTPUTS C13	30
NUMBER OF OUTPUTS C19	6
NUMBER OF OUTPUTS C20	0
NUMBER OF OUTPUTS HARDWIRED	0
NUM OF OUTPUTS PC (SCHUKO)	0
NUMBER OF OUTPUTS (OTHER)	0
NUMBER OF OUTLETS WITH EARTH PIN	36
NO OF OUTLET SUISSE STNDRD TYPE13	0
NO OF OUTLET SUISSE STNDRD TYPE15	0
NO OF OUTLET SUISSE STNDRD TYPE23	0
NO OF OUTLET SUISSE STNDRD TYPE25	0
NUMBER OF UK BS1363 SOCKETS	0
CIRCUIT BREAKER	(6) single-pole
SNMP	Yes
ELECTRICAL CONNECTION	Connecting cord with plug
EVALUATION	Other
MOUNTING DIMENSION (METRICAL)	1729
MOUNTING DIMENSION (STANDARDIZED)	Other
SWITCHABLE	No
OVER VOLTAGE CATEGORY	2
AMPEREMETER	No
WITH SURGE PROTECTION MODULE	No
FITTED WITH:	Fuse Mounting material
NUMBER OF USB CONNECTIONS	0

NUMBER OF RJ45 SOCKETS	0
ACCESSORY	No

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

