

MPN: 0070-24132-W-TOUCH

32" 24/7 Full-HD resolution Touchscreen monitor - Vandal & Waterproof

PRODUCT CHARACTERISTICS

- 1980 x 1080P resolution
- Industrial-grade LED screen
- Designed for CCTV
- High brightness, high contrast, high definition
- Adapts to the latest 3D digital filtering and 3D digital noise reduction technology
- Picture fast response
- 178° wide viewing angle
- High fidelity digital processing, brilliant and vivid video
- 24/7 working status, working continuously for 5 years
- Metal chassis design, anti-static, anti-magnetic field, anti-interference, no radiation
- Menu with convenient Controller



VESA size: 100x100

- 24/7 display
- Security monitor
- EU + UK Power cord included
- HDMI cable included
- Waterproof IP67 in front and IP22 on connectors
- Touchscreen

Specifications

Design	Housing material	Metal
	IK code	IK10
	International Protection (IP) code	IP67
	Market positioning	Industrial
	Product colour	Black
	Protection features	Vandal proof, Waterproof
Display	Aspect ratio	16:9
	Contrast ratio (typical)	1000:1
	Display brightness (typical)	203 cd/m ²
	Display diagonal	32 "
	Display resolution	1920 x 1080 pixels
	Display technology	LCD, LED
	HD type	Full HD
	Native aspect ratio	16:9
	Response time	5 ms
	Touch technology	Single-touch

Display	Touchscreen technology	Resistive touchscreen
	Touchscreen type	Resistive
	Viewing angle, horizontal	178 °
	Viewing angle, vertical	178 °
Ergonomics	On Screen Display (OSD)	Yes
	On Screen Display (OSD) languages	English
	Panel mounting interface	200 x 200 mm
	Plug and Play	Yes
	VESA mounting	Yes
Legal Information	ADR Information	No restrictions
	Country of Origin	China
	Tariff No.	8528529100
	UNSPSC Code	43211902
Multimedia	Built-in speaker(s)	Yes
	Number of speakers	2
Operational conditions	Operating temperature (T-T)	-30 - +85 °C
Other features	Active display area (W x H)	697.4mm(W)×391.9mm(H) mm
	Audio in/out	Yes
	Automatic brightness control	Yes
	Brightness	203 cd/m ²
	Certification	EMC Class A
	Comb filter	3D
	Compatible wall mount	Vesa 100 x 100
	Dimensions (WxDxH)	641 x 51 x 382 mm
	Display language	English
	Light sensor	Yes
	Mean time between failures (MTBF)	50000 h
	Mounting	Stand mount, VESA mount 100 x 100 mm
	Noise filter	Yes
	Package dimensions (WxDxH)	783 x 19.7 x 515 mm
	Picture enhancement	DNle digital image processing
	Power consumption (max)	25 Watt
	Remote control included	Yes
	Speakers	2 x 3W Stereo
	Touchscreen	Yes
	USB ports quantity	1
	Weight	8500 g
Package dimensions	Depth (package,cm)	19.7 cm
	Gross Weight (Package, kg)	11.2 kg

Package dimensions	Height (package,cm)	51.5 cm
	Width (package,cm)	78.3 cm
Packaging content	Power adapter included	Yes
	Quick start guide	Yes
Performance	Operating hours (hours/days)	24/7
Ports & interfaces	AC (power) in	Yes
	HDMI ports quantity	1
	HDMI version	2.0
	VGA (D-Sub) ports quantity	1
Power	AC input frequency	50/60 Hz
	AC input voltage	100-240 V
	Power consumption (average)	25 W
	Socket connector type	C13
Product dimensions	Net Weight (Product, kg)	8.5 kg
	Product Depth	5.1 cm
	Product Height	38.2 cm
	Product Width	64.1 cm
Technical details	Warranty period	5 year(s)
Vendor information	Brand Name	Ernitec
	Homepage	http://www.ernitec.com
	Warranty	5 Year(s)

Other products in this series

Display diagonal	
22	0070-24122-W-TOUCH -RS232
24	0070-24124-W-TOUC H-A
27	0070-24127-W-TOUCH
32	0070-24132-W-TOUCH

Other images

