

Specifications

Eaton EHMIF132K



Eaton Metered Input G4 Rack PDU, 2U, 32A, IEC60309 input, 3m cord, 1ph, 7.4 KW, 100-240V, 16 outlets (8)C13, (8)C39

General specifications

PRODUCT NAME	Eaton Rack PDU G4
CATALOG NUMBER	EHMIF132K
EAN	3553340697555
PRODUCT LENGTH/DEPTH	175 mm
PRODUCT HEIGHT	88.3 mm
PRODUCT WIDTH	444.5 mm
PRODUCT WEIGHT	4.35 kg
WARRANTY	3 year
COMPLIANCES	LVD Directive EMC Directive RoHS Directive WEEE Directive Packaging Directive CISPR 32/EN 55032
CERTIFICATIONS	IEC 62368-1 EN IEC 63000 CE EAC Cm Ukr IEC/EN 61000-6-2 IEC/EN 61000-6-4 EN 61000-3-2 EN 61000-3-3 RCM
MODEL CODE	PDU G4 MI 2U 309 32A 1P 8xC13,8xC39

Product specifications

SPECIAL FEATURES

- Remote Site Management
- Versatile C39 outlet supports C14 or C20 power cord plug
- High retention outlets designed to securely fit standard power cords and support P-Lock power cords
- Cybersecurity standards UL 2900-1 and IEC 62443-4-2
- Hot-Swap network control module
- Network Cascading, connect up to 32 PDUs via network loop
- Power sharing between two network modules PDUs ensures constant access to PDU data & sensors
- 1% IEC Class 1 billing grade measurement accuracy
- Gigabit network card with 2x Gb ports
- Support protocols RestAPI, Modbus TCP, SNMP, LDAP, HTTPS
- Optional sensor Temperature/Humidity
- PDU energy consumption

Resources

BROCHURES	Eaton Rack PDU G4 Brochure EN
DECLARATIONS OF CONFORMITY	EU declaration of conformity Rack PDU G4
DRAWINGS	Eaton Rack PDU G4 2U EHMIF132K technical drawing
MANUALS AND USER GUIDES	Eaton Rack PDU G4 1U and 2U models Installation and Setup manual Eaton Rack PDU G4 Quick Guide

TYPE	Metered input Rack PDU
NUMBER OF MINIATURE CIRCUIT BREAKERS (MCB)	2
FORM FACTOR	2U
OUTLET CONTROL	No
PACKAGE CONTENTS	• Rack PDU • Rack mounting accessories • Quickstart guide • Safety Instructions
OPERATING TEMPERATURE	0° to 60°C (32° to 140°F)
MOUNTING DIRECTION	Horizontal
COLOR	Black

MATERIAL	Steel & Aluminium
INPUT CONNECTION	IEC-60309 32A 1Ph
CORD LENGTH	3m
WATTAGE	7.4 kW max
AMPERAGE RATING	32 A
ELECTRIC CURRENT - MAX	32 A
INPUT VOLTAGE	100-240V
PHASE	Single-phase
FREQUENCY RATING	50/60 Hz
OUTLETS	16 outlets (8) C13, (8) C39
NUMBER OF OUTPUTS C13	8
NUMBER OF OUTPUTS C19	8
NUMBER OF OUTPUTS (OTHER)	8
NUMBER OF OUTLETS WITH EARTH PIN	16
CIRCUIT BREAKER	(2) single-pole
SNMP	Yes
ETHERNET INTERFACE	Yes
SERIAL INTERFACE	Yes
MASS CONFIGURATION	Yes
ELECTRICAL CONNECTION	Connecting cord with plug
EVALUATION	At distance
MOUNTING DIMENSION (METRICAL)	465.2
MOUNTING DIMENSION (STANDARDIZED)	482.6 mm (19 inch)
SWITCHABLE	No
OVER VOLTAGE CATEGORY	2
COMMUNICATION	Yes
SERIES	G4
WITH SURGE PROTECTION MODULE	No
AMPEREMETER	Yes
NUMBER OF USB CONNECTIONS	2
NUMBER OF RJ45 SOCKETS	4

**TOTAL NUMBER OF
OUTLETS**

16

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

