



**Wiremold**  
**4AT Prewired All Power Evolution™ Poke-Thru Device-Black**  
Part No. 4ATCP4RBK



Designed for retrofit and new construction, Evolution Series 4" Poke-Thru devices provide convenient access to power, communications, and audio/video services recessed below floor level - providing maximum device protection. Two gangs of capacity allow you to configure services for the needs of your space. Evolution Series 4" Poke-Thru devices are the perfect fit for kiosks, training rooms, classrooms, healthcare facilities or commercial buildings with open-space architecture.

## Features & Benefits

All Evolution Series Poke-Thru Devices, like every Wiremold Poke-Thru Device, meet and exceed UL scrub water exclusion requirements for tile, carpet, and wood covered floors.

## Specifications

### General Info

Product Line	Wiremold	UPC Number	786564090700
Country Of Origin	United States	Material	Aluminum
Construction	Assembled	Features	Recessed
Cover Style	Surface	Number of Knockouts	10
Application Sector	Commercial, Education, Healthcare, Hospitality	Standard	UL Fire Classified, cULus, NEC
Warranty Type	1-Year from Installation or 2-Years from Day of Sale	Type	Poke-Thru

### Dimensions

Product Width US	5.5 in	Product Weight US	6.263 lb
Product Height US	18.562 in	Product Length US	5.5 in
Cubic Capacity	24.5 in <sup>3</sup>	Core Hole Size	4 in

---

Knockout Size	1-1/2 in, 3/4 in
---------------	------------------

---

### Listing Agencies / 3rd Party Agencies

---

cULus ListingNumber	E2961	cULus Listed	Yes
---------------------	-------	--------------	-----

---

### Additional Information

---

RoHS Compliant	Yes	Product Environmental Profile	Yes
----------------	-----	-------------------------------	-----

---

### Technical Information

---

Floor Type	Carpet, Concrete, Polished Concrete, Terrazzo, Tile, Wood	Is Pre-Wired	Yes
------------	---	--------------	-----

---

Service Capacity	Dual	Fire Rating	2 hr
------------------	------	-------------	------

---

Cable Entry	3/4 in trade size conduit for power	Number of Outlets	4
-------------	-------------------------------------	-------------------	---

---