



Wiremold
4FFATC15-LJB Flush Furniture Feed Poke-Thru Assembly without Junction Box
Part No. 4FFATC15BK-LJB



Complete with one-piece finish flange and conduit assembly. Conduit assembly consists of one 3/4" trade size conduit and one 1 1/2" trade size conduit. Finish cover flange provided with one 3/4" and one 1 1/2" trade size screw plug opening.

Features & Benefits

Integral design component that prevents water, dirt and debris from entering power and communication compartments.

Provides one 3/4" opening for power and one 1 1/2" opening for communication cabling. Provides largest dual service capacity for furniture feed applications in the industry. UL Listed for both power and communication furniture feed applications.

Suitable for use in air handling spaces in accordance with Sec. 300-22 (C) of the National Electrical Code.

UL Listed and UL Fire Classified to U.S. and Canadian safety standards for tile and terrazzo. Includes the new UL requirements under UL514A and UL514C for the scrub water exclusion test for carpet and wood floors..

Step-on-it installation. Quick and easy installation without the need for additional fasteners or the need for a second installer.

Whenever you see the TopGuard protection icon on any Wiremold product, you'll know it meets and exceeds UL scrub water exclusion requirements for tile and carper floors.

Specifications

General Info

| | | | |
|--------------------|--|---------------------|--------------------------------|
| Product Line | Wiremold | Color | Black |
| UPC Number | 786564085454 | Country Of Origin | Mexico |
| Material | Steel | Construction | Assembled |
| Cover Style | Flush, Furniture Feed | Number of Knockouts | 2 |
| Application Sector | Commercial, Education, Healthcare, Hospitality | Standard | UL Fire Classified, cULus, NEC |
| Warranty Type | 1-Year from Installation or 2-Years from Day of Sale | Type | Poke-Thru |

Dimensions

| | | | |
|-------------------|-------------|-------------------|----------------------|
| Product Width US | 8.25 in | Product Weight US | 4.64 lb |
| Product Volume US | 640.0 cu in | Product Depth US | 16.0 in |
| Product Height US | 8.0 in | Cubic Capacity | 24.5 in ³ |
| Core Hole Size | 4 in | Knockout Size | 1-1/2 in, 3/4 in |

Listing Agencies / 3rd Party Agencies

| | | | |
|---------------------|-------|--------------|-----|
| cULus ListingNumber | E2961 | cULus Listed | Yes |
|---------------------|-------|--------------|-----|

Trade Programs

| | |
|-------|-----|
| USMCA | Yes |
|-------|-----|

Additional Information

| | | | |
|----------------|-----|-------------------------------|-----|
| RoHS Compliant | Yes | Product Environmental Profile | Yes |
|----------------|-----|-------------------------------|-----|

Technical Information

| | | | |
|-------------|------------------------------|-------------|------|
| Floor Type | Carpet, Concrete, Tile, Wood | Fire Rating | 2 hr |
| Cable Entry | Conduit | | |
