



QSW-L2110-2S8T (Legacy)

Management Type	Lite Managed
Number of Ports	10
10GbE SFP+	2
2.5GbE (RJ45)	8
Power Supply Description	Adapter
Max. Power Consumption	12W
Input Power Type	DC
Input Voltage Range	12V/1A
MAC Address Table	16K
Total Non-Blocking Throughput	40Gbps
Switching Capacity	80Gbps
Management Interface	Web
Console	RJ45
Energy Efficient Ethernet (IEEE 802.3az complaint)	Yes
Fanless	Yes
Supported Standards	IEEE 802.3 Ethernet IEEE 802.3u 100BASE-T IEEE 802.3ab 1000BASE-T IEEE 802.3bz 2.5G/5GBASE-T IEEE 802.3z 1000BASE-SX/LX IEEE 802.3ae 10G Fiber IEEE 802.3x Full-Duplex Flow Control IEEE 802.1Q VLAN Tagging IEEE 802.3ad LACP IEEE 802.1p Class of Service IEEE 802.3az EEE
Form Factor	Desktop

LED Indicators	Per Port: Speed/Link/Activity Per System: Power/Loop
Buttons	Reset button
Dimensions (HxWxD)	27 x 240 x 105 mm
Weight (Net)	0.63 kg
Weight (Gross)	0.89 kg
Operating Temperature	0°C to 40°C (32°F to 104°F)
Relative Humidity	10~95% Non-condensing
Certifications	CE, VCCI, BSMI, FCC, ICES, RCM, UKCA, LVD
Electromagnetic Compliance	Class B
Jumbo Frames	12K
Warranty	2 Years

Note: QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical performance to the original.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.