

Product datasheet

Specifications



APC NetShelter Rack PDU Advanced Metered, 2U, 3 Phase, 415V, 41.4kVA 60A, 18 Outlets

APDU11454ME

Main

Colour	Black
Product or component type	PDU
PDU type	Metered

Complementary

Input Voltage	415 V AC 3 phases
Height	85 mm
Width	443 mm
Output Voltage	415 V AC 3 phases
Depth	750 mm
Product weight	15.7 kg
Mounting location	Front Rear
Mounting preference	No preference
Input Plug Type	IEC 309 60 A
Mounting mode	Rack-mounted
Rack units	2U
Mounting position	Horizontal
Input current limits	60 A
Network frequency	50/60 Hz
Outlet type and quantity	9 C13/C15/C19/C21 9C13/C15

Environment

IP degree of protection	IP44
Ambient air temperature for operation	-5...60 °C
Relative humidity	5...90 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-20...60 °C
Storage Relative Humidity	5...95 %
Storage altitude	0...15240 m

Packing Units

Rates duty January 2016

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	94 cm
Package 1 Width	60 cm
Package 1 Length	16.5 cm
Package 1 Weight	22.2 kg



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	7547f066-9302-46d9-96e9-461928dd6901
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
PVC free	No
Silicone-free	Yes

Use Longer



Lifetime extension

Repair	No
Updatability	Yes

Use Again



Repack and remanufacture


Take-back	Yes
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

