

Product datasheet

Specifications



Easy UPS 3S Pro 30 kVA 400V 3:3
UPS, 2 internal 7Ah modular battery
strings,expandable to 4

E3SP30KHB1

Main

Main input voltage	3 phases
Input current	(3 phases)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	140 cm
Package 1 Width	50 cm
Package 1 Length	94 cm
Package 1 Weight	451 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Rates duty January 2016



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	73 895 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	4 226 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	705 kg CO2 eq.
Carbon footprint of the installation phase [A5]	48 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	68 226 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	691 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No, we have minimized the use of plastic in the packaging in compliance with regulations and considering quality and safety standards
EU RoHS Directive	Compliant
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	81
End of life manual availability	End of Life Information
Removable battery	Yes

Image of product / Alternate images

Alternative







