

SYSTEM SPECIFICATION

**Built for
work that
doesn't wait.**



**Xerox® C240
Color Printer**



SYSTEM SPECIFICATION

Xerox® C240 Color Printer



PRINT (UP TO:)

SYSTEM SPECIFICATION	XEROX® C240 COLOR PRINTER
Simplex Speed ¹ – Letter/A4 Color, B&W (Up To:)	26/25 pages per minute (ppm)
Duplex Speed ¹ – Letter/A4 Color, B&W (Up To:)	13/13 images per minute (ipm)
Monthly Duty Cycle ² (Up To:) Pages Per Month	50,000
Recommended Average Monthly Print Volume (Up To:) Pages Per Month	2,500
Processor Speed/Memory	1 GHz/1 GB RAM
Connectivity	High-Speed USB 2.0 (Type B), Gigabit Ethernet, Wireless 802.11a/b/g/n/ac + Apple iBeacon
Imaging Technology	Color Laser

PRINT

SYSTEM SPECIFICATION	XEROX® C240 COLOR PRINTER
Print Resolution	4800 Color Quality (2400x600 dpi)
First-print-out Time (As Fast As:)	10.5 B&W/10.7 color (seconds)
Page Description Languages	PostScript® 3 Emulation, PCL®6 Emulation, PCL®5 Emulation, PCL®m, and PDF
Print Features	One-touch UI, Print Quality, Normal, Secure, Saved and Sample Set Job Types, Duplex, Orientation, Collation, Print Job ID in Margins, Draft Mode, N-up, Booklet Layout, Watermark, Tray and Toner Status, Rotate Image 180 Degrees, Saved Settings, Earth Smart Settings

*Driver support only available via Lexmark Universal Print Drivers

MOBILE- AND CLOUD-READY

SYSTEM SPECIFICATION	XEROX® C240 COLOR PRINTER
Mobile Printing	Apple AirPrint™, Mopria® Print Service, Wi-Fi Direct®
Mobile Scanning	Apple AirPrint™, Mopria® Scan Service
Xerox® Workplace Suite and Xerox® Workplace Cloud	Yes
Cloud Connectivity	Yes (via the Xerox® Print and Scan Experience App)

SYSTEM SPECIFICATION

Xerox® C240 Color Printer



PRINT DETAILS	
SYSTEM SPECIFICATION	XEROX® C240 COLOR PRINTER
First-print-out Time – (B&W) (As Fast As:)	10.5 seconds
First-print-out Time – Color (As Fast As:)	10.7 seconds
Warm-up from Off/Hibernate	70 seconds
Resolution	4800 Color Quality (2400x600 dpi)
Page Description Languages	PostScript® 3 Emulation, PCL®6 Emulation, PCL®5 Emulation, PCL®m, and PDF
Unprintable Page Margin	Print: 4.2 mm from each edge
Print Driver Types/Operating Systems	Windows® 11, Windows® 10, Windows® Server 2025, Windows® Server 2022, Windows® Server 2019, Windows® Server 2016, macOS 26, macOS 15, macOS 14, Microsoft Universal Print with Print Support Application. For the latest information about supported Operating Systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com .
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, MS Web Services WSD-Print, 802.1x, Simple Network Management Protocol (SNMP), ThinPrint, Microsoft Universal Print, Bonjour
Font Capability	PCL6 94 Scalable Fonts, 2 Bitmapped PS Emulation, 163 Scalable Fonts

*Driver support only available via Lexmark Universal Print Drivers

DEVICE MANAGEMENT	
SYSTEM SPECIFICATION	XEROX® C240 COLOR PRINTER
Device Management	Xerox® Easy Assist App, Remote Operator Panel, Xerox® Embedded Web Server
Xerox® CentreWare® Web Software	Yes

SECURITY	
SYSTEM SPECIFICATION	XEROX® C240 COLOR PRINTER
Security Protocols/Features	Hardware-Enabled Post-Quantum Cryptography, Digitally Signed Firmware Updates, WPA3, TLS 1.3, OpenSSL cryptographic module validated to FIPS 140-3, Certificate Management, Secure Password Reset, TCP Connection Filtering, Port Filtering, Access Controls, Confidential Print, Non-Volatile Memory Wipe, Fax/Network Separation, Protected USB Ports, Auto-insertion of Sender's Email Address, Login Restrictions, Audit Log, Syslog
WI-FI SECURITY	
Authentication and Encryption Methods	802.11 b/g/n/ac, Infrastructure (BSS) Mode, WEP Encryption (64 and 128-bit keys), WPA2/WPA Personal AES PSK, WPA2-Personal, WPA3-Personal, WPA2/WPA3-Personal, 802.1x: EAP-MD5, EAP-MSCHAPv2, EAP-TLS, EAP-TTLS (CHAPS/MSCHASPV2/PAP), LEAP, PEAP

SYSTEM SPECIFICATION
Xerox® C240 Color Printer



PAPER HANDLING	
SYSTEM SPECIFICATION	XEROX® C240 COLOR PRINTER
MANUAL FEED SLOT	
Standard/Optional	Standard
Capacity	1 sheet
Minimum Media Size	3.7x5.83 in
Minimum Media Size	94x148 mm
Maximum Media Size	8.5x14 in
Maximum Media Size	216x356 mm
Minimum to Maximum Media Weights	60-200 gsm (simplex)/60-105 gsm (duplex)
Media Types Supported	Light Paper, Plain Paper, Heavy Paper, Cardstock, Envelopes, Labels, Recycled, Glossy, Heavy Glossy, Bond, Rough Envelope, Letterhead, Preprinted, Colored Paper, Rough/Cotton, Custom Type
MAIN TRAY	
Capacity ³	250 sheets of 20 lb bond/75 gsm
Minimum Media Size	3.7x5.83 in
Minimum Media Size	94x148 mm
Maximum Media Size	8.5x14 in
MAIN TRAY	
Maximum Media Size	216x356 mm
Minimum to Maximum Media Weight	60-162 gsm (simplex)/60-105 gsm (duplex)
Media Types Supported	Light Paper, Plain Paper, Heavy Paper, Cardstock, Envelopes, Labels, Recycled, Glossy, Heavy Glossy, Bond, Rough Envelope, Letterhead, Preprinted, Colored Paper, Rough/Cotton, Custom Type
OUTPUT CAPACITY	
Output Capacity	100

SYSTEM SPECIFICATION

Xerox® C240 Color Printer



DEVICE SPECIFICATION	
SYSTEM SPECIFICATION	XEROX® C240 COLOR PRINTER
ELECTRICAL REQUIREMENTS	
North America	Voltage: 110–127 VAC +/-10% Current: 10A. Frequency: 57-63Hz
Europe	Voltage: 220–240 VAC +/-10% Current: 5A. Frequency: 47-53 Hz
POWER CONSUMPTION	
Printing (Average)	Simplex: 398 W; Duplex: 247 W
Typical Electricity Consumption (kWh)	0.29
Ready Mode	13.2 W
Sleep Mode	0.8 W
OPERATING ENVIRONMENT AND ACOUSTICS	
Required Temperature Range	50 to 90°F/10 to 32.2°C
Required Relative Humidity (RH)	15 to 80% RH
Sound Power Levels Operating	6.7 Bels(A) or less
Standby	3.0 Bels(A) or less
Sound Pressure Levels Operating	51 dB(A)
Standby	14 dB(A)

DIMENSIONS AND WEIGHTS	
SYSTEM SPECIFICATION	XEROX® C240 COLOR PRINTER
C240 (Engines Unpackaged)	Width: 16.2 in/411 mm Depth: 15.7 in/400 mm Height: 9.6 in/244 mm Weight: 35.9 lb/16.3 kg
Adjustable Printer Stand (Unpackaged)	Width: 23.5 in/597 mm Depth: 23.5 in/597 mm Height: 23.0 in/584 mm Weight: 40.6 lb/18.4 kg
Swivel Cabinet (Unpackaged)	Width: 18.7 in/476 mm Depth: 23.6 in/600 mm Height: 10.3 in/262 mm Weight: 44.1 lb/20.0 kg
C240 (Engines Packaged)	Width: 20.3 in/515 mm Depth: 21.7 in/550 mm Height: 14.6 in/370 mm Weight: 45.1 lb/20.5 kg
Adjustable Printer Stand (Packaged)	Width: 25.8 in/655 mm Depth: 25.8 in/655 mm Height: 25.6 in/650 mm Weight: 50.3 lb/22.8 kg
Swivel Cabinet (Packaged)	Width: 27.6 in/700 mm Depth: 22.4 in/570 mm Height: 13.2 in/335 mm Weight: 53.6 lb/24.3 kg

SYSTEM SPECIFICATION
Xerox® C240 Color Printer



INSTALLATION CONSIDERATIONS

SYSTEM SPECIFICATION	XEROX® C240 COLOR PRINTER
Ventilation clearance requirements. The table below shows the area needed on each side for correct installation.	
Top	4 in/10.2 cm
Rear	4 in/10.2 cm
Left	3 in/7.2 cm
Right	3 in/7.2 cm
Front	3 in/7.2 cm

SYSTEM CERTIFICATION/REGULATORY COMPLIANCE

SYSTEM SPECIFICATION	XEROX® C240 COLOR PRINTER
Certifications	To view the latest list of certifications, go to xerox.com/OfficeCertifications .

WHAT'S IN THE BOX

SYSTEM SPECIFICATION	XEROX® C240 COLOR PRINTER
All items contained in the box	Xerox® C240 Color Printer Power Cord Installation Guide Product Safety Sheet One of Each Print Cartridge (Cyan, Magenta, Yellow): 500 Print Capacity ⁴ ; Black Cartridge: 750 Print Capacity ⁴

SYSTEM SPECIFICATION
Xerox® C240 Color Printer



SUPPLIES AND ACCESSORIES	PART NUMBER
SYSTEM SPECIFICATION	
Genuine Xerox Black Standard Capacity Toner Cartridge, 1,300 Pages ⁴	006R05067
Genuine Xerox Cyan Standard Capacity Toner Cartridge, 1,200 Pages ⁴	006R05068
Genuine Xerox Magenta Standard Capacity Toner Cartridge, 1,200 Pages ⁴	006R05069
Genuine Xerox Yellow Standard Capacity Toner Cartridge, 1,200 Pages ⁴	006R05070
Genuine Xerox Black High Capacity Toner Cartridge, 3,000 Pages ⁴	006R05087
Genuine Xerox Cyan High Capacity Toner Cartridge, 2,500 Pages ⁴	006R05088
Genuine Xerox Magenta High Capacity Toner Cartridge, 2,500 Pages ⁴	006R05089
Genuine Xerox Yellow High Capacity Toner Cartridge, 2,500 Pages ⁴	006R05090
Genuine Xerox Waste Toner Bottle, 15,000 Pages ⁵	008R08165

OPTIONAL ACCESSORIES	PART NUMBER
SYSTEM SPECIFICATION	
Swivel Cabinet	097S05316
Adjustable Printer Stand	097S05315

SYSTEM SPECIFICATION

Xerox® C240 Color Printer



¹ Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

⁴ Average standard pages. Declared yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage, and job run length.

⁵ Waste Toner Bottle yield will vary depending on the image, area coverage, and job run length.

For more information,
visit us at www.xerox.com/en-us/office.

© 2026 Xerox Corporation.

© 2026 Xerox Corporation. All rights reserved. Xerox®, CentreWare®, the Xerox logo and spark graphic are trademarks of XRX Brandco LLC in the United States and/or other countries. The information in this brochure is subject to change without notice.

06/26 TSK-9052 BR42595 24CSS-01UA

