

SYSTEM SPECIFICATION

**Built for
work that
doesn't wait.**



Xerox® C300
Color Printer

Xerox® C303a Color
Multifunction Printer

Xerox® C305ae Color
Multifunction Printer



SYSTEM SPECIFICATION

Xerox® C300 Color Printer and
Xerox® C303a/C305ae Color Multifunction Printers*



PRINT (UP TO:)

SYSTEM SPECIFICATION	XEROX® C300 COLOR PRINTER	XEROX® C303A COLOR MULTIFUNCTION PRINTER	XEROX® C305AE COLOR MULTIFUNCTION PRINTER
Simplex Speed ¹ – Letter/A4 Color, B&W (Up To:)	32/30 pages per minute (ppm)		
Duplex Speed ¹ – Letter/A4 Color, B&W (Up To:)	16/15 images per minute (ipm)		
Monthly Duty Cycle ² (Up To:) Pages Per Month	75,000		
Recommended Average Monthly Print Volume (Up To:) Pages Per Month	5,000		
Processor Speed/Memory	1 GHz 1 GB RAM Optional 128 GB Intelligent Storage Drive (ISD)	1 GHz 1 GB RAM Optional 128 GB Intelligent Storage Drive (ISD)	1.2 GHz 2 GB RAM Optional 128 GB Intelligent Storage Drive (ISD)
Connectivity	Hi-Speed USB 2.0 (Type B rear; Type A front) Gigabit Ethernet, Wireless 802.11a/b/g/n/ac + Apple iBeacon	Hi-Speed USB 2.0 (Type B rear; Type A front) Gigabit Ethernet, Wireless 802.11a/b/g/n/ac + Apple iBeacon	Hi-Speed USB 2.0 (Type B rear; Type A front & rear) Gigabit Ethernet, Wireless 802.11a/b/g/n/ac + Apple iBeacon
Imaging Technology	Color Laser		

PRINT AND COPY

SYSTEM SPECIFICATION	XEROX® C300 COLOR PRINTER	XEROX® C303A COLOR MULTIFUNCTION PRINTER	XEROX® C305AE COLOR MULTIFUNCTION PRINTER
Print Resolution	4800 Color Quality (2400x600 dpi)	4800 Color Quality (2400x600 dpi)	4800 Color Quality (2400x600 dpi) 1200x1200 dpi (Max)
Copy Resolution (Up To:)	N/A	600x600 dpi	
First-print-out Time (As Fast As:)	8.3 B&W/8.6 color (seconds)		
First-copy-out Time (As Fast As:)	N/A	8.1 B&W/8.5 color (seconds)	
Page Description Languages	PostScript® 3 Emulation, PCL® 6 Emulation, PCL® 5 Emulation, PCL® m, and PDF		
Print Features	One-touch UI, Print Quality, Normal, Secure, Saved and Sample Set Job Types, Duplex, Orientation, Collation, Print Job ID in Margins, Draft Mode, N-up, Booklet Layout, Watermark, Tray and Toner Status, Rotate Image 180 Degrees, Saved Settings, Earth Smart Settings		

MOBILE- AND CLOUD-READY

SYSTEM SPECIFICATION	XEROX® C300 COLOR PRINTER	XEROX® C303A COLOR MULTIFUNCTION PRINTER	XEROX® C305AE COLOR MULTIFUNCTION PRINTER
Mobile Printing	Apple AirPrint™, Mopria® Print Service, Chromebook, Wi-Fi Direct®		
Mobile Scanning	Apple AirPrint™, Mopria® Scan Service		
Xerox® Workplace Suite and Xerox® Workplace Cloud	Yes		
Cloud Connectivity	Yes (via the Xerox® Print and Scan Experience App)		

*Product availability varies by country.

SYSTEM SPECIFICATION

Xerox® C300 Color Printer and
Xerox® C303a/C305ae Color Multifunction Printers*



SCAN

SYSTEM SPECIFICATION	XEROX® C300 COLOR PRINTER	XEROX® C303A COLOR MULTIFUNCTION PRINTER	XEROX® C305AE COLOR MULTIFUNCTION PRINTER
Destinations	N/A	Email, Front-side USB drive, File Transfer Protocol (FTP), Network or USB-connected Computer, Windows Network Folder	
File Formats	N/A	Scan Formats: PDF (Searchable PDF available via Xerox® Print and Scan Experience), TIFF, JPEG, PNG	

FAX

SYSTEM SPECIFICATION	XEROX® C300 COLOR PRINTER	XEROX® C303A COLOR MULTIFUNCTION PRINTER	XEROX® C305AE COLOR MULTIFUNCTION PRINTER
Standard Features	N/A	MH/MR/MMR/JBIG/JPEG Compression, Auto Answer, Auto Redial, Auto Reduction, Broadcast Send, Junk Fax Filter, Fax Address Book, Fax Forward, which includes: Fax, Email, FTP, Network Folder, Called Number	

PRINT DETAILS

SYSTEM SPECIFICATION	XEROX® C300 COLOR PRINTER	XEROX® C303A COLOR MULTIFUNCTION PRINTER	XEROX® C305AE COLOR MULTIFUNCTION PRINTER
First-print-out Time – (B&W) (As Fast As:)	8.3 seconds		
First-print-out Time – Color (As Fast As:)	8.6 seconds		
Warm-up from Off/Hibernate	70 seconds	80 seconds	70 seconds
Resolution	4800 Color Quality (2400x600 dpi)	4800 Color Quality (2400x600 dpi)	4800 Color Quality (2400x600 dpi) 1200x1200 dpi (Max)
Page Description Languages	PostScript® 3 Emulation, PCL® 6 Emulation, PCL® 5 Emulation, PCL® m, and PDF		
Unprintable Page Margin	Print: 4.2 mm from each edge	Print: 4.2 mm from each edge; Copy: 3 mm from each edge	
Print from USB	File Formats: Microsoft® Office Formats (Word, Excel, PPT), PDF, Image Formats (JPEG, TIFF, GIF, BMP, PNG, PCX). Options available to configure prints from USB: Paper source, print blank pages, collate, two-sided printing, pages per side orientation, separator sheets, pages per side, pages per side ordering.		
Print Driver Types/Operating Systems	Windows® 11, Windows® 10, Windows® Server 2025, Windows® Server 2022, Windows® Server 2019, Windows® Server 2016, macOS 26, macOS 15, macOS 14, Microsoft Universal Print with Print Support Application. For the latest information about supported Operating Systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com .		
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, MS Web Services WSD-Print, 802.1x, Simple Network Management Protocol (SNMP), ThinPrint, Microsoft Universal Print, Bonjour		
Font Capability	PCL® 6 94 Scalable Fonts, 2 Bitmapped PS Emulation, 163 Scalable Fonts		

*Driver support only available via Lexmark Universal Print Drivers

*Product availability varies by country.

SYSTEM SPECIFICATION

Xerox® C300 Color Printer and
Xerox® C303a/C305ae Color Multifunction Printers*



COPY DETAILS

SYSTEM SPECIFICATION	XEROX® C300 COLOR PRINTER	XEROX® C303A COLOR MULTIFUNCTION PRINTER	XEROX® C305AE COLOR MULTIFUNCTION PRINTER
First-copy-out Time – B&W (As Fast As:)	N/A	8.1 seconds	
First-copy-out Time – Color (As Fast As:)	N/A	8.5 seconds	
Simplex Speed (Up To:)	N/A	32/30 ppm Letter/A4 (Color and B&W)	
Duplex Speed (Up To:)	N/A	16/15 ipm Letter/A4 (Color and B&W)	
Sides (Input/Output)	N/A	1:1, 1:2, 2:1, 2:2	
Quantity	N/A	1-9,999	
Concurrency	N/A	Yes (Copy while printing)	
Copy Features	N/A	Copy From Size; Copy To Size; Scale 25% to 400%; Darkness/Lightness; Sides 1:1, 1:2, 2:1, 2:2; Duplex; Collate; Content Type (Text, Text/Photo, Photo, Graphics). Create Shortcut; Color; Paper Setup; Advanced Imaging, Auto Centre, Background Removal, Contrast, Scan Edge to Edge, Saturation, Color Balance, Edge Erase; Header/Footer; Margin Shift; Overlay; Pages Per Side (2 Pages Per Side, 4 Pages Per Side); Separator Sheets (Between Pages, Between Copies, Between Jobs); Separator Sheet Source	

FAX DETAILS

SYSTEM SPECIFICATION	XEROX® C300 COLOR PRINTER	XEROX® C303A COLOR MULTIFUNCTION PRINTER	XEROX® C305AE COLOR MULTIFUNCTION PRINTER
Fax Speed	N/A	33.6 Kbps	
Memory	N/A	18 MB	
Resolution (dpi)	N/A	B&W standard: 200x100 send, 200x100, 204x98 receive; B&W fine: 200x200 send, 200x200, 204x196 receive; B&W superfine: 300x300 send, 300x300, 204x391 receive; B&W ultrafine: 600x600 send, 600x600, 400x400, 408x391 receive; Color fine: 200x200 send, 200x200 receive; Color superfine: 300x300 send, 300x300, 400x400 receive	
Fax Features	N/A	Auto Answer, Auto Redial, Auto Reduction, Broadcast Send, Junk Fax Filter, Fax Address Book	
Fax Forward Destinations	N/A	Fax, Email, FTP, Network Folder, Called Number	

*Product availability varies by country.

SYSTEM SPECIFICATION

Xerox® C300 Color Printer and
Xerox® C303a/C305ae Color Multifunction Printers*



SCAN DETAILS

SYSTEM SPECIFICATION	XEROX® C300 COLOR PRINTER	XEROX® C303a COLOR MULTIFUNCTION PRINTER	XEROX® C305ae COLOR MULTIFUNCTION PRINTER
Technology	N/A	Color Flatbed Scanner with Single-pass DADF, Contact Image Sensor (CIS)	
Capability	N/A	Single-pass DADF, up to 50 sheets of 20 lb bond/75 gsm	
Concurrency	N/A	Yes (Scan while printing)	
Input Speed – Color (Up To:)	N/A	21/20 ipm Simplex Letter/A4, 42/40 ipm Duplex Letter/A4	
Input Speed – B&W (Up To:)	N/A	48/46 ipm Simplex Letter/A4, 96/92 ipm Duplex Letter/A4	
Resolution (Up To:)	N/A	600x600 dpi	
Resolution (dpi)	N/A	75x75, 150x150, 200x200, 300x300, 400x400, 600x600	
Maximum Scan Area - Automatic Document Feeder (ADF)	N/A	8.5x14 in	
Maximum Scan Area (ADF)	N/A	216x356 mm	
Maximum Scan Area (Platen)	N/A	8.5x11.7 in	
Maximum Scan Area (Platen)	N/A	216x297 mm	
Media Weight (ADF)	N/A	60–90 gsm	
Network Filing Protocol	N/A	FTP, Secure File Transfer Protocol (SFTP), Server Message Block (SMB), USB, Windows Network Folder	
File Formats	N/A	TIFF, JPEG, PDF (OCR available through the Xerox® Print and Scan Experience App for Windows)	
Scan Driver Compatibility	N/A	TWAIN, WIA, ICA	
Scan File Compression Options	N/A	PDF: 1 bit – CCIT G4, ZLIB (Flate), MRC* 8/24 bit – JPEG, ZLIB (Flate), MRC* TIFF: 1 bit – CCITT G4, LZW, Packbits 8/24 bit – LZW, JPEG, Packbits JPG: 8/24 bit – JPEG *Note: MRC is available only if ISD is installed.	
Supported Scan Destinations	N/A	Email, Front-side USB Drive, FTP, LDSS, Network or USB-connected Computer, Windows Network Folder	

DEVICE MANAGEMENT

SYSTEM SPECIFICATION	XEROX® C300 COLOR PRINTER	XEROX® C303A COLOR MULTIFUNCTION PRINTER	XEROX® C305AE COLOR MULTIFUNCTION PRINTER
Device Management	Xerox® Easy Assist App, Remote Operator Panel, Xerox® Embedded Web Server		
Xerox® CentreWare® Web Software	Yes		

ACCESSIBILITY

SYSTEM SPECIFICATION	XEROX® C300 COLOR PRINTER	XEROX® C303A COLOR MULTIFUNCTION PRINTER	XEROX® C305AE COLOR MULTIFUNCTION PRINTER
Accessibility	N/A	N/A	Voice guidance available via speaker or headphone jack

*Product availability varies by country.

SYSTEM SPECIFICATION

Xerox® C300 Color Printer and
Xerox® C303a/C305ae Color Multifunction Printers*



SECURITY

SYSTEM SPECIFICATION	XEROX® C300 COLOR PRINTER	XEROX® C303A COLOR MULTIFUNCTION PRINTER	XEROX® C305AE COLOR MULTIFUNCTION PRINTER
Security Protocols/Features	Hardware-enabled Post-Quantum Cryptography, Digitally Signed Firmware Updates, Trusted Platform Module (TPM 2.0) (C305ae only), WPA3, TLS 1.3, OpenSSL cryptographic module validated to FIPS 140-3, Certificate Management, Secure Password Reset, TCP Connection Filtering, Port Filtering, Access Controls, Confidential Print, Non-Volatile Memory Wipe, Fax/Network Separation, Protected USB Ports, Auto-insertion of Sender's Email Address, Login Restrictions, Audit Log, Syslog		
WI-FI SECURITY			
Authentication and Encryption Methods	802.11 b/g/n/ac, Infrastructure (BSS) Mode, WEP Encryption (64 and 128-bit keys), WPA2/WPA Personal AES PSK, WPA2-Personal, WPA3-Personal, WPA2/WPA3-Personal, 802.1x: EAP-MD5, EAP-MSCHAPv2, EAP-TLS, EAP-TTLS (CHAPS/IMSCHASPV2/PAP), LEAP, PEAP		

PAPER HANDLING

SYSTEM SPECIFICATION	XEROX® C300 COLOR PRINTER	XEROX® C303A COLOR MULTIFUNCTION PRINTER	XEROX® C305AE COLOR MULTIFUNCTION PRINTER
SINGLE-PASS DUPLEX AUTOMATIC DOCUMENT FEEDER (DADF)			
Capacity ³	N/A	50 sheets of 20 lb bond/75 gsm	
Minimum Media Size	N/A	4.13x5.83 in	
Minimum Media Size	N/A	105x148 mm	
Maximum Media Size	N/A	8.5x14 in	
Maximum Media Size	N/A	216x356 mm	
Minimum to Maximum Media Weights	N/A	60–90 gsm	
PLATEN			
Maximum Media Size	N/A	8.5x11.7 in	
Maximum Media Size	N/A	216x297 mm	
MANUAL FEED SLOT			
Standard/Optional	Standard		
Capacity	1 sheet		
Minimum Media Size	3.7x5.83 in		
Minimum Media Size	94x148 mm		
Maximum Media Size	8.5x14 in		
Maximum Media Size	216x356 mm		
Minimum to Maximum Media Weights	60–200 gsm (simplex)/60-105 gsm (duplex)		
Media Types Supported	Light Paper, Plain Paper, Heavy Paper, Cardstock, Envelopes, Labels, Recycled, Glossy, Heavy Glossy, Bond, Rough Envelope, Letterhead, Preprinted, Colored Paper, Rough/Cotton, Custom Type		
MAIN TRAY			
Capacity ³	250 sheets of 20 lb bond/75 gsm		
Minimum Media Size	3.7x5.83 in		
Minimum Media Size	94x148 mm		
Maximum Media Size	8.5x14 in		

*Product availability varies by country.

SYSTEM SPECIFICATION

Xerox® C300 Color Printer and
Xerox® C303a/C305ae Color Multifunction Printers*



MAIN TRAY	
Maximum Media Size	216x356 mm
Minimum to Maximum Media Weight	60-162 gsm (simplex)/60-105 gsm (duplex)
Media Types Supported	Light Paper, Plain Paper, Heavy Paper, Cardstock, Envelopes, Labels, Recycled, Glossy, Heavy Glossy, Bond, Rough Envelope, Letterhead, Preprinted, Colored Paper, Rough/Cotton, Custom Type
2 X OPTIONAL 250-SHEET TRAYS	
Capacity ³	250 sheets of 20 lb bond/75 gsm
Minimum Media Size	3.7x5.83 in
Minimum Media Size	94x148 mm
Maximum Media Size	8.5x14 in
Maximum Media Size	216x356 mm
Minimum to Maximum Media Weight	60-200 gsm (simplex)/60-105 gsm (duplex)
Media Types Supported	Light Paper, Plain Paper, Heavy Paper, Cardstock, Envelopes, Labels, Recycled, Glossy, Heavy Glossy, Bond, Rough Envelope, Letterhead, Preprinted, Colored Paper, Rough/Cotton, Custom Type

STANDARD/MAXIMUM INPUT CAPACITY	
Standard Input Capacity ³	251
Maximum Input Capacity ³	751
OUTPUT CAPACITY	
Output Capacity	100

DEVICE SPECIFICATION			
SYSTEM SPECIFICATION	XEROX® C300 COLOR PRINTER	XEROX® C303A COLOR MULTIFUNCTION PRINTER	XEROX® C305AE COLOR MULTIFUNCTION PRINTER
ELECTRICAL REQUIREMENTS			
North America	Voltage: 110–127 VAC +/-10%; Current: 10A. Frequency: 57-63Hz		
Europe	Voltage: 220–240 VAC +/-10%; Current: 5A. Frequency: 47-53Hz		
POWER CONSUMPTION			
Printing (Average)	Simplex: 432W; Duplex: 270W	Simplex: 436W; Duplex: 272W	Simplex: 432W; Duplex: 274W
Typical Electricity Consumption (kWh)	0.34	0.35	
Ready Mode	14.5W	16.4W	17.5W
Sleep Mode	0.8W	0.8W	
OPERATING ENVIRONMENT AND ACOUSTICS			
Required Temperature Range	50 to 90°F/10 to 32.2°C		
Required Relative Humidity (RH)	15 to 80% RH		
Sound Power Levels Operating	6.7 Bels(A) or less		
Standby	3.1 Bels(A) or less		
Sound Pressure Levels Operating	53 dB(A)		
Standby	14 dB(A)		

*Product availability varies by country.

SYSTEM SPECIFICATION

Xerox® C300 Color Printer and
Xerox® C303a/C305ae Color Multifunction Printers*



DIMENSIONS AND WEIGHTS

SYSTEM SPECIFICATION	XEROX® C300 COLOR PRINTER	XEROX® C303A COLOR MULTIFUNCTION PRINTER	XEROX® C305AE COLOR MULTIFUNCTION PRINTER
C300/C303a/C305ae (Engines Unpackaged)	Width: 16.2 in/411 mm Depth: 15.7 in/400 mm Height: 9.6 in/244 mm Weight: 36.5 lb/16.6 kg	Width: 16.2 in/411 mm Depth: 15.7 in/400 mm Height: 13.6 in/345 mm Weight: 43.6 lb/19.8 kg	Width: 16.2 in/411 mm Depth: 15.8 in/400 mm Height: 13.6 in/345 mm Weight: 44.6 lb/20.2 kg
250-sheet Tray (Unpackaged)	Width: 16.2 in/411 mm Depth: 15.0 in/381 mm Height: 3.4 in/88 mm Weight: 7.38 lb/3.4 kg		
Adjustable Printer Stand (Unpackaged)	Width: 23.5 in/597 mm Depth: 23.5 in/597 mm Height: 23.0 in/584 mm Weight: 40.6 lb/18.4 kg		
Swivel Cabinet (Unpackaged)	Width: 18.7 in/476 mm Depth: 23.6 in/600 mm Height: 10.3 in/262 mm Weight: 44.1 lb/20.0 kg		
C300/C303a/C305ae (Engines Packaged)	Width: 20.3 in/515 mm Depth: 21.7 in/550 mm Height: 14.6 in/370 mm Weight: 45.1 lb/20.5 kg	Width: 20.3 in/515 mm Depth: 22.0 in/560 mm Height: 17.7 in/450 mm Weight: 53.9 lb/24.5 kg	Width: 20.3 in/515 mm Depth: 22.1 in/560 mm Height: 17.9 in/455 mm Weight: 55 lb/25 kg
250-sheet Tray (Packaged)	Width: 17.3 in/440 mm Depth: 18.5 in/470 mm Height: 6.4 in/163 mm Weight: 9.6 lb/4.4 kg		
Adjustable Printer Stand (Packaged)	Width: 25.8 in/655 mm Depth: 25.8 in/655 mm Height: 25.6 in/650 mm Weight: 50.3 lb/22.8 kg		
Swivel Cabinet (Packaged)	Width: 27.6 in/700 mm Depth: 22.4 in/570 mm Height: 13.2 in/335 mm Weight: 53.6 lb/24.3 kg		

*Product availability varies by country.

SYSTEM SPECIFICATION

Xerox® C300 Color Printer and
Xerox® C303a/C305ae Color Multifunction Printers*



INSTALLATION CONSIDERATIONS

SYSTEM SPECIFICATION	XEROX® C300 COLOR PRINTER	XEROX® C303A COLOR MULTIFUNCTION PRINTER	XEROX® C305AE COLOR MULTIFUNCTION PRINTER
Ventilation clearance requirements. The table below shows the area needed on each side for correct installation.			
Top	4 in/10.2 cm	12 in/30.5 cm	
Rear	4 in/10.2 cm	4 in/10.2 cm	
Left	3 in/7.2 cm	3 in/7.2 cm	
Right	3 in/7.2 cm	3 in/7.2 cm	
Front	3 in/7.2 cm	3 in/7.2 cm	

SYSTEM CERTIFICATION/REGULATORY COMPLIANCE

SYSTEM SPECIFICATION	XEROX® C300 COLOR PRINTER	XEROX® C303A COLOR MULTIFUNCTION PRINTER	XEROX® C305AE COLOR MULTIFUNCTION PRINTER
Certifications	To view the latest list of certifications, go to xerox.com/OfficeCertifications .		

WHAT'S IN THE BOX

SYSTEM SPECIFICATION	XEROX® C300 COLOR PRINTER	XEROX® C303A COLOR MULTIFUNCTION PRINTER	XEROX® C305AE COLOR MULTIFUNCTION PRINTER
All items contained in the box	Xerox® C300 Color Printer Power Cord Installation Guide Product Safety Sheet One of Each Print Cartridge (Cyan, Magenta, Yellow): 1200 Print Capacity ⁴ ; Black Cartridge: 1300 Print Capacity ⁴	Xerox® C303a Color MFP Power Cord Installation Guide Product Safety Sheet One of Each Print Cartridge (Cyan, Magenta, Yellow): 1200 Print Capacity ⁴ ; Black Cartridge: 1300 Print Capacity ⁴	Xerox® C305ae Color MFP Power Cord Installation Guide Product Safety Sheet One of Each Print Cartridge (Cyan, Magenta, Yellow): 1200 Print Capacity ⁴ ; Black Cartridge: 2000 Print Capacity ⁴

*Product availability varies by country.

SYSTEM SPECIFICATION

Xerox® C300 Color Printer and
Xerox® C303a/C305ae Color Multifunction Printers*



SUPPLIES AND ACCESSORIES	PART NUMBER
SYSTEM SPECIFICATION	
Genuine Xerox Black Standard Capacity Toner Cartridge, 1,300 Pages ⁴	006R05051
Genuine Xerox Cyan Standard Capacity Toner Cartridge, 1,200 Pages ⁴	006R05052
Genuine Xerox Magenta Standard Capacity Toner Cartridge, 1,200 Pages ⁴	006R05053
Genuine Xerox Yellow Standard Capacity Toner Cartridge, 1,200 Pages ⁴	006R05054
Genuine Xerox Black High Capacity Toner Cartridge, 3,000 Pages ⁴	006R05071
Genuine Xerox Cyan High Capacity Toner Cartridge, 2,500 Pages ⁴	006R05072
Genuine Xerox Magenta High Capacity Toner Cartridge, 2,500 Pages ⁴	006R05073
Genuine Xerox Yellow High Capacity Toner Cartridge, 2,500 Pages ⁴	006R05074
Genuine Xerox Black Extra High Capacity Toner Cartridge, 6,200 Pages ⁴	006R05091
Genuine Xerox Cyan Extra High Capacity Toner Cartridge, 6,500 Pages ⁴	006R05092
Genuine Xerox Magenta Extra High Capacity Toner Cartridge, 6,400 Pages ⁴	006R05093
Genuine Xerox Yellow Extra High Capacity Toner Cartridge, 6,500 Pages ⁴	006R05094
Genuine Xerox Waste Toner Bottle, 15,000 Pages ⁵	008R08165

OPTIONAL ACCESSORIES	PART NUMBER
SYSTEM SPECIFICATION	
250-sheet Tray	097S05292
Internal Storage Drive (ISD)	097S05314
Card Reader (USB Contactless Front Reader TWN4 MultiTech-P LEGIC) [#]	497K26210
Card Reader (USB Contactless Front Reader TWN MultiTech-PI) [#]	497K25970
Swivel Cabinet	097S05316
Adjustable Printer Stand	097S05315

*Product availability varies by country.

SYSTEM SPECIFICATION

Xerox® C300 Color Printer and
Xerox® C303a/C305ae Color Multifunction Printers*



¹ Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

⁴ Average standard pages. Declared yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and job run length.

⁵ Waste Toner Bottle yield will vary depending on image, area coverage, and job run length.

For more information,
visit us at www.xerox.com/en-us/office.

Product availability varies by country. Visit xerox.com or contact your local Xerox representative for details.

© 2026 Xerox Corporation.

© 2026 Xerox Corporation. All rights reserved. Xerox®, CentreWare®, the Xerox logo and spark graphic are trademarks of XRX Brandco LLC in the United States and/or other countries. The information in this brochure is subject to change without notice.

05/26 TSK-7925 BR42608 XXXXX-XX

