

Statement of Volatility

Dell Pro 27 Monitor E2726H

⚠ CAUTION: A CAUTION indicates either potential damage to hardware or loss of data and tells you how to avoid the problem.

The Dell E2726H monitor contains both volatile and non-volatile components. Volatile components erase their data immediately after power is removed from the component. Non-volatile components continue to retain their data even after power is removed from the component. The following non-volatile components are present on the Dell E2726H monitor system board.

Table 1. List of Non-Volatile components on System Board

Description	Reference Designator	Volatility Description	User Accessible for external data	Remedial Action (Action necessary to prevent loss of data)
Serial Flash ROM GD25Q80ETIGR	U302	Non-volatile Flash memory, 8M bit. To store scaler firmware.	No	Part place on Interface Board, it has hardware/software write protected.
EEPROM GT24C16H-2GLI-TR	U303	Non-volatile memory, 16K bit. To store scaler data.	No	Part place on Interface Board, it has hardware/software write protected.
EEPROM GT24C02H-2GLI-TR	U1001	Non-volatile memory, 2K bit. To store scaler data.	No	Part place on interface board, it has hardware/software write protected.

⚠ CAUTION: All other components on the system board lose data if power is removed from the computer. Primary power loss (unplugging the power cable and removing the battery) destroys all user data on the memory. Secondary power loss (removing the on-board coin-cell battery) destroys system data on the system configuration and time-of-day information.