



Statement of Volatility - Dell Pro P 43 4K Huddle Conferencing Monitor P4326QEB

 **CAUTION:** A CAUTION indicates either potential damage to hardware or loss of data and tells you how to avoid the problem.

The Dell P4326QEB monitor contains both volatile and non-volatile components. Volatile components erase their data immediately after power is removed from the component. Non-volatile components continue to retain their data even after power is removed from the component. The following non-volatile components are present on the Dell P4326QEB monitor system board.

Table 1. List of Non-Volatile Components on System Board

Description	Reference Designator	Volatility Description	User Accessible for external data	Remedial Action (Action necessary to prevent loss of data)
Serial Flash ROM MX25L3233F M2I-08G	U302	Non-volatile Flash memory, 32M bit. To store scaler firmware.	No	The part is installed on the Interface Board and is configured with both hardware and software-level write protection.
EEPROM M24128-BRMN6TP	U303	Non-volatile memory, 128K bit. To store scaler data.	No	The part is installed on the Interface Board and is configured with both hardware and software-level write protection.
Serial Flash ROM MX25V8035 FM1I	U1303	Non-volatile Flash memory, 8M bit. To store PD firmware.	No	The part is installed on the Interface Board and is configured with both hardware and software-level write protection.
Serial Flash ROM MX25V4035 FM1I	U1902	Non-volatile Flash memory, 4M bit. To store HUB1 firmware.	No	The part is installed on the Interface Board and is configured with both hardware and software-level write protection.
Serial Flash ROM MX25L6473F M2I-08G	U2004	Non-volatile Flash memory, 64M bit. To store DSP firmware.	No	The part is installed on the Interface Board and is configured with both hardware and software-level write protection.

 **CAUTION:** All other components on the system board lose data if power is removed from the computer. Primary power loss (unplugging the power cable and removing the battery) destroys all user data on the memory. Secondary power loss (removing the on-board coin-cell battery) destroys system data on the system configuration and time-of-day information.