



# FREE YOUR DESK

## ULTRA LOW-PROFILE WALL MOUNTS FOR THE CISCO TELEPRESENCE<sup>™</sup> EX90

Chief has developed two new mounting interfaces for the Cisco TelePresence EX90 that provide flexible solutions to enhance the user experience. These innovative solutions save valuable desk space – or require no desk at all, giving you great flexibility in choosing locations where the EX90 can be used for in-person video communications.



*(Shown with the TS218SU)*

Thinstall<sup>™</sup> wall mounts are engineered to deliver ultra low-profile installations with state-of-the-art functionality for the EX90. Installer-inspired features make installation safe and easy. The Kontour<sup>™</sup> articulating mount is an elegantly designed desk mount solution that provides patented Centris<sup>®</sup> tilt for a flexible, ergonomic installation.

### FEATURES

- 1 FULL EXTENSION**  
Mounts extend for maximum viewing potential
- 2 CENTRIS<sup>™</sup> LOW PROFILE TILT**  
Mounts provide up to 15 degrees of effortless fingertip tilt to achieve optimal viewing angles
- 3 INTEGRATED CABLE MANAGEMENT**  
Enclosed, tool-less cable covers make it easy to route power and signal cables
- 4 INCLUDED SHELF**  
Provides a dedicated space for the Cisco TelePresence Touch 8

### ORDERING OPTIONS

JSB2090B  
compatible with Thinstall Series TS318TU and TS218SU

FSB4090B  
Compatible with Kontour Series K2C100B



DUAL STUD SWING ARM MOUNT - SPECIFICATIONS

REQUIRES JSB2090B



TS318TU

|                            |   |
|----------------------------|---|
| Extension                  | 18" (457 mm)                              |
| Tilt                       | -15°                                      |
| Height Adjust              | 1" (25 mm)                                |
| Dimensions (HxWxD)         | 17.2 x 23.6 x 1.8"<br>(437 x 599 x 46 mm) |
| Max Mounting Pattern (H,W) | 15.75" (400 mm)<br>23.62" (600 mm)        |
| Color                      | Black                                     |
| Weight Capacity            | 75 lbs (34 kg)                            |

SINGLE STUD SWING ARM MOUNT - SPECIFICATIONS

REQUIRES JSB2090B



TS218SU

|                            |                                    |
|----------------------------|------------------------------------|
| Depth from Wall            | 1.5" (38 mm)                       |
| Extension                  | 18" (457 mm)                       |
| Tilt                       | -12°                               |
| Height Adjust              | 1" (25 mm)                         |
| Max Mounting Pattern (H,W) | 15.75" (400 mm)<br>15.75" (400 mm) |
| Color                      | Black                              |
| Weight Capacity            | 75 lbs (34 kg)                     |

ARTICULATING DESK MOUNT - SPECIFICATIONS

REQUIRES FSB4090B



K2C100B

|                     |                          |
|---------------------|--------------------------|
| Extension           | 19.2" (490 mm)           |
| Tilt                | -15°/+15°                |
| Height Adjust       | 9.63" (245 mm)           |
| Desktop Clamp Range | 0.5" - 3.25" (12 - 82mm) |
| Color               | Black                    |
| Weight Capacity     | 40 lbs (18.1 kg)         |



A BRAND OF MILESTONE AV TECHNOLOGIES ■ [www.chiefmfg.com](http://www.chiefmfg.com)

USA P 800.582.6480 / +1.952.225.6000 ■ F 877.894.6918 / +1.952.894.6918 ■ [chief@chiefmfg.com](mailto:chief@chiefmfg.com)  
 Canada P 877.345.4329 ■ F 888.377.5314 ■ [info@chiefmounts.ca](mailto:info@chiefmounts.ca)  
 EMEA P +31 495 580 852 ■ F +31 495 580 845 ■ [europe.chief@milestone.com](mailto:europe.chief@milestone.com)  
 Asia Pacific P +852 2145 4099 ■ F +852 2145 4477 ■ [asia.chief@milestone.com](mailto:asia.chief@milestone.com)

In British Columbia, Milestone AV Technologies ULC carries on business as MAVT Milestone AV Technologies ULC.

©2012 Milestone AV Technologies, a Duchossois Group Company. 120121B 11/12 Chief is a registered trademark of Milestone AV Technologies. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All patents are protected under existing designations. Other patents pending.