



Notes:

1. Plug: JT006A/2\*JT-ST3 Clear injection no scratch and dirt;
2. Cable: H05VV-F 3G0.75mm<sup>2</sup> Jacket  $\phi 6.5 \pm 0.2$  Conductor  $24 \times 0.198 \pm 0.004$  Core  $\phi 2.4 \pm 0.1$   
Cable Mark: <VDE> H05VV-F 3G0.75mm<sup>2</sup>
3. Test: Hi-pot: Inner Voltage AC2500V/1S External Voltage AC4000V/1S  
current leakage 1mA, insulation resistance no less than 5M $\Omega$ , no strike out;

尺寸标注		公差		第三角度投影			第X张 共X张		
DIMENSION		TOLERANCE		版本	比例	1:1	单位	图框	图幅
LENGTH	ANGLE	VERSION	A	PROPORTION	UNIT	mm	图框	图幅	
<200	$\pm 0.1$	$\pm 0.5^\circ$	FILE LOCATION						
200~500	$\pm 0.3$		FIGURE NO				材料		
500~800	$\pm 0.5$		FIGURE NO				RESIN MATERIALS		
<800	$\pm 1.0$		FIGURE NO				包装		
设计	王绪安	产品名称		JT006A/2*JT-ST3					
审核		PRODUCTOR NAME							
批准									
批准									