

DIGITUS DisplayPort Adapter / Converter

AK-340403-001-S
EAN 4016032289289



DisplayPort adapter cable, DP - HD15 M/F, 0.15m,w/interlock, DP 1.2 compatible, bl

This adapter / converter suits for example ideal to connect a notebook or computer with DP interface to a VGA monitor, beamer, LCD/TFT monitor with a VGA monitor cable.

Use your existing VGA monitor with a DisplayPort device without loss of quality

- Supports up to 1080p with 60Hz
- Supports monitor resolutions of up to 1920 x 1200p
- Supported transmission modes: RBR, HBR, HBR2
- Maximal bandwidth: 21,6 Gbps
- HBR-Version/transfer mode: HBR2 (5,40 Gbit/s per lane)
- HDCP-Version: HDCP 1.3
- Assortment: DisplayPort Cables
- AWG: 28

- Color cable: black
- Color connector: black
- Connector 1: DP, plug
- Connector 2: HD15, jack
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.2
- Ferrite filter: none
- HDTV Standard: Ultra HD 4K
- Hoods: molded
- Interlock: Snap fastener
- Packaging: Polybag
- Wire material: CU
- Length: 0.15 m
- AOC - Active Optical Cable: no
- Shielding: Double shielding

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	200	8.00	38.10	30.20	31.10	35,784.30
Packaging Unit Inside	10	0.40	40.60	40.60	8.10	13,351.70
Packaging Unit Single	1	0.04	20.00	15.00	1.62	486.00
Net single without Packaging	1	0.03	24.50	4.50	1.50	0.00

More images:



