

MPN: B-UTP50750

CAT5e U/UTP Network Cable 7.5m, Orange

CAT5e cables enables a convenient and reliable connection from one network device, such as switch, modem or router, to another or to the infrastructure at large through a patch panel, keystone jack or wall outlet. This cable are also used a lot in small office and home network and entertainment applications. These cables are tested up to 100Mhz (CAT5e standard) and are backwards compatible with CAT5 cables. They are produced with latch protection, which prevents the connector do be damaged when you install the cable through an installation with very less space.



- To order a full box, please select the following quantity: 40 pcs.
- Suitable for Gigabit (10/100/1000 Mbit) network
- CAT5e tested up to 100MHz
- with Latch Protection
- with slimline relief
- with gold plated PINs

Specifications

| | | |
|--------------------------------|---------------------------|---|
| Features | AWG wire size | 26/7 |
| | Cable length | 7.5 m |
| | Cable shielding | U/UTP (UTP) |
| | Cable standard | Cat5e |
| | Conductor material | Copper-Clad Aluminium (CCA) |
| | Conductor type | Stranded |
| | Connector 1 | RJ45 |
| | Connector 1 gender | Male |
| | Connector 2 | RJ45 |
| | Connector 2 gender | Male |
| | Data transfer rate | 1000 Mbit/s |
| | Frequency | 100 MHz |
| | Jacket material | Polyvinyl chloride (PVC) |
| | Product colour | Orange |
| | RoHS compliance | Yes |
| Other features | Product series | Round Cable |
| | Technical features | Kink Protection, strain relief and Latch Protection |
| Packaging data | Quantity per pack | 1 pc(s) |
| Vendor information | Brand Name | MicroConnect |
| | Homepage | https://microconnect.me/ |
| | Warranty | 25 Year(s) |
| Weight & dimensions | Outer diameter | 4.5 mm |

Other products in this series

| Cable length | Black | Blue | Green | Grey |
|--------------|-------------|-------------|-------------|------------|
| 0.25 | B-UTP50025S | B-UTP50025B | B-UTP50025G | B-UTP50025 |
| 0.5 | B-UTP5005S | B-UTP5005B | B-UTP5005G | B-UTP5005 |
| 1 | B-UTP501S | B-UTP501B | B-UTP501G | B-UTP501 |
| 1.5 | B-UTP5015S | B-UTP5015B | B-UTP5015G | B-UTP5015 |
| 2 | B-UTP502S | B-UTP502B | B-UTP502G | B-UTP502 |
| 3 | B-UTP503S | B-UTP503B | B-UTP503G | B-UTP503 |
| 5 | B-UTP505S | B-UTP505B | B-UTP505G | B-UTP505 |
| 7.5 | B-UTP5075S | B-UTP5075B | B-UTP5075G | B-UTP5075 |
| 10 | B-UTP510S | B-UTP510B | B-UTP510G | B-UTP510 |
| 15 | B-UTP515S | B-UTP515B | B-UTP515G | B-UTP515 |
| 20 | B-UTP520S | B-UTP520B | B-UTP520G | B-UTP520 |
| 30 | B-UTP530S | | | |

| Cable length | Orange | Purple | Red | White |
|--------------|-------------|-------------|-------------|-------------|
| 0.25 | B-UTP50025O | B-UTP50025P | B-UTP50025R | B-UTP50025W |
| 0.5 | B-UTP5005O | B-UTP5005P | B-UTP5005R | B-UTP5005W |
| 1 | B-UTP501O | B-UTP501P | B-UTP501R | B-UTP501W |
| 1.5 | B-UTP5015O | B-UTP5015P | B-UTP5015R | B-UTP5015W |
| 2 | B-UTP502O | B-UTP502P | B-UTP502R | B-UTP502W |
| 3 | B-UTP503O | B-UTP503P | B-UTP503R | B-UTP503W |
| 5 | B-UTP505O | B-UTP505P | B-UTP505R | B-UTP505W |
| 7.5 | B-UTP5075O | B-UTP5075P | B-UTP5075R | B-UTP5075W |
| 10 | B-UTP510O | B-UTP510P | B-UTP510R | B-UTP510W |
| 15 | B-UTP515O | B-UTP515P | B-UTP515R | B-UTP515W |
| 20 | B-UTP520O | B-UTP520P | B-UTP520R | B-UTP520W |
| 30 | | | | |

| Cable length | Yellow |
|--------------|-------------|
| 0.25 | B-UTP50025Y |
| 0.5 | B-UTP5005Y |
| 1 | B-UTP501Y |
| 1.5 | B-UTP5015Y |

| Cable length | Yellow |
|--------------|------------|
| 2 | B-UTP502Y |
| 3 | B-UTP503Y |
| 5 | B-UTP505Y |
| 7.5 | B-UTP5075Y |
| 10 | B-UTP510Y |
| 15 | B-UTP515Y |
| 20 | B-UTP520Y |
| 30 | |