

# Product datasheet

Specifications



## APC Smart-UPS On-Line SRT Battery Pack for 5/6kVA Extended runtime model 192V

SRT192BP

EAN Code: 0731304301769

### Main

Product or component type	External battery pack
Number of rack unit	3U
Battery type	Lead-acid battery
Provided equipment	Documentation CD Installation guide Warranty card
Range of product	Smart-UPS Battery Systems
Replacement battery	<a href="#">APCRBC140</a>

### Batteries & Runtime

Number of battery free slots	0
Number of battery filled slots	0
Device mounting	Stand alone battery stack
Battery voltage	192 V
Number of battery replacement quantity	2

### Physical

Colour	Black
Height	432 mm
Width	130 mm
Depth	682.7 mm
Product weight	91 kg
Mounting mode	Rack-mounted with kit

### Output

Battery capacity	10 Ah
------------------	-------

### Environmental

Ambient air temperature for operation	0...40 °C
Operating altitude	0...10000 ft
Relative humidity	0...95 % non-condensing
Ambient air temperature for storage	-15...45 °C
Storage altitude	0...4572 m

---

Storage Relative Humidity	0...95 % non-condensing
---------------------------	-------------------------

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	42.000 cm
------------------	-----------

---

Package 1 Width	60.000 cm
-----------------	-----------

---

Package 1 Length	100.000 cm
------------------	------------

---

Package 1 Weight	101.500 kg
------------------	------------

## Logistical informations

---

Country of origin	VN
-------------------	----

## Contractual warranty

---

Warranty (in months)	24
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint	749 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	376 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	25 kg CO2 eq.
Carbon footprint of the installation phase [A5]	29 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	285 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	36 kg CO2 eq.

## Use Better

### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	488c31fb-3af8-42cf-9558-1362d000a07e
EU RoHS Directive	<a href="#">Compliant By Exemption</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>

## Use Longer

### Lifetime extension

Repair	No
--------	----

## Use Again

### Repack and remanufacture

Recyclability potential, in %	48
End of life manual availability	<a href="#">End of Life Information</a>
Removable battery	User replaceable
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

---





