

MPN: MO-GLC-BX10-U

SFP 1 Gbps, SMF, 20 km, LC, DDMI support, Compatible with Cisco GLC-BX10-U

Micro-Optics products provide seamless connectivity for all your current and future network hardware needs.

- **100% Cisco Compatible**



Specifications

Features	Brand compatibility	Cisco
	Certification	MSA
	Compatible products	Cisco GLC-BX10-U
	Easy to install	Yes
	Plug and Play	Yes
	RoHS compliance	Yes
Operational conditions	Operating temperature (T-T)	-45 - 75 °C
	Storage relative humidity (H-H)	10 - 85 %
	Storage temperature (T-T)	-40 - 85 °C
Packaging data	Number of products included	1 pc(s)
Performance	Digital Diagnostics Monitoring (DDM)	Yes
	Duplex system	Full
	Fiber optic connector	LC
	Fiber ports quantity	1
	Interface type	SFP
	Maximum data transfer rate	1000 Mbit/s
	Maximum transfer distance	20000 m
	Multi-mode fiber (MMF) supported	No
	Rx wavelength (min)	1550 nm
	SFP transceiver type	Fiber optic
	Single-mode fiber (SMF) supported	Yes
	Tx wavelength (min)	1310 nm
Vendor information	Brand Name	Lanview

Vendor information	Warranty	5 Year(s)
	Package type	White Box