

DIGITUS Industrial mini GBIC (SFP) Module, 1.25 Gbps, 20km

DN-81011

EAN 4016032307587



1.25 Gbps SFP Module, Singlemode, Industrial vers. LC Duplex Connector, 1310nm, up to 20km

The DIGITUS® mini GBIC (SFP) transceiver modules offer highest quality and reliability. Whether from switch to switch, converter to switch, converter to converter or any else application: The wide product range of DIGITUS® modules makes possible a flexible usage of the fiber technology. The conformity to the MSA (Multi Source Agreement) standard ensures a compatibility to third party manufacturers.

The plug and play fiber connection

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Compatible with the following manufacturers: Allied Telesis, Allnet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon, Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik, ENTERASYS, RIVERSTONE, Unifi, Ubiquiti, ZyXEL, ZTE
- High quality and excellent reliability
- 1.25 Gbps Maximum Data Rate
- Compliant to IEEE 802.3z Gigabit Standard
- Class 1 laser product compliant with EN 60825-1
- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant

- Hot pluggable
- Connector: 1x LC Duplex
- 1000Base-LX - For Long Haul
- Wavelength: 1310nm
- Transmission power: minimum -8 dBm, maximum -3 dBm
- Sensitivity receiving power: minimum -24 dBm
- For a Distance of up to 20km
- Suitable for OM3/OM4 Singlemode Fiber Cables
- Safe fast-locking mechanism
- 3.3V power supply
- Operating temperature: -40 °C - +85 °C
- Mode: Singlemode
- Connector: LC
- Distance (km): 20
- Wavelength: 1310 nm
- DDM Support: no
- Broadcasting Mode: Unidirectional
- Manufacturer compatibility: Universal (MSA), Cisco
- Ethernet speed: Gigabit

Package contents

- SFP module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	240	8.50	50.00	29.00	54.50	79,025.00
Packaging Unit Inside	30	1.06	7.00	20.00	30.00	4,200.00
Packaging Unit Single	1	0.04	3.00	12.00	9.00	324.00
Net single without Packaging	1	0.00	0.00	0.00	0.00	0.00

More images:

SFP Modules							
Product Number	Data Rate	Speed	Distance	Connector	Wavelength	Operating Temperature	Industrial Version
250-01001	40 Gbps	100 Gbps	10 km	LC	1310 nm	-40 °C to 75 °C	✓
250-01002	40 Gbps	100 Gbps	10 km	LC	1550 nm	-40 °C to 75 °C	✓
250-01003	40 Gbps	100 Gbps	10 km	LC	1310 nm	-40 °C to 75 °C	✓
250-01004	40 Gbps	100 Gbps	10 km	LC	1550 nm	-40 °C to 75 °C	✓
250-01005	40 Gbps	100 Gbps	10 km	LC	1310 nm	-40 °C to 75 °C	✓
250-01006	40 Gbps	100 Gbps	10 km	LC	1550 nm	-40 °C to 75 °C	✓
250-01007	40 Gbps	100 Gbps	10 km	LC	1310 nm	-40 °C to 75 °C	✓
250-01008	40 Gbps	100 Gbps	10 km	LC	1550 nm	-40 °C to 75 °C	✓
250-01009	40 Gbps	100 Gbps	10 km	LC	1310 nm	-40 °C to 75 °C	✓
250-01010	40 Gbps	100 Gbps	10 km	LC	1550 nm	-40 °C to 75 °C	✓
250-01011	40 Gbps	100 Gbps	10 km	LC	1310 nm	-40 °C to 75 °C	✓
250-01012	40 Gbps	100 Gbps	10 km	LC	1550 nm	-40 °C to 75 °C	✓
250-01013	40 Gbps	100 Gbps	10 km	LC	1310 nm	-40 °C to 75 °C	✓
250-01014	40 Gbps	100 Gbps	10 km	LC	1550 nm	-40 °C to 75 °C	✓
250-01015	40 Gbps	100 Gbps	10 km	LC	1310 nm	-40 °C to 75 °C	✓
250-01016	40 Gbps	100 Gbps	10 km	LC	1550 nm	-40 °C to 75 °C	✓
250-01017	40 Gbps	100 Gbps	10 km	LC	1310 nm	-40 °C to 75 °C	✓
250-01018	40 Gbps	100 Gbps	10 km	LC	1550 nm	-40 °C to 75 °C	✓
250-01019	40 Gbps	100 Gbps	10 km	LC	1310 nm	-40 °C to 75 °C	✓
250-01020	40 Gbps	100 Gbps	10 km	LC	1550 nm	-40 °C to 75 °C	✓
250-01021	40 Gbps	100 Gbps	10 km	LC	1310 nm	-40 °C to 75 °C	✓
250-01022	40 Gbps	100 Gbps	10 km	LC	1550 nm	-40 °C to 75 °C	✓
250-01023	40 Gbps	100 Gbps	10 km	LC	1310 nm	-40 °C to 75 °C	✓
250-01024	40 Gbps	100 Gbps	10 km	LC	1550 nm	-40 °C to 75 °C	✓
250-01025	40 Gbps	100 Gbps	10 km	LC	1310 nm	-40 °C to 75 °C	✓
250-01026	40 Gbps	100 Gbps	10 km	LC	1550 nm	-40 °C to 75 °C	✓
250-01027	40 Gbps	100 Gbps	10 km	LC	1310 nm	-40 °C to 75 °C	✓
250-01028	40 Gbps	100 Gbps	10 km	LC	1550 nm	-40 °C to 75 °C	✓
250-01029	40 Gbps	100 Gbps	10 km	LC	1310 nm	-40 °C to 75 °C	✓
250-01030	40 Gbps	100 Gbps	10 km	LC	1550 nm	-40 °C to 75 °C	✓
250-01031	40 Gbps	100 Gbps	10 km	LC	1310 nm	-40 °C to 75 °C	✓
250-01032	40 Gbps	100 Gbps	10 km	LC	1550 nm	-40 °C to 75 °C	✓
250-01033	40 Gbps	100 Gbps	10 km	LC	1310 nm	-40 °C to 75 °C	✓
250-01034	40 Gbps	100 Gbps	10 km	LC	1550 nm	-40 °C to 75 °C	✓
250-01035	40 Gbps	100 Gbps	10 km	LC	1310 nm	-40 °C to 75 °C	✓
250-01036	40 Gbps	100 Gbps	10 km	LC	1550 nm	-40 °C to 75 °C	✓
250-01037	40 Gbps	100 Gbps	10 km	LC	1310 nm	-40 °C to 75 °C	✓
250-01038	40 Gbps	100 Gbps	10 km	LC	1550 nm	-40 °C to 75 °C	✓
250-01039	40 Gbps	100 Gbps	10 km	LC	1310 nm	-40 °C to 75 °C	✓
250-01040	40 Gbps	100 Gbps	10 km	LC	1550 nm	-40 °C to 75 °C	✓

