

DIGITUS mini GBIC (SFP) Module, 10Gbps, 0.3km, with DDM Feature

DN-81200

EAN 4016032324133



10G SFP+ Module, Multimode, DDM LC Duplex Connector, 850nm, up to 300m

The DIGITUS® mini GBIC (SFP) transceiver modules offer highest quality and reliability. Whether from switch to switch, converter to switch, converter to converter or any else application: The wide product range of DIGITUS® modules makes possible a flexible usage of the fiber technology. The conformity to the MSA (Multi Source Agreement) standard ensures a compatibility to third party manufacturers.

The plug and play fiber connection

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Compatible with the following manufacturers: Allied Telesis, Allnet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon, Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik, ENTERASYS, RIVERSTONE, Unifi, Ubiquiti, ZyXEL, ZTE
- Supports DDM (Digital Diagnostic Monitoring)
- High quality and excellent reliability
- 10 Gbps Maximum Data Rate
- Compliant to IEEE802.3ae 10 Gigabit Standard
- Class 1 laser product compliant with EN 60825-1

- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant
- Hot pluggable
- Connector: 1x LC Duplex
- Wavelength: 850nm
- Transmission Power: Minimum -5 dBm, Maximum -1 dBm
- Empfangssensitivität: Minimum -11,5 dBm
- For a distance of up to 0.3km
- Safe fast-locking mechanism
- 3.3V power supply
- Operating temperature: 0 °C ~ 70 °C
- Mode: Multimode
- Connector: LC
- Distance (km): 0.3
- Wavelength: 850 nm
- DDM Support: yes
- Broadcasting Mode: Unidirectional
- Manufacturer compatibility: Cisco
- Ethernet speed: 10 Gigabit

Package contents

- SFP module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	0.80	41.00	26.00	16.00	17,056.00
Packaging Unit Inside	1	0.04	3.00	11.50	9.00	310.50
Packaging Unit Single	1	0.04	3.00	11.50	9.00	310.50
Net single without Packaging	1	0.03	5.50	1.20	0.80	0.00

More images:

Product Number	SKU Code	Speed	Distance	Connectors	Wavelength	Operating Temperature	Industrial Access
294-001	294-001-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-002	294-002-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-004	294-004-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-005	294-005-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-006	294-006-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-007	294-007-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-008	294-008-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-009	294-009-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-010	294-010-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-011	294-011-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-012	294-012-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-013	294-013-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-014	294-014-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-015	294-015-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-016	294-016-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-017	294-017-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-018	294-018-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-019	294-019-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-020	294-020-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-021	294-021-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-022	294-022-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-023	294-023-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-024	294-024-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-025	294-025-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-026	294-026-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-027	294-027-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-028	294-028-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-029	294-029-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-030	294-030-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-031	294-031-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-032	294-032-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-033	294-033-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-034	294-034-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-035	294-035-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-036	294-036-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-037	294-037-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-038	294-038-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-039	294-039-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-040	294-040-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-041	294-041-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-042	294-042-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-043	294-043-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-044	294-044-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-045	294-045-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-046	294-046-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-047	294-047-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-048	294-048-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-049	294-049-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-050	294-050-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-051	294-051-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-052	294-052-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-053	294-053-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-054	294-054-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-055	294-055-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-056	294-056-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-057	294-057-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-058	294-058-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-059	294-059-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-060	294-060-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-061	294-061-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-062	294-062-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-063	294-063-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-064	294-064-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-065	294-065-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-066	294-066-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-067	294-067-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-068	294-068-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-069	294-069-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-070	294-070-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-071	294-071-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-072	294-072-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-073	294-073-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-074	294-074-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-075	294-075-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-076	294-076-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-077	294-077-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-078	294-078-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-079	294-079-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-080	294-080-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-081	294-081-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-082	294-082-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-083	294-083-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-084	294-084-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-085	294-085-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-086	294-086-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-087	294-087-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-088	294-088-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-089	294-089-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-090	294-090-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-091	294-091-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-092	294-092-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-093	294-093-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-094	294-094-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-095	294-095-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-096	294-096-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-097	294-097-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-098	294-098-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓
294-099	294-099-010	100 km/s	2 km	12.5-Micron Fibers	1550nm	-40 to 70 °C	✓
294-100	294-100-010	100 km/s	2 km	12.5-Micron Fibers	1310nm	-40 to 70 °C	✓

