

DIGITUS mini GBIC (SFP) Module, 10Gbps, 10.0km, with DDM Feature

DN-81201**EAN 4016032324140****10G SFP+ Module, Singlemode, DDM LC Duplex Connector, 1310nm, up to 10km**

The DIGITUS® mini GBIC (SFP) transceiver modules offer highest quality and reliability. Whether from switch to switch, converter to switch, converter to converter or any else application: The wide product range of DIGITUS® modules makes possible a flexible usage of the fiber technology. The conformity to the MSA (Multi Source Agreement) standard ensures a compatibility to third party manufacturers.

The plug and play fiber connection

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Compatible with the following manufacturers: Allied Telesis, Allnet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon, Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik, ENTERASYS, RIVERSTONE, Unifi, Ubiquiti, ZyXEL, ZTE
- Supports DDM (Digital Diagnostic Monitoring)
- High quality and excellent reliability
- 10 Gbps Maximum Data Rate
- Compliant to IEEE802.3ae 10 Gigabit Standard
- Class 1 laser product compliant with EN 60825-1


- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant
- Hot pluggable
- Connector: 1x LC Duplex
- Wavelength: 1310nm
- Transmission Power: Minimum -8 dBm, Maximum -0,5 dBm
- Sensitivity Receiving Power: Minimum -12.5 dBm
- For a distance of up to 10,0km
- Safe fast-locking mechanism
- Operating temperature: 0 °C ~ 70 °C
- Mode: Singlemode
- Connector: LC
- Distance (km): 10
- Wavelength: 1310 nm
- DDM Support: yes
- Broadcasting Mode: Unidirectional
- Manufacturer compatibility: Universal (MSA)
- Ethernet speed: 10 Gigabit

Package contents

- SFP module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	2.00	41.00	26.00	16.00	17,056.00
Packaging Unit Inside	1	0.10	3.00	11.50	9.00	310.50
Packaging Unit Single	1	0.10	3.00	11.50	9.00	310.50
Net single without Packaging	1	0.03	5.50	1.20	0.80	0.00

More images:



SFP Modules						
Product Number	Serial Code	Speed	Distance	Connector	Wavelength	Operating Temperature
Fast Ethernet						
DE-40100	40100000000000	10 Gbps	10 km	LC Duplex OM3	1310nm	-40 to +70 °C
DE-40101	40100000000000	10 Gbps	25 km	LC Duplex OM3	1310nm	-40 to +70 °C
DE-40102	40100000000000	10 Gbps	25 km	LC Duplex OM3	1310nm	-40 to +70 °C
SFP						
DE-40103	40100000000000	10 Gbps	10 km	LC Duplex OM3	1310nm	-40 to +70 °C
DE-40104	40100000000000	10 Gbps	25 km	LC Duplex OM3	1310nm	-40 to +70 °C
DE-40105	40100000000000	10 Gbps	25 km	LC Duplex OM3	1310nm	-40 to +70 °C
DE-40106	40100000000000	10 Gbps	25 km	LC Duplex OM3	1310nm	-40 to +70 °C
DE-40107	40100000000000	10 Gbps	25 km	LC Duplex OM3	1310nm	-40 to +70 °C
SFP						
DE-40108	40100000000000	10 Gbps	10 km	LC Duplex OM3	1310nm	-40 to +70 °C
DE-40109	40100000000000	10 Gbps	10 km	LC Duplex OM3	1310nm	-40 to +70 °C
Fast Ethernet						
DE-40110	40100000000000	10 Gbps	10 km	LC Duplex OM3	1310nm	-40 to +70 °C
DE-40111	40100000000000	10 Gbps	25 km	LC Duplex OM3	1310nm	-40 to +70 °C
DE-40112	40100000000000	10 Gbps	25 km	LC Duplex OM3	1310nm	-40 to +70 °C
DE-40113	40100000000000	10 Gbps	25 km	LC Duplex OM3	1310nm	-40 to +70 °C
DE-40114	40100000000000	10 Gbps	25 km	LC Duplex OM3	1310nm	-40 to +70 °C
DE-40115	40100000000000	10 Gbps	25 km	LC Duplex OM3	1310nm	-40 to +70 °C
DE-40116	40100000000000	10 Gbps	25 km	LC Duplex OM3	1310nm	-40 to +70 °C
DE-40117	40100000000000	10 Gbps	25 km	LC Duplex OM3	1310nm	-40 to +70 °C
DE-40118	40100000000000	10 Gbps	25 km	LC Duplex OM3	1310nm	-40 to +70 °C
DE-40119	40100000000000	10 Gbps	25 km	LC Duplex OM3	1310nm	-40 to +70 °C