



# Planar PS5561T

## Interactive Large Format Display

The Planar® PS Series PS5561T is a 55" commercial-grade, multi-touch LCD display offering up to 6 touch points and is compatible with Windows, MacOS X, and Linux. The Planar PS Series PS5561T is the ideal combination of value, performance, and 24x7 reliability for interactive applications



SPECIFICATION	DETAIL
Product Name	PS5561T
Planar Part Number	997-7656-01
Viewable Size	55" diagonal
Aspect Ratio	16:9
Display Resolution	FHD 1080p (1920 x 1080)
Brightness (Typical)	500 cd/m <sup>2</sup>
Contrast Ratio (typ)	4000:1
Response Time (typ)	6.5 ms
Viewing Angle (typ)	178°
External Connections	DisplayPort, HDMI, VGA, DVI
Power Requirements	100 - 240V; 50/60Hz
Power Consumption (max)	165W
Service and Support/Warranty	3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only)
Product Approvals	FCC Class A, UL, CE
VESA Compatible/Location	400 mm x 200 mm; 4 holes
Audio Input	PC Audio in (Jack)
Audio Output	R/L Line out (Jack)
Bezel Width	0.8" (21mm)
Cabinet Dimensions (W x H x D)	49.5" x 28.7" x 2.8" (1257mm x 728mm x 71mm)
Display Control	RS232in, IR, Keypad, LAN

<b>Display Weight</b>	91 lbs (41 kg)
<b>Shipping weight</b>	113 lbs (51 kg)
<b>Display Type</b>	LCD Active Matrix Flat Panel Display (TFT)
<b>Refresh Rate</b>	60 Hz
<b>Operating Temperature</b>	5-35°C (41 -95°F)
<b>Palette</b>	1.073B colors (10 bit)
<b>Pixel Pitch</b>	0.1323mm
<b>Orientation</b>	Landscape/Portrait
<b>Speakers</b>	10W x 2 built-in
<b>Fanless</b>	Yes
<b>Touchscreen Type</b>	IR 6 point touch
<b>OS Compatibility</b>	Windows 10, 8, 7, Vista, XP, Mac OSX and Linux
<b>Features</b>	On/off scheduling, TAA compliant
<b>In the Box</b>	PS5561T display, power cord, VGA cable, IR extender cable, remote control, and USB cable
<b>UPC</b>	8 10689 00138 6

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 6/12/2017*

*© Copyright 2017 Planar Systems, Inc. All rights reserved*