

Data sheet

HP USB-C™ to HDMI Adapter



Share your work

Project your notebook or tablet's high-definition video and audio content to an external display, TV, or projector with the HP USB-C™ to HDMI Adapter.

One-cable setup

Connect the adapter to your tablet or notebook's USB-C™ port and broadcast to a monitor, projector or TV through the HDMI port.

Ready to go

Pack the small adapter with you in your device's carrying case for quick connections wherever you work.

World-class support

Rest easy with a one-year limited warranty.

Specifications

HP USB-C™ to HDMI Adapter

| | | |
|------------------------------|--|---|
| Model number | N9K77AA | |
| Host Interface | USB Type CTM | |
| Device interface | HDMI 1.4a compliant | |
| Connectors | Video output: HDMI female Connector Host input: USB Type CTM male Connector | |
| Supported Resolutions | 4K x 2K @ 30Hz | |
| Operating Temperature | 0°C ~ 40°C | |
| Storage Temperature | 0°C ~ 85°C | |
| System Requirements | Software | Microsoft Windows 7 with Service Pack 1 (32-bit or 64-bit), Windows 8, Windows 10 |
| Mechanical | Dimensions (H x W x L) | Unpackaged: 0.43 x 0.98 x 5.90 in (11 x 25 x 150 mm) |
| Weight | Unpackaged: 0.89 oz (25.4 g) | |
| Environmental | ROHS, REACH, WEEE | |
| Box Contents | HP USB Type CTM to HDMI Adapter, warranty and documentation | |
| Compatibility | HP Pro Tablet 608 G1 | |

Sign up for updates
hp.com/go/getupdated



Share with colleagues



Rate this document

© Copyright 2015 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum.

4AA6-0103ENW, March 2016

