

Part no.:

30311

1m C14 to C7 Mains Cable, lead free

IEC C14 Connector to IEC C7 Connector

| DESCRIPTION

- IEC C14 to IEC C7 Mains Cable for use in professional areas and private sectors
- Provides max. 2.5A/250V to a device
- Robust PVC/PBT housing and PVC cable jacket, lead-free connectors (<0.1% lead in brass)
- High temperature resistance allows the cable to be used in non air-conditioned areas
- 10 year warranty

Lindy Power Cables are high quality, reliable power delivery connections for use in a wide variety of professional and home environments.

The IEC C14 connector fits to devices with C13 ports and the IEC C7 connector fits to devices with IEC C8 connectors. The earth pin of the IEC C14 connector is not being used.

The brass used in the connectors has a lead content of far below 0.1% and is therefore SVHC-free, as are all other materials used in these cables.

Please note that this cable is for use in dry areas only.

IEC C14 to IEC C7 Mains Cables are available in the following lengths: 1m and 2m.

Connectors

- Connector A: IEC C14
- Connector B: IEC C7
- Housing Material:
 - A: PVC & PBT
 - B: PVC
- Pin Construction:
 - A: Brass
 - B: Phosphor Bronze
- Pin Plating: Nickel
- Dimensions (approx.) WxDxH:
 - A: 28x64x21mm (1.1x2.52x0.83in)
 - B: 15.8x57x8mm (0.62x2.24x0.31in)

Cable Construction

- Length: 1m (3.28ft)
- Colour: Black

- Conductor Material: Copper
- Cable Material: H05-VVF 2G 0.75mm²
- Number of Wires: 2
- Wire Gauge: 0.75mm²
- Jacket Diameter: 6.2mm (0.24in)
- Jacket Material: PVC

Specifications

- Rated Voltage and Current: 2.5A/250V
- Operating Temperature: -10°C - 60°C (14°F - 140°F)
- Storage Temperature: -20°C - 70°C (-4°F - 158°F)

Miscellaneous

- Packaging Type: Polybag
- Warranty (Years): 10
- Product Compliance: CE, RoHS, REACH, California Proposition 65

Purchasing Information

- No.: 30311
- EAN: 4002888303118

This product is also available in other lengths

- 30311 - 1m (3.28ft)
- 30312 - 2m (6.56ft)