

# Product Information

## LED Base Classic A60



### Benefits

- LED-Lamp with a frosted bulb in the well know GLS shape; available in many colour temperatures
- GLS outer dimensions – GLS inspired design!
- For all household luminaires
- Low energy consumption and maintenance costs
- Same size as dimmable version
- True 60W incandescent replacement

### Product Overview

Product	Wattage	CCT	lm	Base
LED BASE CLASSIC A 60	9	2700	806	E27

### Key Features

- 9W LED lamp as high-quality replacement for a 60W incandescent lamp
- Frosted version with unique OSRAM patented optics
- Designed in Germany
- Same dimensions as incandescent lamp
- UV and NIR radiation free
- Mercury free

Product	Wattage	CCT	lm	Base	Diameter	Length	Weight	Beam Angle	EAN10	EAN40 (ship.unit)	Ship. unit
LED BASE CLASSIC A 60	9	2700	806	E27	60	110	56	200	4052899955493	4052899955523	10

<sup>1</sup>With many common dimmers, see also [www.osram.com/dim](http://www.osram.com/dim)

<sup>2</sup> Typical values. All the technical parameters apply to the entire lamp. In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual products may vary from the typical values.

<sup>3</sup> The average lifetime of LED lamps is defined as the number of hours when the light output of 50% of a large group of identical lamps goes below 70% of its initial luminous flux (L70B50, IEC60969). The lifetime is estimated at room temperature (25°C), free air burning, base up burning position and at rated voltage.

# Product Information

## LED Base Classic A60

### Common Characteristics<sup>3</sup>

Average lifetime <sup>4</sup>	Switching cycles (30s on, 30s off)	Casing material	Starting time	Warm up time for 60% light	Power factor
10000	100000	Plastic	<2	<0,5	0,55
Nominal current	Max. inrush current	Tc temperature	CRI	Mercury max.	Luminous intensity
68 mA	-	98	≥ 80	0mg	n.a.



T<sub>c</sub>

Good heat exchange supports ideal performance

### Disposal information

- Lamps with WEEE sign can be returned at specific collection points.
- LED lamps have to be disposed as special waste.



<sup>3</sup> Typical values. All the technical parameters apply to the entire lamp. In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual products may vary from the typical values.

<sup>4</sup> The average lifetime of LED lamps is defined as the number of hours when the light output of 50% of a large group of identical lamps goes below 70% of its initial luminous flux (L70B50, IEC60969). The lifetime is estimated at room temperature (25°C), free air burning, base up burning position and at rated voltage.

<sup>5</sup> The T<sub>c</sub> is defined as the highest permissible temperature which may occur on the outer surface of the LED lamp (in the indicated position) under normal operating conditions and at the rated voltage/current/power or the maximum of the rated voltage/current/power range (DIN EN 62031: 2009-01)



# Product Information

## LED Base Classic A60

### Application information

- Suitable for indoor application.
- For outdoor applications and operation in damp locations special approved fixture are required.
- Input voltage: 220-240 V
- Storage temperature & humidity conditions (-20°C up to +40°C, at max. 95% relative humidity)
- Operating temperature & humidity conditions (-20°C up to +40°C, at max. 95% relative humidity)

### Lamp conformity

- 2004/108/EC Electromagnetic compatibility (EMC)
- 244/2009 Ecodesign requirements for non-directional household lamps
- IEC/ PAS 62612 Self ballasted LED-lamps for general lighting services – Performance requirements
- 2009/125/EC Ecodesign requirements for energy related products
- 2011/65/EC Restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)
- 1907/2006 Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH Regulation)
- 2002/96/EC Waste Electrical and Electronic Equipment Directive (WEEE)
- EN 62471 Photobiological safety of lamps and lamp systems
- EN 55015 Limits and methods of measurement of radio disturbance
- EN 61000-3-2 Electromagnetic compatibility – Limits for harmonic current emission
- EN 61000-3-3 Electromagnetic compatibility – Limitation of voltage changes, voltage fluctuations, flicker in public low voltage supply systems
- EN61547 Electromagnetic compatibility immunity requirements
- 1194/2012 Eco design requirement for directional lamps, light emitting diode lamps and related equipment (DIM II)
- IEC 62560 self-ballasted LED-lamps for general lighting services by voltage >50V – Safety specifications
- 874/2012/EU Energy labeling of electrical lamps and luminaires