


MPN: MC-SATA3-T4

PCIe SATA III Expansion Card ASM1061

This board is a single-chip, PCI Express to two SATA Gen III 6Gb/s channels host controller that brings server-class features to the desktop. This board enables the use of the industry's newest and fastest hard drives at 6Gb/s while providing backward compatibility to legacy SATA 1.5Gb/s or 3Gb/s drives. It uses the same cable and connectors as previous SATA generations to ease integration. Besides, PCI Express 2.0 double the bandwidth of the existing PCI Express bus for faster data throughput. It will enhance system performance for every type of computer user. Each PCI-Express 2.0 lane provides up to 500MB/s of throughput. It also backward compatible with previous generation of PCI Express 1.0 technology.



- Compliant with PCI-Express Specification v2.0 and backward compatible with PCI-Express 1.x
- Compliant with Serial ATA Specification 3.0
- Supports communication speeds of 6.0Gbps, 3.0Gbps and 1.5Gbps
- Hot plug and Hot Swap
- Support Native Command Queue (NCQ)
- Support Port Multiplier
- Compatible with SATA 6G, 3G and 1.5G Hard Drives
- Supports Windows® XP/Vista/7 (32/64 bit)
- Low profile

Specifications

| | | |
|-------------------------------|--|---|
| Design | Internal | Yes |
| Features | Bandwidth | 6 Gbit/s |
| | Chipset | ASMedia ASM1061 |
| Operational conditions | Operating temperature (T-T) | 5 - 35 °C |
| Packaging data | Quantity | 1 |
| Ports & interfaces | eSATA ports quantity | 2 |
| | Host interface | PCI Express |
| | Internal SATA ports quantity | 2 |
| | Output interface | SATA, eSATA |
| Power | Output current | 0.9 A |
| | Output voltage | 5 V |
| System requirements | Windows operating systems supported | Yes |
| Vendor information | Brand Name | MicroConnect |
| | Homepage | https://microconnect.me/ |
| | Warranty | 3 Year(s) |

Other images

