



LS2208 Technical Accessory Guide











NOTE: This document is only for general reference. Solution Builder and related PMBs should be used for product availability, pricing, and final solution selection.

* Zebra does not endorse or specifically recommend any **third-party products, accessories, or hardware**. ZEBRA DISCLAIMS ANY AND ALL LIABILITY, INCLUDING ANY EXPRESS OR IMPLIED WARRANTIES, WHETHER ORAL OR WRITTEN, FOR SUCH THIRD PARTY PRODUCTS, ACCESSORIES, OR HARDWARE. THE CUSTOMER ACKNOWLEDGES THAT NO REPRESENTATION HAS BEEN MADE BY ZEBRA AS TO THE FITNESS OF THE THIRD-PARTY PRODUCTS, ACCESSORIES, OR HARDWARE FOR THE CUSTOMER'S INTENDED PURPOSE.












Communication Cables














Zebra associates and partners can also see Zebra's Universal Cable Guide at:









https://partnerportal.zebra.com/PartnerPortal/product_services/downloads_z/barcode_scanners/Universal-Cable-Guide-Bar-Code-Scanners.xlsx









Standard USB Cables					
Part Number	Picture	Description	Notes	Required Items	
CBA-U01-S07ZAR		USB Cable: Series A Connector, 7ft. Straight			
CBA-U18-S07PAR		USB Cable: Series A Connector, 7ft. Powered	•Discontinued 10/31/2012, PMB 2152 •Cable can be used when host device doesn't provide enough power on USB port or to provide power to scanner while host is turned off.	Requires 5V external power supply like PWRS-14000-058R	
CBA-U30-S15ZBR (cable ties shield to ground which allows it to be used with scanners requiring Non-Shielded or Shielded cables)		USB Cable: Series A Connector, 15ft. Straight			
CBA-U10-S15ZAR					
CBA-U12-C09ZAR		USB Cable: (Series A Connector, 9ft. Coiled)			
CBA-U09-C15ZAR		USB Cable: Series A Connector, 15ft. Coiled			
CBA-U06-S09EAR		USB Cable: EAS, Series A Connector, 9ft. Straight	Integrates with Checkpoint EAS security tag system		
IBM POS USB Cables					
Non-Shielded USB Cable Part Number	Shielded USB Cable Part Number	Picture	Description	Notes	Required Items
Used with units Manufactured prior to Jan 2015 (will have black logo on device)	Used with units Manufactured after Jan 2015 - LS2208+ (will have silver logo on device)				
					
CBA-U23-S07ZBR (cable ties shield to ground which allows it to be used with scanners requiring Non-Shielded or Shielded cables)	CBA-U23-S07ZBR (has heavier gauge wire vs. CBA-U23-S07ZAR, can support 5V and 12V power, scanner dependent)		USB Cable: Power Plus Connector, 7ft. Straight		
CBA-U03-S07ZAR	CBA-U23-S07ZAR •Discontinued 2/2019, now use CBA-U23-S07ZBR - see PMB 10044				

CBA-U35-S15ZBR (cable ties shield to ground which allows it to be used with scanners requiring Non-Shielded or Shielded cables)	CBA-U35-S15ZBR (has heavier gauge wire vs. CBA-U35-S15ZAR, can support 5V and 12V power, scanner dependent)		USB Cable: Power Plus Connector, 15ft. Straight		
CBA-U15-S15ZAR	CBA-U35-S15ZAR *Discontinued 2/2019, now use CBA-U35-S15ZBR - see PMB 10044				
CBA-U14-C09ZAR *Discontinued 10/31/2012, PMB 2152	CBA-U34-C09ZAR		USB Cable: Power Plus Connector, 9ft. Coiled		
CBA-U08-C15ZAR	CBA-U28-C15ZBR (has heavier gauge wire vs. CBA-U28-C15ZAR, can support 5V and 12V power, scanner dependent)		USB Cable: Power Plus Connector, 15ft. Coiled		
	CBA-U28-C15ZAR				
CBA-U07-S09EAR	CBA-U27-S09EAR		*USB Cable: Power Plus Connector, 9ft. Straight with EAS	Integrates with Checkpoint EAS security tag system	
RS232 Cables					
Part Number	Picture	Description	Notes	Required Items	
CBA-R01-S07PBR		RS232 Cable:STD-DB9 Female, TxD on 2, 7ft. Straight	*Includes improved TTL current limit protection circuitry vs. CBA-R01-S07PAR	Requires external power supply	
CBA-R01-S07PAR		RS232 Cable:STD-DB9 Female, TxD on 2, 7ft. Straight	*Discontinued 2/2019, now use CBA-R01-S07PBR - see PMB 10044	Requires external power supply	
CBA-R02-C09PAR		RS232 Cable:STD-DB9 Female, TxD on 2, 9ft. Coiled		Requires external power supply	
CBA-R03-C12PAR		RS232 Cable:STD-DB9 Female, TxD on 2, 12ft. Coiled		Requires external power supply	
CBA-R06-C20PBR		RS232 Cable:STD-DB9 Female, TxD on 2, 20ft. Coiled	*Includes improved TTL current limit protection circuitry vs. CBA-R06-C20PAR	Requires external power supply	
CBA-R06-C20PAR		RS232 Cable:STD-DB9 Female, TxD on 2, 20ft. Coiled		Requires external power supply	










CBA-R04-S09FAR		RS232 Cable: DB9 Female, TxD on 2, 6ft Straight with EAS	<ul style="list-style-type: none"> Discontinued 8/2013 Integrates with Checkpoint EAS security tag system 	Requires external power supply
CBA-R05-C09FAR		RS232 Cable: DB9 Female, TxD on 2, 9ft Straight with EAS	<ul style="list-style-type: none"> Discontinued 11/2011 Integrates with Checkpoint EAS security tag system 	Requires external power supply
CBA-R49-C09ZAR		RS232 Cable: True Cvtr, DB9 Female, Pwr Pin 9, TxD on 2, 9ft. Coiled - Freezer Rated	<ul style="list-style-type: none"> Cable and strain relief are rated for freezer environment use (-30°C). Cable provides ±12V signaling (RS232C) needed by some older PLC's which may not support TTL signalling 	
CBA-R46-C09ZBR		RS232 Cable: True Cvtr, DB9 Female, Pwr Pin 9, TxD on 2, 9ft. Coiled	<ul style="list-style-type: none"> Cable provides ±12V signaling (RS232C) needed by some older PLC's which may not support TTL signalling 	
CBA-R46-C09ZAR		RS232 Cable: True Cvtr, DB9 Female, Pwr Pin 9, TxD on 2, 9ft. Coiled	<ul style="list-style-type: none"> Discontinued 9/2014. Now use CBA-R46-C09ZBR which has improved cable strain relief design. Cable provides ±12V signaling (RS232C) needed by some older PLC's which may not support TTL signalling 	
CBA-R35-C09ZAR		RS232 Cable: True Cvtr, DB9 Female, Pwr Pin 9, TxD on 2, 9ft. Coiled	<ul style="list-style-type: none"> Discontinued 11/2008. Replaced by CBA-R46-C09ZAR which has improved ESD performance. Cable provides ±12V signaling (RS232C) needed by some older PLC's which may not support TTL signalling 	
CBA-R37-C09ZBR		RS232 Cable: STD-DB9 Female, PWR Pin 9, 9ft coiled	<ul style="list-style-type: none"> Includes improved TTL current limit protection vs. CBA-R37-C09ZAR. 	
CBA-R37-C09ZAR		RS232 Cable: STD-DB9 Female, PWR Pin 9, 9ft coiled	<ul style="list-style-type: none"> Includes improved strain relief design over CBA-R36-C09ZAR 	
CBA-R36-C09ZAR		RS232 Cable: STD-DB9 Female, PWR Pin 9, 9ft coiled)	<ul style="list-style-type: none"> Discontinued 3/2013, now use CBA-R37-C09ZAR 	
CBA-R73-C09ZAR		RS232 Cable: True Cvtr, DB9 Male, Pwr Pin 9, TxD on 2, 9ft. Coiled	<ul style="list-style-type: none"> Cable provides ±12V signaling (RS232C) needed by some older PLC's which may not support TTL signalling 	
CBA-R18-C09ZAR		RS232 Cable: STD-DB9 Female, PWR on PIN 1, 9ft Coiled	<ul style="list-style-type: none"> Discontinued 10/31/2012, PMB 2152 	
CBA-R32-S07PAR		RS232 Cable: True Cvtr, DB9 Female, TxD on 2, 7ft. Straight	<ul style="list-style-type: none"> Cable provides ±12V signaling (RS232C) needed by some older PLC's which may not support TTL signalling 	Requires external power supply









CBA-R33-C09PAR		RS232 Cable: True Cvtr, DB9 Female, Tx/D on 2, 9ft. Coiled	Discontinued 11/2011	Requires external power supply
CBA-R34-C20PAR		CBL: RS232 (TRU TTL DB9F) 20FT, CL	Discontinued 9/2011	Requires external power supply
CBA-R40-C09SAR		RS232 Cable: Split DB9F & power line 9ft coiled	Discontinued 10/31/2012, PMB 2152	Requires external power supply
CBA-R38-C09ZAR		RS232 Cable: DB25 Female, PWR PIN 12, 9ft coiled	Discontinued 10/31/2012, PMB 2152	
CBA-R39-C20ZAR		RS232 Cable: DB25 Female, PWR PIN 12, 20ft coiled	Discontinued 9/2011	
Siemens Nixdorf Beetle POS Terminal RS232 Cables				
Part Number	Picture	Description	Notes	Required Items
CBA-R08-S07ZBR		RS232 Cable: Nixdorf Beetle-5V Direct Power Cable 7ft. Straight	Includes improved TTL current limit protection circuitry vs. CBA-R08-S07ZAR	
CBA-R08-S07ZAR		RS232 Cable: Nixdorf Beetle-5V Direct Power Cable 7ft. Straight	Discontinued 2/2019, now use CBA-R08-S07ZBR - see PMB 10044	
CBA-R09-C09ZAR		RS232 Cable: Nixdorf Beetle-5V Direct Power Cable 9ft. Coiled		
CBA-R10-S07ZBR		RS232 Cable: Nixdorf Beetle-12V Direct Power, 7ft. Straight	Includes improved TTL current limit protection circuitry vs. CBA-R10-S07ZAR	
CBA-R10-S07ZAR		RS232 Cable: Nixdorf Beetle-12V Direct Power, 7ft. Straight	Discontinued 2/2019, now use CBA-R10-S07ZBR - see PMB 10044	
CBA-R41-S12ZAR		RS232 Cable: Nixdorf Beetle-12V Direct Power, 12ft. Straight		
CBA-R11-C09ZAR		RS232 Cable: Nixdorf Beetle-12V Direct Power, 9ft. Coiled	Discontinued 8/2013	
CBA-R12-C12ZAR		RS232 Cable: Nixdorf Beetle-12V Direct Power, 12ft. Coiled	Discontinued 5/2019 - see PMB 10111	







CBA-R14-C20ZAR		RS232 Cable: Nixdorf Beetle, 20ft. Coiled		
CBA-R43-C20ZAR		RS232 Cable: Nixdorf Beetle, DB25, 20ft. Coiled		
CBA-R13-S09EAR		RS232 Cable: Nixdorf Beetle-12V Direct Power, 7ft. Straight., with EAS	Integrates with Checkpoint EAS security tag system	
CBA-R15-C09EAR		RS232 Cable: Nixdorf Beetle-12V Direct Power, 9ft. Coiled, with EAS	<ul style="list-style-type: none"> Discontinued 5/2015 Integrates with Checkpoint EAS security tag system 	
Other POS Terminal RS232 Cables				
Part Number	Picture	Description	Notes	Required Items
CBA-R16-S07ZAR		RS232 Cable: IBM Sure One, DB15 TxD on 2, 7ft Straight	Discontinued 12/31/10	
CBA-R17-C09ZAR		RS232 Cable: IBM Sure One, DB15 TxD on 2, 9ft. Coiled	Discontinued 9/2011	
CBA-R23-S07ZBR		RS232 Cable: Fujitsu Team POS 500 ICL, 7ft straight	Includes improved TTL current limit protection circuitry vs. CBA-R23-S07ZAR	
CBA-R23-S07ZAR		RS232 Cable: Fujitsu Team POS 500 ICL, 7ft straight	Discontinued 2/2019, now use CBA-R23-S07ZBR - see PMB 10044	
CBA-R22-C09ZAR		RS232 Cable: Fujitsu Team POS 500 ICL, 9ft coiled		
CBA-R24-C20ZAR		RS232 Cable: Fujitsu Team POS 500 ICL, 20ft Coiled		
CBA-R27-S07ZAR		RS232 Cable: NCR7432 DYNAKEY, 7ft. Straight	Discontinued 2/2019 - see PMB 10043	
CBA-R26-C09ZAR		RS232 Cable: NCR 7452 DYNAKEY, 9ft. Coiled	Discontinued 12/31/10	
CBA-R29-C12ZAR		RS232 Cable: NCR 7452 DYNAKEY, 12ft Coiled	Discontinued 12/31/10	



CBA-R31-C09ZAR		CBL:RS232 (NCR7448) 9FT,CLD		
CBA-R47-C09ZAR		CBL:RS232 (NCR AUX PORT) 9FT, CLD		
CBA-R42-C09ZAR		CBL:RS232 (NCR AUX PORT) 9FT, CLD	Discontinued 12/31/10, now use CBA- R47-C09ZAR	
CBA-R19-C09PAR		RS232 Cable: Olivetti - ORS500, 9ft coiled	Discontinued 12/31/10	
CBA-R20-S07PAR		RS232 Cable: Olivetti - ORS500, 7ft straight	Discontinued 2/2009	
25-32465-26		RS232 Cable: PSC Magellan scanner Auxiliary Port, 6ft Coiled		
CBA-R28-C09ZAR		RS232 Cable: Verifone Ruby, 9ft, Coiled		
Keyboard Wedge Cables				
NOTE: Cables for pre-Jan 2015 and post-Jan 2015 devices are interchangeable, however, post-Jan 2015 devices will support auto-detect for switching into keyboard wedge mode without scanning configuration barcode when used with a post-Jan 2015 cable.				
Units Manufactured prior to Jan 2015 (will have black logo on device)	Units Manufactured after Jan 2015 - LS2208+ (will have silver logo on device)	Picture	Description	Notes
				
CBA-K01-S07PAR	CBA-K61-S07PAR		Keyboard Wedge Cable: PS/2, Power Port, 7ft. Straight	<ul style="list-style-type: none"> •Host can provide enough power on PS2 port for scanner, however, Zebra recommends using an external power supply to protect the host's PS2 port. •Recommend using CBA-K61-S07ZAR for post Jan-2015 scanners to support host auto-detect so configuration barcode is not needed to put device into Keyboard Wedge mode.
CBA-K05-S15PAR	N/A		Keyboard Wedge Cable: PS/2, Power Port, 15ft. Straight	<ul style="list-style-type: none"> •Discontinued 2/2019 - see PMB 10043 •Host can provide enough power on PS2 port for scanner, however, Zebra recommends using an external power supply to protect the host's PS2 port.

CBA-K02-C09PAR	CBA-K62-C09PAR		Keyboard Wedge Cable: PS/2, Power Port, 9ft. Coiled	<ul style="list-style-type: none"> Host can provide enough power on PS2 port for scanner, however, Zebra recommends using an external power supply to protect the host's PS2 port. Recommend using CBA-K62-C09ZAR for post Jan-2015 scanners to support host auto-detect so configuration barcode is not needed to put device into Keyboard Wedge mode. 	
CBA-K06-C12PAR	N/A		Keyboard Wedge Cable: PS/2, Power Port, 12ft. Coiled	<ul style="list-style-type: none"> Discontinued 2/2019 - see PMB 10043 Host can provide enough power on PS2 port for scanner, however, Zebra recommends using an external power supply to protect the host's PS2 port. 	
CBA-K08-C20PAR	N/A		Keyboard Wedge Cable: PS/2, Power Port, 20ft. Coiled	<ul style="list-style-type: none"> Host can provide enough power on PS2 port for scanner, however, Zebra recommends using an external power supply to protect the host's PS2 port. 	
CBA-K07-S09FAR	N/A		Keyboard Wedge Cable: PS/2 with EAS 9ft Power Port, Straight	<ul style="list-style-type: none"> Discontinued 9/2011 Integrates with Checkpoint EAS security tag system Host can provide enough power on PS2 port for scanner, however, Zebra recommends using an external power supply to protect the host's PS2 port. 	
KT-32903-01R		Adapter Connector for PS/2 to AT/XT		<ul style="list-style-type: none"> Discontinued 12/2015 - PMB 2724 	
IBM 468x/469x POS Cables					
NOTE: Cables for pre-Jan 2015 and post-Jan 2015 devices are NOT interchangeable.					
Units Manufactured prior to Jan 2015 (will have black logo on device)	Units Manufactured after Jan 2015 - LS2208+ (will have silver logo on device)	Picture	Description	Notes	Required Items
					
CBA-M04-S07ZAR	CBA-M64-S07ZAR		IBM 468x/9x, Port 5B Cable, 7ft. Straight	<ul style="list-style-type: none"> CBA-M64-S07ZAR supports host auto-detect so configuration barcode is not needed to put post Jan-2015 unit into IBM host mode. 	
CBA-M05-C09ZAR	N/A		IBM 468x/9x, Port 5B Cable, 9ft. Coiled	Discontinued 11/2011	
CBA-M13-C12ZAR	N/A		IBM 468x/9x-Port 5B, 12ft. Coiled	Discontinued 12/31/10	
CBA-M06-S09EAR	N/A		IBM 468x/9x Port 5B Cable with EAS, 9ft. Straight	<ul style="list-style-type: none"> Discontinued 12/31/10 Integrates with Checkpoint EAS security tag system 	

CBA-M01-S07ZAR	CBA-M61-S07ZAR		IBM 468x/9x, Port 9B Cable, 7ft. Straight	•CBA-M61-S07ZAR supports host auto-detect so configuration barcode is not needed to put post Jan-2015 unit into IBM host mode.	
CBA-M12-S07ZAR	N/A		LS4278 Only: IBM Port 9B 7ft. Straight	Discontinued 11/2011	
CBA-M02-C09ZAR	N/A		IBM 468x/9x, Port 9B Cable, 9ft. Coiled		
CBA-M10-C12ZAR	N/A		IBM 468x/9x-Port 9B, 12ft. Coiled	•Discontinued 5/2019 - see PMB 10111	
CBA-M11-C20ZAR	N/A		IBM 468x/9x-Port 9B, 20ft. Coiled	Discontinued 11/2011	
CBA-M03-S09EAR	N/A		IBM 468x/9x Cable, Port 9B with EAS, 9ft. Straight	•Discontinued 5/2019 - see PMB 10111 •Integrates with Checkpoint EAS security tag system	
CBA-M07-S07ZAR	N/A		IBM 468x/9x Port 17 Cable, 7ft. Straight	Discontinued 2/2009	
CBA-M08-C09ZAR	N/A		IBM 468x/9x Port 17 Cable, 9ft. Coiled	Discontinued 2/2009	
CBA-M09-S09EAR	N/A		IBM 468x/9x Port 17 Cable with EAS, 9ft. Straight	Discontinued 2/2009 Integrates with Checkpoint EAS security tag system	
Scanner Emulation Cables <i>NOTE: Not supported on models manufactured after Jan-2015</i>					
CBA-D02-C09ZAR		CBL: STD UNDECODED 9 FT COILED		Requires external power supply	
CBA-D01-S07ZAR		Scanner Emulation cable: Undecoded 7ft Straight	•Discontinued 10/31/2012, PMB 2152	Requires external power supply	
CBA-D03-C20ZAR		Scanner Emulation cable: Undecoded 20ft Coiled	Discontinued 11/2011	Requires external power supply	
Wand Cables <i>NOTE: Not supported on models manufactured after Jan-2015</i>					

CBA-W01-S07ZAR		Wand Cable: 7ft Straight	Discontinued 10/31/2012, PMB 2152	Requires external power supply
CBA-W02-C09ZAR		Wand Cable: 9ft coiled	Discontinued 8/2013	Requires external power supply
Vehicle Mount Computer Cables				
25-159548-02		VC70N0 to scanner (USB)	<ul style="list-style-type: none"> USB cable locks onto VC70 using two screws Provides enough power for DS3508-ER 12 ft long when extended Improved performance in freezer environments vs. 25-159548-01. The conductor insulation material was changed to a stiffer material so the copper does not flex at as sharp an angle, resulting in a longer bend life. 	
25-159548-01		VC70N0 to scanner (USB)	<ul style="list-style-type: none"> Discontinued 4/2016, now use 25-159548-02 - PMB 2712 USB cable locks onto VC70 using two screws Provides enough power for DS3508-ER 12 ft long when extended 	
25-164479-02		VC6090 to Scanner (USB)	<ul style="list-style-type: none"> To be discontinued 1/2020 - see PMB 10261 Locking and sealed USB cable Provides enough power for DS3508-ER coiled cable 9 ft. long when extended Improved performance in freezer environments vs. 25-164479-01. The conductor insulation material was changed to a stiffer material so the copper does not flex at as sharp an angle, resulting in a longer bend life. 	
25-164479-01		VC6090 to Scanner (USB)	<ul style="list-style-type: none"> Discontinued 4/2016, now use 25-164479-02 - PMB 2712 Locking and sealed USB cable Provides enough power for DS3508-ER coiled cable 9 ft. long when extended 	
25-71917-03R		VC5000 or FLC9000 to scanner (serial)	<ul style="list-style-type: none"> 9 ft long when extended Improved performance in freezer environments vs. 25-71917-02R. The conductor insulation material was changed to a stiffer material so the copper does not flex at as sharp an angle, resulting in a longer bend life. 	
25-71917-02R		VC5000 or FLC9000 to scanner (serial)	<ul style="list-style-type: none"> Discontinued 4/2016, now use 25-71917-03R - PMB 2712 9 ft long when extended 	






CBL-71918-12R		VC5000 or FLC9000 to scanner (USB)	<ul style="list-style-type: none"> •To be discontinued 1/2020 - see PMB 10261 •Improved performance in freezer environments vs. CBL-71918-11R. The conductor insulation material was changed to a stiffer material so the copper does not flex at as sharp an angle, resulting in a longer bend life. •This cable can't be used on full screen VC5000 units that use an external keyboard since the keyboard uses the same rugged USB connector. •9 ft long when extended 	
CBL-71918-11R		VC5000 or FLC9000 to scanner (USB)	<ul style="list-style-type: none"> •Discontinued 4/2016, now use CBL-71918-12R - PMB 2712 •NOTE: Recommend using 25-71918-01R in freezer environments instead of this cable. •Cable adds additional components vs. 25-71918-01R to keep inner wiring from being over torqued under certain installation conditions. •This cable can't be used on full screen units that use an external keyboard since the keyboard uses the same rugged USB connector. •9 ft long when extended 	
25-71918-01R		VC5000 or FLC9000 to scanner (USB)	<ul style="list-style-type: none"> •This cable can't be used on full screen units that use an external keyboard since the keyboard uses the same rugged USB connector. •9 ft long when extended •Recommend using CBL-71918-11R instead 	
CBA-T14-C09ZAR		Scanner Emulation Cable: Connects scanner to VRC6900		
CBA-T28-C09ZAR		CBL: UNDECODED, to be used with the VRC69XX Only, 9FT CL	<ul style="list-style-type: none"> •Discontinued 8/2013 •Includes improved strain relief design 	
CBA-T27-C09ZAR		CBL: UNDECODED, to be used with the VRC69XX Only, 9FT CL	<ul style="list-style-type: none"> •Discontinued 3/2013, now use CBA-T28-C09ZAR 	
CBA-T13-C09ZAR		RS232 Cable: Connects scanner to VRC7900/8900		
CBA-T12-C12ZAR		Telxon 860/870 IM 12ft. Coiled	Discontinued 12/31/10	
CBA-T17-C09ZAR		RS232 Scanner Emulation (LXE LEMO, Circular Locking Connector 9ft Coiled)	Discontinued 2/2009	
CBA-T18-C09ZAR		Wand Emulation (LXE LEMO, Circular Locking Connector 9ft Coiled)	Discontinued 11/2011	
CBA-T09-C09ZAR		RS232 - Teklogix 7035, 9ft Coiled	Discontinued 12/31/10	


CBA-T05-C09ZAR		Undecoded - Teklogix 7035, 8055-56, 9ft Coiled	Discontinued 12/31/10	
CBA-T06-C09ZAR		Undecoded - Teklogix - Circular connector 9ft Coiled	Discontinued 11/2011	
CBA-T07-C09ZAR		Undecoded - Teklogix - OEM - 28 Pin Connector 9ft Coiled	Discontinued 9/2011	
CBA-T10-C09ZAR		Undecoded - Teklogix- 28 Pin connector 9ft Coiled	Discontinued 11/2011	
Terminal Specific Cables				
P1031365-057		Scanner to QLn/ZQ6 Series Printer Cable	<ul style="list-style-type: none"> Allows scanner to be directly connected to serial port on QLn or ZQ6 series printers. Serial port on printer will power the scanner 41" long when extended 	
CBA-A51-S16ZAR		Auxiliary Scanner Cable to MP6000/MP7000, RS232 Serial	<ul style="list-style-type: none"> Allows handheld scanners to be used with MP6000/MP7000 for scanning heavy/awkward items. 5 meter length RS232 serial connection to scanner Connects to AUX2 port on MP6000/MP7000 Provides power to corded scanners NOTE: MP6000/MP7000 supports maximum of 2 auxiliary scanners. 	
CBA-T01-C09ZAR		RS232 Cable: MK1000/MK2000/MK2200 Aux Scanner Cable – LS 4208 / 3408	Discontinued 12/31/10	
CBA-T02-C09ZAR		RS232 (PDT8146 9ft Coiled)	Discontinued 12/31/10	
CBA-T19-C09ZAR		RS232 (RENAULT, CEV W/FERRITE 9ft Coiled)	Discontinued 2/2009	
CBA-T21-C20ZAR		RS232, 20ft coiled, pick to light	Discontinued 12/31/10	
CBA-T22-C20ZAR		RS232 (Sun DB25F, 12-5V, 20ft Coiled)	Discontinued 11/2011	










CBA-T23-C20ZAR		RS232 (Sun DB25F, 20ft Coiled)	Discontinued 12/31/10	
CBA-T24-C09ZAR		RS232 (EPSON DB9F PWR ON 1) 9ft Coiled	Discontinued 12/31/10	
Synapse Adapter Cables NOTE: Not supported on models manufactured after Jan-2015				
CBA-S01-S07ZAR		Synapse Adapter Cable: 7ft. Straight		May require external power supply depending on Synapse adapter chosen
CBA-S03-C09ZAR		Synapse Adapter Cable: 9ft. Coiled	Discontinued 10/31/2012, PMB 2152	May require external power supply depending on Synapse adapter chosen
CBA-S04-C16ZAR		Synapse Adapter Cable: 16ft. Coiled	Discontinued 4/2018 - PMB 3047.	May require external power supply depending on Synapse adapter chosen
CBA-S05-S09EAR		Synapse Adapter Cable with EAS 9ft. Straight	Integrates with Checkpoint EAS security tag system	
Misc				
Part Number	Picture	Description	Notes	Required Items
STND-GS00UNC-04		Universal Gooseneck Intellistand (Black color)	<ul style="list-style-type: none"> Expected to be released June 2017 Stand is compatible with LS2208, LI2208, LS4208, DS4208, DS4308, DS2208, DS8108 Stand has scanner trigger magnets in both nose and base. 	
20-61019-02R		Gooseneck Intellistand (Black color)	Compatible with all LS2208 versions	
20-61019-04R		Gooseneck Intellistand with Weighted Base (Black color)	Compatible with all LS2208 versions	

20-61019-01R		Gooseneck Intellistand (White color)	<ul style="list-style-type: none"> Compatible with all LS2208 versions 	
20-61022-04R		Gooseneck Intellistand (Black color)	<ul style="list-style-type: none"> Only compatible with units manufactured after Jan 2015 - LS2208+ (will have silver logo on device)  Also compatible with LI2208 units 	
20-70777-01R		Desk Holder		
11-66553-06R		Wall Mount Holder		

Power Supplies/Power Cords

Part Number	Picture	Description	Notes	Required Items
PWR-WUA5V4W0US		Power Supply (US)	<ul style="list-style-type: none"> Used when connecting communication cables labeled above as "Requires external power supply". For use in US, CA, MX, JP, TW. 5.2V, 1.1A, 5.7W Provides US DOE Level VI compliance for power efficiency. Replaces PWRS-14000-253R 	
PWRS-14000-253R		Power Supply (US)	<ul style="list-style-type: none"> Discontinued 2/2017, now use PWR-WUA5V4W0US - PMB 2903. Used when connecting communication cables labeled above as "Requires external power supply". 110V/60Hz - For use in US and CA-MX-JP-TW 5VDC, 850MA Energy Star Compliant 	
50-14000-253R		Power Supply (US)	<ul style="list-style-type: none"> Discontinued 11/2010, now use PWRS-14000-253R Used when connecting communication cables labeled above as "Requires external power supply". 110V/60Hz - For use in US and other countries 	
KT-14001-001R		Power Supply (US)	<ul style="list-style-type: none"> 110V/60Hz - For use in US and other countries Includes 50-14001-001R power supply, 25-100620-01R DC Line cord, and 23844-00-00R AC Line cord Discontinued 11/08 - now use 50-14000-253R 	
50-14000-008R		Power Supply (US)	<ul style="list-style-type: none"> 110V/60Hz - For use in US and other countries Discontinued 11/1/07 - now use KT-14001-001R 	

PWR-WUA5V4W0IN		Power Supply (India)	<ul style="list-style-type: none"> •Used when connecting communication cables labeled above as "Requires external power supply". •For use in India. •5.2V, 1.1A, 5.7W •Provides US DOE Level VI compliance for power efficiency. •Replaces PWRS-14000-254R 	
PWRS-14000-254R		Power Supply (India)	<ul style="list-style-type: none"> •Used when connecting communication cables labeled above as "Requires external power supply". •110V/60Hz - For use in India •5VDC,850MA •Energy Star Compliant •Discontinued 4/2018, now use PWR-WUA5V4W0IN - PMB 3047. 	
PWR-WUA5V4W0BR		Power Supply (Brazil)	<ul style="list-style-type: none"> •Used when connecting communication cables labeled above as "Requires external power supply". •For use in Brazil. •5.2V, 1.1A, 5.7W •Provides US DOE Level VI compliance for power efficiency. •Replaces PWRS-14000-255R 	
PWRS-14000-255R		Power Supply (Brazil)	<ul style="list-style-type: none"> •Used when connecting communication cables labeled above as "Requires external power supply". •110V/60Hz - For use in Brazil •5VDC,850MA •Energy Star Compliant •Discontinued 3/2017, now use PWR-WUA5V4W0BR - PMB 2903. 	
PWR-WUA5V4W0EU		Power Supply (EU and UK)	<ul style="list-style-type: none"> •Used when connecting communication cables labeled above as "Requires external power supply". •For use in EU and UK. •5.2V, 1.1A, 5.7W •Provides US DOE Level VI compliance for power efficiency. •Replaces PWRS-14000-256R 	
PWRS-14000-256R		Power Supply (EU and UK)	<ul style="list-style-type: none"> •Discontinued 2/2017, now use PWR-WUA5V4W0EU - PMB 2903. •Used when connecting communication cables labeled above as "Requires external power supply". •110V/60Hz - For use in EU and UK. •5VDC,850MA •Energy Star Compliant 	
PWR-WUA5V4W0CN		Power Supply (China)	<ul style="list-style-type: none"> •Used when connecting communication cables labeled above as "Requires external power supply". •For use in China. •5.2V, 1.1A, 5.7W •Provides US DOE Level VI compliance for power efficiency. •Replaces PWRS-14000-257R 	
PWRS-14000-257R		Power Supply (China)	<ul style="list-style-type: none"> •Discontinued 2/2017, now use PWR-WUA5V4W0CN - PMB 2903. •Used when connecting communication cables labeled above as "Requires external power supply". •110V/60Hz - For use in China •5VDC,850MA •Energy Star Compliant 	
PWR-WUA5V4W0AU		Power Supply (Australia)	<ul style="list-style-type: none"> •Used when connecting communication cables labeled above as "Requires external power supply". •For use in Australia. •5.2V, 1.1A, 5.7W •Provides US DOE Level VI compliance for power efficiency. •Replaces PWRS-14000-258R 	
PWRS-14000-258R		Power Supply (Australia)	<ul style="list-style-type: none"> •Used when connecting communication cables labeled above as "Requires external power supply". •110V/60Hz - For use in Australia. •5VDC,850MA •Energy Star Compliant •Discontinued 1/2017, now use PWR-WUA5V4W0AU. 	

PWRS-14000-259R		Power Supply (Argentina/UY)	<ul style="list-style-type: none"> ►Used when connecting communication cables labeled above as "Requires external power supply". ►110V/60Hz - For use in Argentina/UY. ►5VDC,850MA ►Energy Star Compliant ►Discontinued 4/2016. 	
50-14000-256R (UK/EU) 50-14000-257R (China) 50-14000-258R (Australia/New Zealand/Hong Kong) 50-14000-259R (Argentina)		Power Supply	<ul style="list-style-type: none"> ►Discontinued 11/2010, now use PWRS-14000-256R, -257R, -258R, -259R ►Used when connecting communication cables labeled above as "Requires external power supply". ►Used in various countries (not US) 	
KT-14001-002R		Power Supply (non-US)	<ul style="list-style-type: none"> ►Discontinued 12/2008, now use 50-14000-256R, 50-14000-257R, 50-14000-258R, or 50-14000-259R depending on country. ►For use in European countries ►Same as KT-14001-001R, but doesn't include AC Line Cord 	
KT-14001-003R		Power Supply (Japan)	<ul style="list-style-type: none"> ►Discontinued 5/2009, now use 50-14000-253R ►For use in Japan ►Same as KT-14001-001R, but uses different AC Line Cord 	
50-14000-010R		Power Supply (Japan)	<ul style="list-style-type: none"> ►100V/50Hz - For use in Japan only ►Discontinued 2/1/08 - now use KT-14001-003R 	
50-14000-009R		Power Supply (non-US)	<ul style="list-style-type: none"> ►220V/50Hz - For use in certain European countries (not US) ►Discontinued 4/15/08 - now use KT-14001-002R 	
PWRS-14000-058R		Power Supply (Universal)	<ul style="list-style-type: none"> ►100-250 VAC,5.2VDC,2A ►Energy Star Compliant ►Can be used as alternative to PWRS-14000-25xR power supplies. 	23844-00-00
50-14000-058R		Power Supply (Universal for non-EU countries)	<ul style="list-style-type: none"> ►Discontinued 2/2012, now use PWRS-14000-058R ►100-240 VAC - Can be used in all Non-EU countries. Use PWRS-14000-058R in EU countries. ►5VDC, 2A 	23844-00-00
23844-00-00R		AC Line Cord		