



8-Port Fast Ethernet PoE+ Switch

4 x PoE IEEE 802.3at/af Power-over-Ethernet (PoE+/PoE) ports, 4 x Standard RJ45 Ports, Endspan, Desktop, 19" Rackmount

Part No.: **561075**

Save installation time and money with PoE.

The Intellinet 8-Port Fast Ethernet PoE+ Switch (561075) is designed to pass both data and electrical power to a number of PoE-compatible devices via standard Cat5e or Cat6 network cables. Equipped with eight Fast Ethernet ports (four of which support 802.3at/af PoE/PoE+), this switch can power wireless LAN access points and bridges, VoIP phones, IP video cameras and more while delivering network speeds of up to 100 Mbps.

Power over Ethernet 802.3at

The Intellinet 8-Port Fast Ethernet PoE+ Switch supports the IEEE 802.3at protocol and is designed to inject up to 30 watts of power per port*. IEEE802.3af- or IEEE802.3at-compliant devices attached to the switch require no additional power, thus eliminating the time and expense of electrical rewiring and minimizing the unsightly clutter caused by power supplies and adapters in awkward places such as ceilings and walls. Any mix of PoE and non-PoE devices is supported, and thanks to its short-circuit, overload and high-voltage protection function, your equipment is well protected. For devices that are not 802.3at/af compliant (legacy wireless access points or network cameras), we suggest use of an Intellinet PoE/PoE+ Splitter.

* Total PoE budget for this switch is 70 watts. Per-port average power distribution is 17.5 watts; maximum per-port power usage cannot exceed 30 watts.

Features:

- Provides power and data connection for up to four PoE network devices
- Save time and money by delivering data and power via existing network cables
- For use on desktop or mounted in standard 19" rack
- 10/100 auto-sensing ports automatically detect optimal network speeds
- Four IEEE 802.3at/af-compliant RJ45 PoE/PoE+ output ports
- PoE power budget of 70 watts
- Supports IEEE 802.3at and IEEE 802.3af-compliant PoE devices (wireless access points, VoIP phones, IP cameras)
- Supports IEEE 802.3at/af detection and short circuit, overload and high-voltage protection
- Complies with the IEEE 802.3az (Energy Efficient Ethernet EEE) specification
- All RJ45 ports with Auto-MDIX (auto uplink) support
- Store and forward switching architecture
- IEEE 802.3x flow control for full duplex
- Supports up to 2K MAC address entries

- 768 kBytes buffer memory
- Desktop-size metal case
- Includes 19" rackmount brackets
- Three-Year Warranty

Specifications:

Standards

- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3af (Power over Ethernet 802.3at Type 1)
- IEEE 802.3at (Power over Ethernet 802.3at Type 2)
- IEEE 802.3az (Energy Efficient Ethernet EEE)
- IEEE 802.3u (100Base-TX Fast Ethernet)
- IEEE 802.3x (flow control, for full duplex mode)

General

- Media support:
 - 10Base-T Cat3, 4, 5 UTP/STP RJ45
 - 100Base-TX Cat5 UTP/STP RJ45
- Packet filter/forwarding rate:
 - 148,800 pps (100 Mbps)
 - 14,880 pps (10 Mbps)
- MAC address table: 2K entries
- Buffer memory: 768 kBytes
- Backplane speed: 1.6 Gbps
- Switch architecture: store and forward
- Certifications: FCC Class A, CE

LEDs

- PoE
- Power
- Link/activity

Power

- Input: 100 – 240 VAC, 50 – 60 Hz
- Power consumption: 80 watts (maximum)

Environmental

- Metal housing
- Dimensions: 280 (L) x 179 (W) x 44 (H) [mm] / 11.02 (L) x 7.05 (W) x 1.73 (H) [in.]
- Weight: 1.5 kg (3.3 lbs.)
- Operating temperature: 0 – 40°C (32 – 104°F)
- Operating humidity: 10 – 90% RH, non-condensing
- Storage temperature: -10 – 70°C (14 – 158°F)

Package Contents

- 8-Port Fast Ethernet PoE+ Switch

- 19" rackmount brackets
- Power cable
- Instructions

