

Product datasheet

Specifications



APC Symmetra 4-16kVA Battery Module

SYBATT

EAN Code: 0731304073642

Overview

Presentation Extended run power protection for servers, networks, and telecommunications

Main

Product or component type Battery accessory

Number of cables 1.0

Battery type Lead-acid battery

Range of product Symmetra Battery Systems

Batteries & Runtime

Battery location Internal battery

Number of battery free slots 0

Number of battery filled slots 0

Device mounting Enclosed battery cartridge

Battery voltage 120 V

Number of battery replacement quantity 1

Physical

Colour Beige

Height 150 mm

Width 229 mm

Depth 508 mm

Product weight 29.55 kg

Mounting mode Not rack-mountable

Output

Battery capacity 7 Ah

Environmental

Ambient air temperature for operation 0...40 °C

Operating altitude 0...10000 ft

Relative humidity 0...95 %

Ambient air temperature for storage -15...45 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|------------------|-------------|
| Storage altitude | 0...15240 m |
|------------------|-------------|

| | |
|---------------------------|----------|
| Storage Relative Humidity | 0...95 % |
|---------------------------|----------|

Packing Units

| | |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
|------------------------|-----|

| | |
|------------------------------|---|
| Number of Units in Package 1 | 1 |
|------------------------------|---|

| | |
|------------------|---------|
| Package 1 Height | 43.9 cm |
|------------------|---------|

| | |
|-----------------|-------|
| Package 1 Width | 79 cm |
|-----------------|-------|

| | |
|------------------|-------|
| Package 1 Length | 33 cm |
|------------------|-------|

| | |
|------------------|----------|
| Package 1 Weight | 31.36 kg |
|------------------|----------|

Logistical informations

| | |
|-------------------|----|
| Country of origin | PH |
|-------------------|----|

Contractual warranty

| | |
|----------------------|----|
| Warranty (in months) | 24 |
|----------------------|----|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

| | |
|--|---|
| Total lifecycle Carbon footprint | 104 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 94 kg CO2 eq. |
| Carbon footprint of the distribution phase [A4] | 2 kg CO2 eq. |
| Carbon footprint of the installation phase [A5] | 0 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 9 540 kg CO2 eq. |
| Carbon footprint of the end-of-life phase [C1 to C4] | 2 kg CO2 eq. |
| Environmental Disclosure | Product Environmental Profile |

Use Better



Materials and Substances

| | |
|--|--|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant By Exemption |
| REACH Regulation | Reference contains Substances of Very High Concern above the threshold |

Use Longer



Lifetime extension

| | |
|--------|----|
| Repair | No |
|--------|----|

Use Again



Repack and remanufacture


| | |
|---------------------------------|---|
| Recyclability potential, in % | 66 |
| End of life manual availability | End of Life Information |
| Take-back | No |
| WEEE Label |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Image of product / Alternate images

Alternative





