

DIGITUS 1.25 Gbps copper SFP-module, RJ45

DN-81005**EAN 4016032389484****1.25 Gbps Copper SFP Module, RJ45 10/100/1000Base-T, up to 100m**

The DIGITUS® Mini GBIC (SFP) transceiver modules offer the highest quality and reliability. The module offers a perfect opportunity for you to extend your Gigabit network switch with a free SFP Uplink Port around an additional RJ45 connection. Thanks to the hot-plug capability, you can install the module without any interruption to the network traffic or restart of the device. In addition, conformity with the MSA (Multi Source Agreement) standard provides compatibility with the current network switch manufacturers.

The plug and play extension for your network switch

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Compatible with the following manufacturers: Allied Telesis, Allnet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon, Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik, ENTERASYS, RIVERSTONE, Unifi, Ubiquiti, ZyXEL, ZTE
- Up to 1.25 Gbps bidirectional maximum data rate

- Compliant to IEEE 802.3z Gigabit Standard
- High quality and excellent reliability
- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant
- Hot pluggable - installation possible while in operation
- Auto MDI/MDI-X
- Connection: 1x RJ45, CAT 5
- Distance: up to 100 m
- Operating temperature: 0 °C ~ 70 °C
- Mode: Copper
- Connector: RJ45
- Distance (km): 0.1
- DDM Support: no
- Manufacturer compatibility: Universal (MSA)
- Ethernet speed: Gigabit

Package contents

- SFP module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	120	7.00	25.40	39.40	55.00	55,041.80
Packaging Unit Inside	30	1.75	7.00	20.00	30.00	4,200.00
Packaging Unit Single	1	0.06	3.20	9.30	12.00	357.12
Net single without Packaging	1	0.02	1.50	1.50	7.00	0.00



SP Modules								
Product Name	SKU Code	Speed	Full Bezel	Distance	Connector	Viewing Ang.	Operating Temperature	Industrial Version
200-001	AV100000001	100 MHz	Yes	270°	12-Medium Duplex	170°/180°	-30 to +70 °C	✓
200-002	AV100000002	100 MHz	Yes	270°	12-Beginner Duplex	70°/180°/180°	-30 to +70 °C	✓
200-003	AV100000010	100 MHz	Yes	270°	12-Beginner Single	70°/180°/180°	-30 to +70 °C	✓
200-004	AV100000012	100 MHz	Yes	270°	12-Beginner Single	70°/180°/180°	-30 to +70 °C	✓
Signal								
200-006	AV100000001	120 MHz	Yes	330°	12-Medium Duplex	180°/180°	-30 to +70 °C	✓
200-007	AV100000002	120 MHz	Yes	330°	12-Beginner Duplex	170°/180°	-30 to +70 °C	✓
200-008	AV100000010	120 MHz	Yes	330°	12-Beginner Single	70°/180°/180°	-30 to +70 °C	✓
200-009	AV100000012	120 MHz	Yes	330°	12-Beginner Single	70°/180°/180°	-30 to +70 °C	✓
200-010	AV100000001	120 MHz	Yes	330°	12-Beginner Duplex	180°/180°	-30 to +70 °C	✓
RGB								
200-006	AV100000010	120 MHz	Yes	330°	12-Medium Duplex	180°/180°	-30 to +70 °C	✓
200-007	AV100000012	120 MHz	Yes	330°	12-Beginner Duplex	170°/180°	-30 to +70 °C	✓
Full Bezel								
200-011	AV100000001	100 MHz	Yes	270°	12-Beginner Duplex	70°/180°/180°	-30 to +70 °C	✓
200-012	AV100000002	100 MHz	Yes	270°	12-Beginner Duplex	70°/180°/180°	-30 to +70 °C	✓
200-013	AV100000010	100 MHz	Yes	270°	12-Beginner Single	70°/180°/180°	-30 to +70 °C	✓
200-014	AV100000012	100 MHz	Yes	270°	12-Beginner Single	70°/180°/180°	-30 to +70 °C	✓
200-015	AV100000001	120 MHz	Yes	330°	12-Beginner Duplex	170°/180°	-30 to +70 °C	✓
200-016	AV100000002	120 MHz	Yes	330°	12-Beginner Duplex	170°/180°	-30 to +70 °C	✓
200-017	AV100000010	120 MHz	Yes	330°	12-Beginner Single	70°/180°/180°	-30 to +70 °C	✓
200-018	AV100000012	120 MHz	Yes	330°	12-Beginner Single	70°/180°/180°	-30 to +70 °C	✓

