

1-Port 10G Open SFP+ Network Card - PCIe - Intel Chip - MM/SM

StarTech ID: PEX10000SFPI



This fiber network card delivers reliable, high-performance network connectivity, by adding an open SFP+ slot to your server or high-powered workstation. It provides an easy and cost-effective way to upgrade your server or workstation to a 10 Gigabit fiber network using the SFP+ module of your choice and gives you the flexibility to use either multimode or single-mode fiber.

Increase your network speed

Several factors drive the need for more bandwidth in your network infrastructure. An increase in the number of network users and data-intensive applications, such as multimedia streaming and large file transfers all contribute to the need for more bandwidth in your network infrastructure. This fiber NIC lets you take advantage of the increased speed and stability of a 10 Gigabit network, with data transfers of up to 10Gbps.

Add scalable network connections to your server or workstation

The fiber NIC is compatible with most 10GbE SFP+ transceivers. This gives you flexible and scalable configuration options for connecting your computer directly to a fiber network, at greater distances.

The card features an open SFP+ slot with support for one interchangeable 10GBase SFP+ module. This gives you the option to use the fiber transceiver module that best suits your network needs based on distance and connector type. StarTech.com offers a variety of SFP+ transceiver modules including the SFP10GLRST [single-mode SFP+](#) the SFP10GLRMST [multi-mode SFP+](#), and SFP10GSRST [multimode LC with DDM](#).

In addition, StarTech.com [SFP+ Cables](#) provide a dependable solution for linking telecom and data communications equipment, such as routers and switches.

Enhance your network capabilities

The 10 Gigabit network card features the Intel® 82599 chipset, delivering the power, performance and

enhanced capabilities you need for reliable network connections to your server or computer. The Intel chip offers many advanced features including Intel® Virtualization Technology for Connectivity, PXE network boot support and up to 15K jumbo frame support.

The PEX10000SFPI is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Add 10Gbps network connectivity to file or application servers and high-performance workstations
- Transmit full 10 Gigabit network speeds to a remote terminal over longer distances than copper cabling
- Supports secure setups - a direct fiber connection means no electronic interference, which can be a problem with RJ45 network cards
- Upgrade your onboard network adapter to 10 Gigabit SFP+, for faster communication
- Create a video / audio editing console with 10Gbps access to network storage
- Ideal for remote embedded industrial monitoring systems, and high-speed video surveillance

Features

- Add a 10GbE SFP+ slot to your server or workstation for fast, high bandwidth connectivity, compatible with SR or LR transceivers
- Compatible with multimode or single-mode fiber
- Intel 82599 chipset with Intel Virtualization Technology for Connectivity
- PXE network boot support
- Compliant with IEEE 802.3ae (10GBASE-LR/SR only) and IEEE 802.3aq (10GBASE-LRM)
- Compliant with PCI Express Rev 2.0 specification, using PCIe x4 (or higher) slot
- Up to 15K jumbo frame support

Technical Specifications

Warranty	2 Years
Bus Type	PCI Express
Card Type	Standard Profile (LP bracket incl.)
Chipset ID	Intel 82599
Industry Standards	IEEE 802.3ae (10GBASE-LR/SR only), IEEE 802.3aq (10GBASE-LRM) PCI Express Rev 2.0, using PCIe x8 (or higher) slot
Interface	Fiber (10 Gigabit Ethernet)
Ports	1
Compatible Networks	10 Gbps
Full Duplex Support	Yes
Jumbo Frame Support	15K max.
Maximum Data Transfer Rate	10 Gbps
Supported Protocols	IEEE 802.3ad (Link Aggregation) IEEE 802.3x (Flow Control Support) IEEE 802.1Q (VLAN tagging)
Connector Type(s)	1 - PCI Express x8 Male
Internal Ports	1 - SFP+ Slot Female
OS Compatibility	Windows® 7, 8, 8.1, 10 Windows Server® 2008 R2, 2012, 2012 R2, 2016 Linux 2.6.24 to 4.4.x <i>LTS Versions only</i>
Humidity	20% ~ 80% RH
Operating Temperature	5°C to 50°C (41°F to 122°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Color	Black
Product Height	4.7 in [120 mm]
Product Length	5.3 in [135 mm]
Product Weight	3.6 oz [102 g]
Product Width	0.7 in [18 mm]
Shipping (Package) Weight	6.3 oz [178 g]
Included in Package	1 - 10G open SFP+ fiber network card
Included in Package	1 - low-profile bracket
Included in Package	1 - quick-start guide

Certifications, Reports and Compatibility

