

PRODUCT FAMILY DATASHEET

TubeKIT +

Mobile LED batten luminaire



AREAS OF APPLICATION

- Indoor applications
- Utility room

PRODUCT BENEFITS

- Up to 65 % energy savings (compared to T8 fluorescent lamps with CCG)
- Extremely robust
- Can be rotated and swiveled for optimum illumination



TECHNICAL DATA

Product description	Electrical data			Photometrical data				Dimensions & weight			Colors & materials
	Nominal wattage	Nominal voltage	Mains frequency	Color temperature	Luminous flux	Light color (designation)	Color rendering index Ra	Length	Width	Height	Body material
TubeKIT+ 8 W 830 3000 K	8.90 W	220...240 V	50/60 Hz	3000 K	720 lm	Warm White	>80	600.0 mm	35.0 mm	86.0 mm	Plastic
TubeKIT+ 8 W 840 4000 K	8.90 W	220...240 V	50/60 Hz	4000 K	800 lm	Cool White	>80	600.0 mm	35.0 mm	86.0 mm	Plastic

Product description	Product color	Cover material	Capabilities		Certificates & standards	
			Dimmable	Type of connection	Protection class	Type of protection
TubeKIT+ 8 W 830 3000 K	White	Plastic	No	Plug, EU	II	IP20
TubeKIT+ 8 W 840 4000 K	White	Plastic	No	Plug, EU	II	IP20

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899971431	TubeKIT+ 8 W 830 3000 K	Shipping carton box 8	690 mm x 245 mm x 270 mm	45.64 dm ³	4210.00 g
4052899971448	TubeKIT+ 8 W 840 4000 K	Shipping carton box 8	690 mm x 245 mm x 270 mm	45.64 dm ³	4210.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.