

## 8-Port Rack-Mount PDU with C13 Outlets - 16 A - 2m Power Cord (BS 1363) - 1U

**Product ID:** PDU08C13GB



This rack-mount PDU features eight C13 outlets and you can install it into 1U of rack space to power your rack-mounted equipment.

Unlike some rack power solutions that mount awkwardly if at all, this rack-mount PDU is EIA-310D compliant which ensures a secure and tidy installation into any 19" rack with 1U of available space. Mounting screws and cage nuts are also included to ensure you have everything you need, saving you time and hassle.

For maximum compatibility with your devices, this PDU features C13 outlets which are ideal for a wide range of globally distributed devices including I.T equipment, office equipment, measuring instruments and medical devices. Plus, with a total of eight C13 outlets, the PDU can distribute power to your entire rack.

In the event of random energy surges that can occur during power outages or other anomalies, this PDU prevents costly damages to your equipment with a built-in dual circuit breaker, ensuring your equipment is protected.

The housing of this PDU is also constructed of rugged steel to provide maximum durability in any environment.

The PDU08C13GB is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Note: Although the PDU can provide 16 amps of power to be shared across eight outlets, due to regional limitations, the cord provided is only rated at 13 amps. A user supplied cord and capable outlet would be required to attain the full 16 amp rating.

### Certifications, Reports and Compatibility



## Applications

- Add eight easily accessible power outlets to your rack
- Provide power to equipment with C13 power plugs

## Features

- Ensure hassle-free installation with a 1U EIA-310D compliant PDU
- Get wide device compatibility with a PDU that features C13 outlets
- 6.6 ft. (2 m) C19 to BS 1363 power cord included
- Protect your equipment with the dual circuit breaker that's built into this PDU
- Solid steel chassis for durability
- 1U rack-mount design

---

### Hardware

Warranty	2 Years
Form Factor	Horizontal
Number of Power Outlets	8
Rack-Mountable	Yes

---

### Performance

General Specifications	Surge Protection: 3600 Joules
	Phase Power: Single phase power adapter
	Power cord included: 10 ft [3 m] C19 to BS 1363
Maximum Total Current	16A
Maximum Total Current Draw per Phase	16A
Regulatory Derated Input Current (North America)	13A
Nominal Input Voltage	110V - 240V
Nominal Output Voltage	110V - 240V
Maximum Output Voltage	240V

Load Capacity 3120 VA

---

**Connector(s)**

Input Connector(s) 1 - IEC C20 (16A, 3 conductor) Power

Output Connectors 8 - IEC C13 (10A, 3 conductor) Power Receptacle

---

**Power**

Input Voltage 110V-240V AC

---

**Physical Characteristics**

Material Steel

Product Length 3.9 in [10.0 cm]

Product Width 18.9 in [48.0 cm]

Product Height 1.7 in [4.4 cm]

Weight of Product 4.4 lb [2.0 kg]

---

**Packaging Information**

Package Quantity 1

Package Length 21.7 in [55.0 cm]

Package Width 7.5 in [19.0 cm]

Package Height 3.2 in [8.2 cm]

Shipping (Package) Weight 4.9 lb [2.2 kg]

---

**What's in the Box**

Included in Package

- 1 - rack-mount PDU
- 1 - 6.6 ft [2 m] C19 to BS 1363 power cord
- 4 - M5 screws
- 4 - M5 cage nuts
- 1 - instruction manual

---

**Warranty**

Information

Warranty

2 Years

---

***\*Product appearance and specifications are subject to change without notice.***

