

DIGITUS DisplayPort Connection Cable

DB-340100-020-S
EAN 4016032292142



DisplayPort connection cable, DP M/M, 2.0m, w/interlock, DP 1.2, Ultra HD 4K, bl

This high performance HD digital audio and video cable for example is used to connect a PC or notebook with DisplayPort interface to a monitor with DisplayPort interface.

Save and reliable connection based on the snap fastener at connector

- Supported Video format: 4K/2K@24Hz, 4K/2K@30Hz or 4K/2K@60Hz
- Supported Video Resolution: 4096 x 2160p; 1920 x 1080p
- Maximal bandwidth: 21,6 Gbps
- HBR-Version/transfer mode: HBR2 (5,40 Gbit/s per lane)
- HDCP-Version: HDCP 1.3
- Assortment: DisplayPort Cables

- AWG: 28
- Color cable: black
- Color connector: black
- Connector 1: DP, plug
- Connector 2: DP, plug
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.2
- Ferrite filter: none
- HDTV Standard: Ultra HD 4K
- Hoods: molded
- Interlock: Snap fastener
- Wire material: CU
- Length: 2 m
- AOC - Active Optical Cable: no
- Shielding: Double shielding

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	40	1.10	56.00	29.00	39.00	63,336.00
Packaging Unit Inside	10	0.28	27.00	27.00	17.00	12,393.00
Packaging Unit Single	1	0.03	5.00	7.50	23.50	881.25
Net single without Packaging	1	0.20	3.00	5.00	20.00	0.00

More images:



