


REQUIREMENTS:

1:100% short,open and miss wire test.
2:Insulation resistance:DC300V 10MΩ(Min)
Conduction resistance 5Ω(Max)

⑥	OUTER MOLDED	BLACK 45P PVC	0.038	KG
⑤	INTER MOLDED	LDPE	0.021	KG
④	SCREW	#4-40UNC 2.3*45.5MM,BLACK PVC	4	PCS
③	CONNECTOR	HDB 15PIN/MALE BLUE INSULATOR,NICKEL PLATED SHELL, GOLD PLATED PIN	2	PCS
①	CABLE	(1C*28#+D+AL+PVC)*3C+6C*28#+AL+D+B JACKET:BLACK PVC OD:8.0±0.15 MARKING:AWM STYLE 2919 80°C 30V LOW VOLTAGE COMPUTER CABLE ROHS COMPLIANT	10	M
NO.	MATERIAL	DESCRIPTIONG	QTY.	UNIT

PIN OUT



Litemref	Quantity	Title/Name,designation,material,dimension etc	Article No./Reference
Designed by ACHY	HELEN	Approved by - date MARCH 6,2012	File name HDB15PIN M/M L=10M Date MARCH 6,2012 Scale FREE

32 1100	32 1100	1	Sheet 1/1
---------	---------	---	--------------