






SCALE 1/1



Specification :

Material :

- Plastic Housing : ABS + PC, UL 94V-0.
- Jack Bracket Set : Polycarbonate, UL 94-HB, Transparent color.
- RJ45 Jack Contact material & finished :
 - Phosphor Bronze with 50-60 micro-inch Nickel plated.
 - Contact area : Min. 3 mm 50 micro-inch Gold plated.

Performance :

- Insertion Force : 900 gms for 8 contacts.
- Retention Strength : 7.7 kgs between Jack and Plug.
- Operation Temperature : -40°C to 80°C.
- Durability Jack : 750 cycles Plug-Jack mating and unmating test, insertion cycles at 20 cycles/minute max. Contact resistance test per 100 cycles.
- The Cat.5e performance is in compliance with the ANSI/TIA/EIA 568 B.2 standard.

Remark : JE315A-CE/XX
(1)

(1) XX : Housing Color
BK=Black, WH=White

GENERAL TOLERANCE OF DIMENSIONS X.XXX ±0.005 X.XX ±0.05 X.X ±0.1	DRAWING	11.JAN.2007	Michelle		
	CHECK	12.JAN.2007	Jaimy		
	APPROVAL	12.JAN.2007	Jaimy		
		DATE	NAME	ITEM NO.: JE315A-CE/XX	
	SCALE	1/1 (A4)	UNIT	mm	DES.: CAT.5e Inline Coupler, Unshield
			DRAWING NO. JE315A-CE-XX(SA3)		
			DRAWING CLASSIFICATION	S	SHEET 1 OF 1
					A3