

Item No. 86110

Delock Media Converter 10/100/1000Base-T to 100/1000Base-X SFP

Description

This Gigabit Ethernet Media Converter by Delock can be used to expand a network with an optical fiber interface. In the SFP slot, an optional 100 Mb/s or 1 Gb/s SFP module can be used.



Specification

- Connectors:
 - 1 x SFP slot for 100/1000Base-X SFP module (SFP module not included)
 - 1 x RJ45 jack for 10/100/1000 Mb/s Base-T
 - 1 x DC female 5.5 x 2.1 mm (power)
- Data transfer rate up to 1 Gb/s
- 6 LEDs for status monitoring
- DIP-switch for configuration of LFP (Link Fault Pass Through)
- Supports IEEE 802.3 / 802.3u / 802.3ab / 802.3z
- Power consumption: 2.5 W
- Metal housing
- Fanless
- Operating temperature: 0 °C ~ 55 °C
- Dimensions (LxWxH): ca. 94 x 70 x 26 mm

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.2 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:
 - inside: ø ca. 2.1 mm
 - outside: ø ca. 5.5 mm
 - length: ca. 9.5 mm

System requirements

- 100/1000Base-X SFP module
- Device with one free RJ45 port

Package content

- Media Converter
- Power supply
- User manual

Additional Information

EAN: 4043619861101

Country of origin: China

Package: White Box



Images



| Interface | |
|---------------------------|---|
| Output: | 1 x SFP slot |
| Input: | 1 x 5 V DC female 5,5 mm x 2,1 mm 1 x RJ45 jack |
| Technical characteristics | |
| Data transfer rate: | Fast Ethernet up to 100 Mbps Gigabit Ethernet up to 1 Gbps |
| Physical characteristics | |
| Housing colour: | black |
| Housing material: | metal |
| Length: | 94 mm |
| Width: | 70 mm |
| Height: | 26 mm |
| Power supply | |
| Type: | Euro wall power supply |
| Input: | AC 100 - 240 V / 50 - 60 Hz / 0.25 A |
| Output: | 5 V / 1.25 A |
| Connector: | DC male 5.5 mm x 2.1 mm |