

PRODUCT FAMILY DATASHEET

Decorative LED ceiling luminaires illuminated by LED strips

AREAS OF APPLICATION

- For indoor use only
- Decorative domestic lighting
- Ceiling and wall surface mounting

PRODUCT BENEFITS

- Very homogenous light
- Easy and quick installation

PRODUCT FEATURES





- Ceiling luminaire with advanced LED technology
- Housing material: aluminum
- Diffuser made of opal polycarbonate



TECHNICAL DATA

Product description	Electrical data				Photometrical data				Dimensions & weight		
	Operating mode	Nominal wattage	Nominal voltage	Mains frequency	Color temperature	Luminous flux	Light color (designation)	Color rendering index Ra	Length	Width	Height
LED STRIPE TWIN 600+600 18 W 830	Integrated LED driver	18.00 W	220...240 V	50/60 Hz	3000 K	1010 lm	Warm White	>80	610.0 mm	100.0 mm	60.0 mm
LED STRIPE DUO 600+800 20 W 830	Integrated LED driver	20.00 W	220...240 V	50/60 Hz	3000 K	1160 lm	Warm White	>80	900.0 mm	100.0 mm	60.0 mm
LED STRIPE FLEX 500+700 15 W 830	Integrated LED driver	15.00 W	220...240 V	50/60 Hz	3000 K	900 lm	Warm White	>80	1060 mm	120.0 mm	135.0 mm
LED STRIPE TRIO 600+600+600 24 W 830	Integrated LED driver	24.00 W	220...240 V	50/60 Hz	3000 K	1450 lm	Warm White	>80	900.0 mm	120.0 mm	60.0 mm

Product description	Colors & materials			Temperatures & operating conditions	Lifespan	Capabilities		Certificates & standards	
	Body material	Product color	Cover material	Ambient temperature range	Lifespan	Dimmable	Type of connection	Protection class	Type of protection
LED STRIPE TWIN 600+600 18 W 830	Aluminum	Steel	Polycarbonate (PC)	-30...70 °C	20000 h	No	Terminal	II	IP20
LED STRIPE DUO 600+800 20 W 830	Aluminum	Steel	Polycarbonate (PC)	-30...70 °C	20000 h	No	Terminal	II	IP20
LED STRIPE FLEX 500+700 15 W 830	Aluminum	Steel	Polycarbonate (PC)	-30...70 °C	20000 h	No	Terminal	II	IP20
LED STRIPE TRIO 600+600+600 24 W 830	Aluminum	Steel	Polycarbonate (PC)	-30...70 °C	20000 h	No	Terminal	II	IP20



LED STRIPE TWIN 600+600 18 W 830

LED STRIPE DUO 600+800 20 W 830

LED STRIPE FLEX 500+700 15 W 830

LED STRIPE TRIO 600+600+600 24 W
830

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075054974	LED STRIPE TWIN 600+600 18 W 830	Shipping carton box 8	660 mm x 275 mm x 325 mm	58.99 dm ³	7570.00 g
4058075054998	LED STRIPE DUO 600+800 20 W 830	Shipping carton box 8	950 mm x 275 mm x 325 mm	84.91 dm ³	9165.00 g

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075055018	LED STRIPE FLEX 500+700 15 W 830	Shipping carton box 8	815 mm x 315 mm x 625 mm	160.45 dm ³	10580.00 g
4058075055032	LED STRIPE TRIO 600+600+600 24 W 830	Shipping carton box 8	950 mm x 315 mm x 325 mm	97.26 dm ³	10537.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.