


Delock Kabel mini Displayport 1.1 Stecker > DVI 24+1 Stecker 1 m

Description

This cable by Delock can be used to connect a display with an DVI port to a PC or a laptop with mini Displayport interface.



ca. 1 m

Specification

- Connectors:
1 x mini Displayport 20 pin male >
1 x DVI 24+1 male with screws
- Chipset: NXP PTN3361
- DVI-D (Single Link), VGA not wired
- Displayport 1.1a specification
- Passive cable (level shifter), suitable only for graphics cards with DP++ output
- Signal direction: mini Displayport input > DVI output
- Cable gauge: 32 AWG
- Cable diameter: ca. 5.5 mm
- Twisted-pair cabling
- Copper conductor
- Gold-plated connectors
- Triple shielded cable
- Data transfer rate up to 3.96 Gb/s
- Resolution up to 1920 x 1200 @ 60 Hz (depending on the system and the connected hardware)
- Colour: black
- Length incl. connectors: ca. 1 m

System requirements

- One free mini Displayport DP++ female

Package content


- Mini Displayport to DVI cable

Item no. 83988

EAN: 4043619839889

Country of origin: China

Package: Poly bag



Images



General	
Specification:	standard Displayport 1.1
Interface	
connector:	standard 1 x mini Displayport 20 pin male 1 x DVI 24+1 male with screws
Technical characteristics	
Data transfer rate:	standard 3.96 Gb/s
Maximum screen resolution:	standard 1920 x 1200 @ 60 Hz
Physical characteristics	
Cable colour:	standard black
Cable diameter:	standard 5.5 mm
Cable length incl. connector:	standard 1 m
Connector finishing:	standard gold-plated
Pin finishing:	standard gold-plated
Conductor material:	standard copper
Conductor gauge:	standard 32 AWG
Shielding:	standard triple